

R FAQ

Frequently Asked Questions on R
Version 2.6.2007-11-23
ISBN 3-900051-08-9

Kurt Hornik

Table of Contents

1	Introduction	1
1.1	Legalese	1
1.2	Obtaining this document	1
1.3	Citing this document	1
1.4	Notation	1
1.5	Feedback	2
2	R Basics	3
2.1	What is R?	3
2.2	What machines does R run on?	3
2.3	What is the current version of R?	4
2.4	How can R be obtained?	4
2.5	How can R be installed?	4
2.5.1	How can R be installed (Unix)	4
2.5.2	How can R be installed (Windows)	5
2.5.3	How can R be installed (Macintosh)	5
2.6	Are there Unix binaries for R?	6
2.7	What documentation exists for R?	6
2.8	Citing R	8
2.9	What mailing lists exist for R?	9
2.10	What is CRAN?	10
2.11	Can I use R for commercial purposes?	10
2.12	Why is R named R?	11
2.13	What is the R Foundation?	11
3	R and S	12
3.1	What is S?	12
3.2	What is S-PLUS?	12
3.3	What are the differences between R and S?	13
3.3.1	Lexical scoping	13
3.3.2	Models	16
3.3.3	Others	16
3.4	Is there anything R can do that S-PLUS cannot?	19
3.5	What is R-plus?	19
4	R Web Interfaces	20

5	R Add-On Packages	22
5.1	Which add-on packages exist for R?	22
5.1.1	Add-on packages in R	22
5.1.2	Add-on packages from CRAN	22
5.1.3	Add-on packages from Omegahat	74
5.1.4	Add-on packages from Bioconductor	77
5.1.5	Other add-on packages	87
5.2	How can add-on packages be installed?	87
5.3	How can add-on packages be used?	87
5.4	How can add-on packages be removed?	88
5.5	How can I create an R package?	89
5.6	How can I contribute to R?	89
6	R and Emacs	90
6.1	Is there Emacs support for R?	90
6.2	Should I run R from within Emacs?	90
6.3	Debugging R from within Emacs	91
7	R Miscellanea	92
7.1	How can I set components of a list to NULL?	92
7.2	How can I save my workspace?	92
7.3	How can I clean up my workspace?	92
7.4	How can I get eval() and D() to work?	92
7.5	Why do my matrices lose dimensions?	93
7.6	How does autoloading work?	93
7.7	How should I set options?	93
7.8	How do file names work in Windows?	94
7.9	Why does plotting give a color allocation error?	94
7.10	How do I convert factors to numeric?	94
7.11	Are Trellis displays implemented in R?	94
7.12	What are the enclosing and parent environments?	95
7.13	How can I substitute into a plot label?	95
7.14	What are valid names?	96
7.15	Are GAMs implemented in R?	96
7.16	Why is the output not printed when I source() a file?	96
7.17	Why does outer() behave strangely with my function?	97
7.18	Why does the output from anova() depend on the order of factors in the model?	97
7.19	How do I produce PNG graphics in batch mode?	98
7.20	How can I get command line editing to work?	98
7.21	How can I turn a string into a variable?	98
7.22	Why do lattice/trellis graphics not work?	99
7.23	How can I sort the rows of a data frame?	99
7.24	Why does the help.start() search engine not work?	99
7.25	Why did my .Rprofile stop working when I updated R?	99
7.26	Where have all the methods gone?	99
7.27	How can I create rotated axis labels?	100

7.28	Why is <code>read.table()</code> so inefficient?	100
7.29	What is the difference between package and library?	100
7.30	I installed a package but the functions are not there	101
7.31	Why doesn't R think these numbers are equal?	101
7.32	How can I capture or ignore errors in a long simulation?	101
7.33	Why are powers of negative numbers wrong?	101
7.34	How can I save the result of each iteration in a loop into a separate file?	102
7.35	Why are <i>p</i> -values not displayed when using <code>lmer()</code> ?	102
7.36	Why are there unwanted lines between polygons in PDF output viewed in Adobe Reader?	102
7.37	Why does backslash behave strangely inside strings?	102
8	R Programming	104
8.1	How should I write summary methods?	104
8.2	How can I debug dynamically loaded code?	104
8.3	How can I inspect R objects when debugging?	104
8.4	How can I change compilation flags?	104
8.5	How can I debug S4 methods?	104
9	R Bugs	105
9.1	What is a bug?	105
9.2	How to report a bug	105
10	Acknowledgments	108

1 Introduction

This document contains answers to some of the most frequently asked questions about R.

1.1 Legalese

This document is copyright © 1998–2007 by Kurt Hornik.

This document is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2, or (at your option) any later version.

This document is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

A copy of the GNU General Public License is available via WWW at

<http://www.gnu.org/copyleft/gpl.html>.

You can also obtain it by writing to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, U.S.A.

1.2 Obtaining this document

The latest version of this document is always available from

<http://CRAN.R-project.org/doc/FAQ/>

From there, you can obtain versions converted to [plain ASCII text](#), [DVI](#), [GNU info](#), [HTML](#), [PDF](#), [PostScript](#) as well as the [Texinfo source](#) used for creating all these formats using the [GNU Texinfo system](#).

You can also obtain the R FAQ from the ‘doc/FAQ’ subdirectory of a CRAN site (see [Section 2.10 \[What is CRAN?\]](#), [page 10](#)).

1.3 Citing this document

In publications, please refer to this FAQ as Hornik (2007), “The R FAQ”, and give the above, *official* URL and the ISBN 3-900051-08-9:

```
@Misc{
  author      = {Kurt Hornik},
  title       = {The {R} {FAQ}},
  year        = {2007},
  note        = {{ISBN} 3-900051-08-9},
  url         = {http://CRAN.R-project.org/doc/FAQ/R-FAQ.html}
}
```

1.4 Notation

Everything should be pretty standard. ‘R>’ is used for the R prompt, and a ‘\$’ for the shell prompt (where applicable).

1.5 Feedback

Feedback via email to Kurt.Hornik@R-project.org is of course most welcome.

In particular, note that I do not have access to Windows or Macintosh systems. Features specific to the Windows and Mac OS X ports of R are described in the “[R for Windows FAQ](#)” and the “[R for Mac OS X FAQ](#)”. If you have information on Macintosh or Windows systems that you think should be added to this document, please let me know.

2 R Basics

2.1 What is R?

R is a system for statistical computation and graphics. It consists of a language plus a run-time environment with graphics, a debugger, access to certain system functions, and the ability to run programs stored in script files.

The design of R has been heavily influenced by two existing languages: Becker, Chambers & Wilks' S (see [Section 3.1 \[What is S?\]](#), page 12) and Sussman's [Scheme](#). Whereas the resulting language is very similar in appearance to S, the underlying implementation and semantics are derived from Scheme. See [Section 3.3 \[What are the differences between R and S?\]](#), page 13, for further details.

The core of R is an interpreted computer language which allows branching and looping as well as modular programming using functions. Most of the user-visible functions in R are written in R. It is possible for the user to interface to procedures written in the C, C++, or FORTRAN languages for efficiency. The R distribution contains functionality for a large number of statistical procedures. Among these are: linear and generalized linear models, nonlinear regression models, time series analysis, classical parametric and nonparametric tests, clustering and smoothing. There is also a large set of functions which provide a flexible graphical environment for creating various kinds of data presentations. Additional modules ("add-on packages") are available for a variety of specific purposes (see [Chapter 5 \[R Add-On Packages\]](#), page 22).

R was initially written by [Ross Ihaka](#) and [Robert Gentleman](#) at the Department of Statistics of the University of Auckland in Auckland, New Zealand. In addition, a large group of individuals has contributed to R by sending code and bug reports.

Since mid-1997 there has been a core group (the "R Core Team") who can modify the R source code archive. The group currently consists of Doug Bates, John Chambers, Peter Dalgaard, Robert Gentleman, Kurt Hornik, Stefano Iacus, Ross Ihaka, Friedrich Leisch, Thomas Lumley, Martin Maechler, Duncan Murdoch, Paul Murrell, Martyn Plummer, Brian Ripley, Duncan Temple Lang, Luke Tierney, and Simon Urbanek.

R has a home page at <http://www.R-project.org/>. It is [free software](#) distributed under a GNU-style [copyleft](#), and an official part of the [GNU](#) project ("GNU S").

2.2 What machines does R run on?

R is being developed for the Unix, Windows and Mac families of operating systems. Support for Mac OS Classic ended with R 1.7.1.

The current version of R will configure and build under a number of common Unix platforms including *cpu-linux-gnu* for the i386, alpha, arm, hppa, ia64, m68k, mips/mipsel, powerpc, s390, sparc (e.g., <http://buildd.debian.org/build.php?&pkg=r-base>), and x86_64 CPUs, powerpc-apple-darwin, mips-sgi-irix, rs6000-ibm-aix, and sparc-sun-solaris.

If you know about other platforms, please drop us a note.

2.3 What is the current version of R?

The current released version is 2.6.1. Based on this ‘major.minor.patchlevel’ numbering scheme, there are two development versions of R, a patched version of the current release (‘r-patched’) and one working towards the next minor or eventually major (‘r-devel’) releases of R, respectively. Version r-patched is for bug fixes mostly. New features are typically introduced in r-devel.

2.4 How can R be obtained?

Sources, binaries and documentation for R can be obtained via CRAN, the “Comprehensive R Archive Network” (see [Section 2.10 \[What is CRAN?\]](#), page 10).

Sources are also available via <https://svn.R-project.org/R/>, the R Subversion repository, but currently not via anonymous rsync (nor CVS).

Tarballs with daily snapshots of the r-devel and r-patched development versions of R can be found at <ftp://ftp.stat.math.ethz.ch/Software/R>.

2.5 How can R be installed?

2.5.1 How can R be installed (Unix)

If R is already installed, it can be started by typing `R` at the shell prompt (of course, provided that the executable is in your path).

If binaries are available for your platform (see [Section 2.6 \[Are there Unix binaries for R?\]](#), page 6), you can use these, following the instructions that come with them.

Otherwise, you can compile and install R yourself, which can be done very easily under a number of common Unix platforms (see [Section 2.2 \[What machines does R run on?\]](#), page 3). The file ‘INSTALL’ that comes with the R distribution contains a brief introduction, and the “R Installation and Administration” guide (see [Section 2.7 \[What documentation exists for R?\]](#), page 6) has full details.

Note that you need a FORTRAN compiler or perhaps `f2c` in addition to a C compiler to build R. Also, you need Perl version 5 to build the R object documentations. (If this is not available on your system, you can obtain a PDF version of the object reference manual via CRAN.)

In the simplest case, untar the R source code, change to the directory thus created, and issue the following commands (at the shell prompt):

```
$ ./configure
$ make
```

If these commands execute successfully, the R binary and a shell script front-end called ‘R’ are created and copied to the ‘bin’ directory. You can copy the script to a place where users can invoke it, for example to ‘/usr/local/bin’. In addition, plain text help pages as well as HTML and \LaTeX versions of the documentation are built.

Use `make dvi` to create DVI versions of the R manuals, such as ‘`refman.dvi`’ (an R object reference index) and ‘`R-exts.dvi`’, the “R Extension Writers Guide”, in the ‘`doc/manual`’ subdirectory. These files can be previewed and printed using standard programs such as `xdvi` and `dvips`. You can also use `make pdf` to build PDF (Portable Document Format)

version of the manuals, and view these using e.g. Acrobat. Manuals written in the GNU Texinfo system can also be converted to info files suitable for reading online with Emacs or stand-alone GNU Info; use *make info* to create these versions (note that this requires Makeinfo version 4.5).

Finally, use *make check* to find out whether your R system works correctly.

You can also perform a “system-wide” installation using *make install*. By default, this will install to the following directories:

```
'${prefix}/bin'
    the front-end shell script

'${prefix}/man/man1'
    the man page

'${prefix}/lib/R'
    all the rest (libraries, on-line help system, ...). This is the “R Home Directory”
    (R_HOME) of the installed system.
```

In the above, `prefix` is determined during configuration (typically `/usr/local`) and can be set by running `configure` with the option

```
$ ./configure --prefix=/where/you/want/R/to/go
```

(E.g., the R executable will then be installed into `/where/you/want/R/to/go/bin`.)

To install DVI, info and PDF versions of the manuals, use *make install-dvi*, *make install-info* and *make install-pdf*, respectively.

2.5.2 How can R be installed (Windows)

The `bin/windows` directory of a CRAN site contains binaries for a base distribution and a large number of add-on packages from CRAN to run on Windows 95, 98, ME, NT4, 2000, and XP (at least) on Intel and clones (but not on other platforms). The Windows version of R was created by Robert Gentleman and Guido Masarotto, and is now being developed and maintained by [Duncan Murdoch](#) and [Brian D. Ripley](#).

For most installations the Windows installer program will be the easiest tool to use.

See the [“R for Windows FAQ”](#) for more details.

2.5.3 How can R be installed (Macintosh)

The `bin/macosx` directory of a CRAN site contains a standard Apple installer package inside a disk image named `R.dmg`. Once downloaded and executed, the installer will install the current non-developer release of R. RAqua is a native Mac OS X Darwin version of R with a R.app Mac OS X GUI. Inside `bin/macosx/powerpc/contrib/x.y` there are prebuilt binary packages (for powerpc version of Mac OS X) to be used with RAqua corresponding to the “x.y” release of R. The installation of these packages is available through the “Package” menu of the R.app GUI. This port of R for Mac OS X is maintained by [Stefano Iacus](#). The [“R for Mac OS X FAQ”](#) has more details.

The `bin/macos` directory of a CRAN site contains bin-hexed (`hqx`) and stuffit (`sit`) archives for a base distribution and a large number of add-on packages of R 1.7.1 to run under Mac OS 8.6 to Mac OS 9.2.2. This port of R for Macintosh is no longer supported.

2.6 Are there Unix binaries for R?

The ‘bin/linux’ directory of a CRAN site contains the following packages.

	CPU	Versions	Provider
Debian	i386	stable/oldstable	Johannes Ranke
	amd64	stable/oldstable	Johannes Ranke
Red Hat	i386	FC3/FC4/FC5/FC6	Martyn Plummer
	x86_64	FC3	Brian Ripley
	x86_64	FC4/FC5/FC6	Martyn Plummer
	i386	Enterprise Linux	Matthew P. Cox
SuSE	x86_64	Enterprise Linux	Matthew P. Cox
	i386	7.3/8.0/8.1/8.2	Detlef Steuer
	i586	9.0/9.1/9.2/9.3/10.0/10.1	Detlef Steuer
	x86_64	9.2/9.3/10.0/10.1	Detlef Steuer
Ubuntu	i386	dapper/edgy/feisty	Vincent Goulet
VineLinux	i386	3.2	Susumu Tanimura

Debian packages, maintained by Dirk Eddelbuettel and Doug Bates, have long been part of the Debian distribution, and can be accessed through APT, the Debian package maintenance tool. Use e.g. `apt-get install r-base r-recommended` to install the R environment and recommended packages. If you also want to build R packages from source, also run `apt-get install r-base-dev` to obtain the additional tools required for this. So-called “backports” of the current R packages for the *stable* distribution of Debian are provided by Johannes Ranke, and available from CRAN. Simply add the line

```
deb http://CRAN.R-project.org/bin/linux/debian stable/
```

(feel free to use a CRAN mirror instead of the master) to the file ‘/etc/apt/sources.list’, and install as usual. More details on installing and administering R on Debian Linux can be found at <http://CRAN.R-project.org/bin/linux/debian/README>. These backports should also be suitable for other Debian derivatives. Native backports for Ubuntu are provided by Vincent Goulet.

No other binary distributions are currently publically available via CRAN.

A “live” Linux distribution with a particular focus on R is *Quantian*, which provides a directly bootable and self-configuring “Live DVD” containing numerous applications of interests to scientists and researchers, including several hundred CRAN and Bioconductor packages, the “ESS” extensions for Emacs, the “JGR” Java GUI for R, the Ggobi visualization tool as well as several other R interfaces. The *Quantian* website at <http://dirk.eddelbuettel.com/quantian/> contains more details as well download information.

2.7 What documentation exists for R?

Online documentation for most of the functions and variables in R exists, and can be printed on-screen by typing `help(name)` (or `?name`) at the R prompt, where *name* is the name of the topic help is sought for. (In the case of unary and binary operators and control-flow special forms, the name may need to be quoted.)

This documentation can also be made available as one reference manual for on-line reading in HTML and PDF formats, and as hardcopy via L^AT_EX, see [Section 2.5](#) [How can

R be installed?], page 4. An up-to-date HTML version is always available for web browsing at <http://stat.ethz.ch/R-manual/>.

Printed copies of the R reference manual for some version(s) are available from Network Theory Ltd, at <http://www.network-theory.co.uk/R/base/>. For each set of manuals sold, the publisher donates USD 10 to the R Foundation (see [Section 2.13 \[What is the R Foundation?\]](#), page 11).

The R distribution also comes with the following manuals.

- “An Introduction to R” (`‘R-intro’`) includes information on data types, programming elements, statistical modeling and graphics. This document is based on the “Notes on S-PLUS” by Bill Venables and David Smith.
- “Writing R Extensions” (`‘R-exts’`) currently describes the process of creating R add-on packages, writing R documentation, R’s system and foreign language interfaces, and the R API.
- “R Data Import/Export” (`‘R-data’`) is a guide to importing and exporting data to and from R.
- “The R Language Definition” (`‘R-lang’`), a first version of the “Kernighan & Ritchie of R”, explains evaluation, parsing, object oriented programming, computing on the language, and so forth.
- “R Installation and Administration” (`‘R-admin’`).
- “R Internals” (`‘R-ints’`) is a guide to R’s internal structures. (Added in R 2.4.0.)

Books on R include

P. Dalgaard (2002), “Introductory Statistics with R”, Springer: New York, ISBN 0-387-95475-9, <http://www.biostat.ku.dk/~pd/ISwR.html>.

J. Fox (2002), “An R and S-PLUS Companion to Applied Regression”, Sage Publications, ISBN 0-761-92280-6 (softcover) or 0-761-92279-2 (hardcover), <http://socserv.socsci.mcmaster.ca/jfox/Books/Companion/>.

J. Maindonald and J. Braun (2003), “Data Analysis and Graphics Using R: An Example-Based Approach”, Cambridge University Press, ISBN 0-521-81336-0, <http://www.maths.anu.edu.au/~johnm/>.

S. M. Iacus and G. Masarotto (2002), “Laboratorio di statistica con R”, McGraw-Hill, ISBN 88-386-6084-0 (in Italian), http://www.ateneonline.it/LibroAteneo.asp?item_id=1436.

P. Murrell (2005), “R Graphics”, Chapman & Hall/CRC, ISBN: 1-584-88486-X, <http://www.stat.auckland.ac.nz/~paul/RGraphics/rgraphics.html>.

The book

W. N. Venables and B. D. Ripley (2002), “Modern Applied Statistics with S. Fourth Edition”. Springer, ISBN 0-387-95457-0

has a home page at <http://www.stats.ox.ac.uk/pub/MASS4/> providing additional material. Its companion is

W. N. Venables and B. D. Ripley (2000), “S Programming”. Springer, ISBN 0-387-98966-8

and provides an in-depth guide to writing software in the S language which forms the basis of both the commercial S-PLUS and the Open Source R data analysis software systems. See <http://www.stats.ox.ac.uk/pub/MASS3/Sprog/> for more information.

In addition to material written specifically or explicitly for R, documentation for S/S-PLUS (see [Chapter 3 \[R and S\], page 12](#)) can be used in combination with this FAQ (see [Section 3.3 \[What are the differences between R and S?\], page 13](#)). Introductory books include

P. Spector (1994), “An introduction to S and S-PLUS”, Duxbury Press.

A. Krause and M. Olsen (2005), “The Basics of S-PLUS” (Fourth Edition). Springer, ISBN 0-387-26109-5.

The book

J. C. Pinheiro and D. M. Bates (2000), “Mixed-Effects Models in S and S-PLUS”, Springer, ISBN 0-387-98957-0

provides a comprehensive guide to the use of the **nlme** package for linear and nonlinear mixed-effects models.

As an example of how R can be used in teaching an advanced introductory statistics course, see

D. Nolan and T. Speed (2000), “Stat Labs: Mathematical Statistics Through Applications”, Springer Texts in Statistics, ISBN 0-387-98974-9

This integrates theory of statistics with the practice of statistics through a collection of case studies (“labs”), and uses R to analyze the data. More information can be found at <http://www.stat.Berkeley.EDU/users/statlabs/>.

Last, but not least, Ross’ and Robert’s experience in designing and implementing R is described in Ihaka & Gentleman (1996), “R: A Language for Data Analysis and Graphics”, *Journal of Computational and Graphical Statistics*, **5**, 299–314.

An annotated bibliography (BibTeX format) of R-related publications which includes most of the above references can be found at

<http://www.R-project.org/doc/bib/R.bib>

2.8 Citing R

To cite R in publications, use

```
@Manual{,
  title      = {R: A Language and Environment for Statistical
                Computing},
  author     = {{R Development Core Team}},
  organization = {R Foundation for Statistical Computing},
  address    = {Vienna, Austria},
  year       = 2007,
  note       = {{ISBN} 3-900051-07-0},
  url        = {http://www.R-project.org}
}
```

Citation strings (or BibTeX entries) for R and R packages can also be obtained by `citation()`.

2.9 What mailing lists exist for R?

Thanks to [Martin Maechler](#), there are four mailing lists devoted to R.

R-announce

A moderated list for major announcements about the development of R and the availability of new code.

R-packages

A moderated list for announcements on the availability of new or enhanced contributed packages.

R-help

The ‘main’ R mailing list, for discussion about problems and solutions using R, announcements (not covered by ‘R-announce’ and ‘R-packages’) about the development of R and the availability of new code.

R-devel

This list is for questions and discussion about code development in R.

Please read the [posting guide](#) *before* sending anything to any mailing list.

Note in particular that R-help is intended to be comprehensible to people who want to use R to solve problems but who are not necessarily interested in or knowledgeable about programming. Questions likely to prompt discussion unintelligible to non-programmers (e.g., questions involving C or C++) should go to R-devel.

Convenient access to information on these lists, subscription, and archives is provided by the web interface at <http://stat.ethz.ch/mailman/listinfo/>. One can also subscribe (or unsubscribe) via email, e.g. to R-help by sending ‘subscribe’ (or ‘unsubscribe’) in the *body* of the message (not in the subject!) to R-help-request@lists.R-project.org.

Send email to R-help@lists.R-project.org to send a message to everyone on the R-help mailing list. Subscription and posting to the other lists is done analogously, with ‘R-help’ replaced by ‘R-announce’, ‘R-packages’, and ‘R-devel’, respectively. Note that the R-announce and R-packages lists are gatewayed into R-help. Hence, you should subscribe to either of them only in case you are not subscribed to R-help.

It is recommended that you send mail to R-help rather than only to the R Core developers (who are also subscribed to the list, of course). This may save them precious time they can use for constantly improving R, and will typically also result in much quicker feedback for yourself.

Of course, in the case of bug reports it would be very helpful to have code which reliably reproduces the problem. Also, make sure that you include information on the system and version of R being used. See [Chapter 9 \[R Bugs\]](#), [page 105](#) for more details.

See <http://www.R-project.org/mail.html> for more information on the R mailing lists.

The R Core Team can be reached at R-core@lists.R-project.org for comments and reports.

Many of the R project’s mailing lists are also available via [Gmane](#), from which they can be read with a web browser, using an NNTP news reader, or via RSS feeds. See <http://dir.gmane.org/index.php?prefix=gmane.comp.lang.r> for the available mailing lists, and <http://www.gmane.org/rss.php> for details on RSS feeds.

2.10 What is CRAN?

The “Comprehensive R Archive Network” (CRAN) is a collection of sites which carry identical material, consisting of the R distribution(s), the contributed extensions, documentation for R, and binaries.

The CRAN master site at Wirtschaftsuniversität Wien, Austria, can be found at the URL

<http://CRAN.R-project.org/>

Daily mirrors are available at URLs including

http://cran.at.R-project.org/	(WU Wien, Austria)
http://cran.au.R-project.org/	(PlanetMirror, Australia)
http://cran.br.R-project.org/	(Universidade Federal de Paraná, Brazil)
http://cran.ch.R-project.org/	(ETH Zürich, Switzerland)
http://cran.dk.R-project.org/	(SunSITE, Denmark)
http://cran.es.R-project.org/	(Spanish National Research Network, Madrid, Spain)
http://cran.fr.R-project.org/	(INRA, Toulouse, France)
http://cran.hu.R-project.org/	(Semmelweis U, Hungary)
http://cran.pt.R-project.org/	(Universidade do Porto, Portugal)
http://cran.uk.R-project.org/	(U of Bristol, United Kingdom)
http://cran.us.R-project.org/	(pair Networks, USA)
http://cran.za.R-project.org/	(Rhodes U, South Africa)

See <http://CRAN.R-project.org/mirrors.html> for a complete list of mirrors. Please use the CRAN site closest to you to reduce network load.

From CRAN, you can obtain the latest official release of R, daily snapshots of R (copies of the current source trees), as gzipped and bziped tar files, a wealth of additional contributed code, as well as prebuilt binaries for various operating systems (Linux, Mac OS Classic, Mac OS X, and MS Windows). CRAN also provides access to documentation on R, existing mailing lists and the R Bug Tracking system.

To “submit” to CRAN, simply upload to <ftp://CRAN.R-project.org/incoming/> and send an email to CRAN@R-project.org. Note that CRAN generally does not accept submissions of precompiled binaries due to security reasons. In particular, binary packages for Windows and Mac OS X are provided by the respective binary package maintainers.

Note: It is very important that you indicate the copyright (license) information (GPL-2, GPL-3, BSD, Artistic, . . .) in your submission.

Please always use the URL of the master site when referring to CRAN.

2.11 Can I use R for commercial purposes?

R is released under the [GNU General Public License \(GPL\)](#). If you have any questions regarding the legality of using R in any particular situation you should bring it up with your legal counsel. We are in no position to offer legal advice.

It is the opinion of the R Core Team that one can use R for commercial purposes (e.g., in business or in consulting). The GPL, like all Open Source licenses, permits all and any use of the package. It only restricts distribution of R or of other programs containing code

from R. This is made clear in clause 6 (“No Discrimination Against Fields of Endeavor”) of the **Open Source Definition**:

The license must not restrict anyone from making use of the program in a specific field of endeavor. For example, it may not restrict the program from being used in a business, or from being used for genetic research.

It is also explicitly stated in clause 0 of the GPL, which says in part

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program.

Most add-on packages, including all recommended ones, also explicitly allow commercial use in this way. A few packages are restricted to “non-commercial use”; you should contact the author to clarify whether these may be used or seek the advice of your legal counsel.

None of the discussion in this section constitutes legal advice. The R Core Team does not provide legal advice under any circumstances.

2.12 Why is R named R?

The name is partly based on the (first) names of the first two R authors (Robert Gentleman and Ross Ihaka), and partly a play on the name of the Bell Labs language ‘S’ (see [Section 3.1 \[What is S?\]](#), page 12).

2.13 What is the R Foundation?

The R Foundation is a not for profit organization working in the public interest. It was founded by the members of the R Core Team in order to provide support for the R project and other innovations in statistical computing, provide a reference point for individuals, institutions or commercial enterprises that want to support or interact with the R development community, and to hold and administer the copyright of R software and documentation. See <http://www.R-project.org/foundation/> for more information.

3 R and S

3.1 What is S?

S is a very high level language and an environment for data analysis and graphics. In 1998, the Association for Computing Machinery (ACM) presented its Software System Award to John M. Chambers, the principal designer of S, for

the S system, which has forever altered the way people analyze, visualize, and manipulate data . . .

S is an elegant, widely accepted, and enduring software system, with conceptual integrity, thanks to the insight, taste, and effort of John Chambers.

The evolution of the S language is characterized by four books by John Chambers and coauthors, which are also the primary references for S.

- Richard A. Becker and John M. Chambers (1984), “S. An Interactive Environment for Data Analysis and Graphics,” Monterey: Wadsworth and Brooks/Cole.

This is also referred to as the “*Brown Book*”, and of historical interest only.

- Richard A. Becker, John M. Chambers and Allan R. Wilks (1988), “The New S Language,” London: Chapman & Hall.

This book is often called the “*Blue Book*”, and introduced what is now known as S version 2.

- John M. Chambers and Trevor J. Hastie (1992), “Statistical Models in S,” London: Chapman & Hall.

This is also called the “*White Book*”, and introduced S version 3, which added structures to facilitate statistical modeling in S.

- John M. Chambers (1998), “Programming with Data,” New York: Springer, ISBN 0-387-98503-4 (<http://cm.bell-labs.com/cm/ms/departments/sia/Sbook/>).

This “*Green Book*” describes version 4 of S, a major revision of S designed by John Chambers to improve its usefulness at every stage of the programming process.

See <http://cm.bell-labs.com/cm/ms/departments/sia/S/history.html> for further information on “Stages in the Evolution of S”.

There is a huge amount of user-contributed code for S, available at the [S Repository](#) at CMU.

3.2 What is S-PLUS?

S-PLUS is a value-added version of S sold by Insightful Corporation. Based on the S language, S-PLUS provides functionality in a wide variety of areas, including robust regression, modern non-parametric regression, time series, survival analysis, multivariate analysis, classical statistical tests, quality control, and graphics drivers. Add-on modules add additional capabilities.

See the [Insightful S-PLUS page](#) for further information.

3.3 What are the differences between R and S?

We can regard S as a language with three current implementations or “engines”, the “old S engine” (S version 3; S-PLUS 3.x and 4.x), the “new S engine” (S version 4; S-PLUS 5.x and above), and R. Given this understanding, asking for “the differences between R and S” really amounts to asking for the specifics of the R implementation of the S language, i.e., the difference between the R and S *engines*.

For the remainder of this section, “S” refers to the S engines and not the S language.

3.3.1 Lexical scoping

Contrary to other implementations of the S language, R has adopted an evaluation model in which nested function definitions are lexically scoped. This is analogous to the evaluation model in Scheme.

This difference becomes manifest when *free* variables occur in a function. Free variables are those which are neither formal parameters (occurring in the argument list of the function) nor local variables (created by assigning to them in the body of the function). In S, the values of free variables are determined by a set of global variables (similar to C, there is only local and global scope). In R, they are determined by the environment in which the function was created.

Consider the following function:

```
cube <- function(n) {
  sq <- function() n * n
  n * sq()
}
```

Under S, `sq()` does not “know” about the variable `n` unless it is defined globally:

```
S> cube(2)
Error in sq(): Object "n" not found
Dumped
S> n <- 3
S> cube(2)
[1] 18
```

In R, the “environment” created when `cube()` was invoked is also looked in:

```
R> cube(2)
[1] 8
```

As a more “interesting” real-world problem, suppose you want to write a function which returns the density function of the r -th order statistic from a sample of size n from a (continuous) distribution. For simplicity, we shall use both the cdf and pdf of the distribution as explicit arguments. (Example compiled from various postings by Luke Tierney.)

The S-PLUS documentation for `call()` basically suggests the following:

```
dorder <- function(n, r, pfun, dfun) {
  f <- function(x) NULL
  con <- round(exp(lgamma(n + 1) - lgamma(r) - lgamma(n - r + 1)))
  PF <- call(substitute(pfun), as.name("x"))
  DF <- call(substitute(dfun), as.name("x"))
  f[[length(f)]] <-
    call("*", con,
          call("*", call("^", PF, r - 1),
                call("*", call("^", call("-", 1, PF), n - r),
                      DF)))
  f
}
```

Rather tricky, isn't it? The code uses the fact that in S, functions are just lists of special mode with the function body as the last argument, and hence does not work in R (one could make the idea work, though).

A version which makes heavy use of `substitute()` and seems to work under both S and R is

```
dorder <- function(n, r, pfun, dfun) {
  con <- round(exp(lgamma(n + 1) - lgamma(r) - lgamma(n - r + 1)))
  eval(substitute(function(x) K * PF(x)^a * (1 - PF(x))^b * DF(x),
                    list(PF = substitute(pfun), DF = substitute(dfun),
                        a = r - 1, b = n - r, K = con)))
}
```

(the `eval()` is not needed in S).

However, in R there is a much easier solution:

```
dorder <- function(n, r, pfun, dfun) {
  con <- round(exp(lgamma(n + 1) - lgamma(r) - lgamma(n - r + 1)))
  function(x) {
    con * pfun(x)^(r - 1) * (1 - pfun(x))^(n - r) * dfun(x)
  }
}
```

This seems to be the “natural” implementation, and it works because the free variables in the returned function can be looked up in the defining environment (this is lexical scope).

Note that what you really need is the function *closure*, i.e., the body along with all variable bindings needed for evaluating it. Since in the above version, the free variables in the value function are not modified, you can actually use it in S as well if you abstract out the closure operation into a function `MC()` (for “make closure”):

```
dorder <- function(n, r, pfun, dfun) {
  con <- round(exp(lgamma(n + 1) - lgamma(r) - lgamma(n - r + 1)))
  MC(function(x) {
    con * pfun(x)^(r - 1) * (1 - pfun(x))^(n - r) * dfun(x)
  },
    list(con = con, pfun = pfun, dfun = dfun, r = r, n = n))
}
```

Given the appropriate definitions of the closure operator, this works in both R and S, and is much “cleaner” than a substitute/eval solution (or one which overrules the default scoping rules by using explicit access to evaluation frames, as is of course possible in both R and S).

For R, `MC()` simply is

```
MC <- function(f, env) f
```

(lexical scope!), a version for S is

```
MC <- function(f, env = NULL) {
  env <- as.list(env)
  if (mode(f) != "function")
    stop(paste("not a function:", f))
  if (length(env) > 0 && any(names(env) == ""))
    stop(paste("not all arguments are named:", env))
  fargs <- if(length(f) > 1) f[1:(length(f) - 1)] else NULL
  fargs <- c(fargs, env)
  if (any(duplicated(names(fargs))))
    stop(paste("duplicated arguments:", paste(names(fargs)),
      collapse = ", "))
  fbody <- f[length(f)]
  cf <- c(fargs, fbody)
  mode(cf) <- "function"
  return(cf)
}
```

Similarly, most optimization (or zero-finding) routines need some arguments to be optimized over and have other parameters that depend on the data but are fixed with respect to optimization. With R scoping rules, this is a trivial problem; simply make up the function with the required definitions in the same environment and scoping takes care of it. With S, one solution is to add an extra parameter to the function and to the optimizer to pass in these extras, which however can only work if the optimizer supports this.

Nested lexically scoped functions allow using function closures and maintaining local state. A simple example (taken from Abelson and Sussman) is obtained by typing `demo("scoping")` at the R prompt. Further information is provided in the standard R reference “R: A Language for Data Analysis and Graphics” (see [Section 2.7 \[What documentation exists for R?\]](#), page 6) and in Robert Gentleman and Ross Ihaka (2000), “Lexical Scope and Statistical Computing”, *Journal of Computational and Graphical Statistics*, **9**, 491–508.

Nested lexically scoped functions also imply a further major difference. Whereas S stores all objects as separate files in a directory somewhere (usually ‘.Data’ under the current directory), R does not. All objects in R are stored internally. When R is started up it grabs a piece of memory and uses it to store the objects. R performs its own memory management of this piece of memory, growing and shrinking its size as needed. Having everything in memory is necessary because it is not really possible to externally maintain all relevant “environments” of symbol/value pairs. This difference also seems to make R *faster* than S.

The down side is that if R crashes you will lose all the work for the current session. Saving and restoring the memory “images” (the functions and data stored in R’s internal memory at any time) can be a bit slow, especially if they are big. In S this does not happen, because everything is saved in disk files and if you crash nothing is likely to happen to them. (In fact, one might conjecture that the S developers felt that the price of changing their approach to persistent storage just to accommodate lexical scope was far too expensive.) Hence, when doing important work, you might consider saving often (see [Section 7.2 \[How can I save my workspace?\]](#), page 92) to safeguard against possible crashes. Other possibilities are logging your sessions, or have your R commands stored in text files which can be read in using `source()`.

Note: If you run R from within Emacs (see [Chapter 6 \[R and Emacs\]](#), page 90), you can save the contents of the interaction buffer to a file and conveniently manipulate it using `ess-transcript-mode`, as well as save source copies of all functions and data used.

3.3.2 Models

There are some differences in the modeling code, such as

- Whereas in S, you would use `lm(y ~ x^3)` to regress y on x^3 , in R, you have to insulate powers of numeric vectors (using `I()`), i.e., you have to use `lm(y ~ I(x^3))`.
- The `glm` family objects are implemented differently in R and S. The same functionality is available but the components have different names.
- Option `na.action` is set to `"na.omit"` by default in R, but not set in S.
- Terms objects are stored differently. In S a terms object is an expression with attributes, in R it is a formula with attributes. The attributes have the same names but are mostly stored differently.
- Finally, in R `y ~ x + 0` is an alternative to `y ~ x - 1` for specifying a model with no intercept. Models with no parameters at all can be specified by `y ~ 0`.

3.3.3 Others

Apart from lexical scoping and its implications, R follows the S language definition in the Blue and White Books as much as possible, and hence really is an “implementation” of S. There are some intentional differences where the behavior of S is considered “not clean”. In general, the rationale is that R should help you detect programming errors, while at the same time being as compatible as possible with S.

Some known differences are the following.

- In R, if `x` is a list, then `x[i] <- NULL` and `x[[i]] <- NULL` remove the specified elements from `x`. The first of these is incompatible with S, where it is a no-op. (Note that you can set elements to NULL using `x[i] <- list(NULL)`.)
- In S, the functions named `.First` and `.Last` in the `‘.Data’` directory can be used for customizing, as they are executed at the very beginning and end of a session, respectively.

In R, the startup mechanism is as follows. R first sources the system startup file `‘$R_HOME/library/base/R/Rprofile’`. Then, it searches for a site-wide startup profile unless the command line option `‘--no-site-file’` was given. The name of this file

is taken from the value of the `R_PROFILE` environment variable. If that variable is unset, the default is `'$R_HOME/etc/Rprofile.site'` (`'$R_HOME/etc/Rprofile'` in versions prior to 1.4.0). This code is loaded in package `base`. Then, unless `'--no-init-file'` was given, R searches for a file called `'.Rprofile'` in the current directory or in the user's home directory (in that order) and sources it into the user workspace. It then loads a saved image of the user workspace from `'.RData'` in case there is one (unless `'--no-restore'` was specified). If needed, the functions `.First()` and `.Last()` should be defined in the appropriate startup profiles.

- In R, `T` and `F` are just variables being set to `TRUE` and `FALSE`, respectively, but are not reserved words as in S and hence can be overwritten by the user. (This helps e.g. when you have factors with levels `"T"` or `"F"`.) Hence, when writing code you should always use `TRUE` and `FALSE`.
- In R, `dyn.load()` can only load *shared objects*, as created for example by R CMD SHLIB.
- In R, `attach()` currently only works for lists and data frames, but not for directories. (In fact, `attach()` also works for R data files created with `save()`, which is analogous to attaching directories in S.) Also, you cannot attach at position 1.
- Categories do not exist in R, and never will as they are deprecated now in S. Use factors instead.
- In R, `For()` loops are not necessary and hence not supported.
- In R, `assign()` uses the argument `'envir='` rather than `'where='` as in S.
- The random number generators are different, and the seeds have different length.
- R passes integer objects to C as `int *` rather than `long *` as in S.
- R has no single precision storage mode. However, as of version 0.65.1, there is a single precision interface to C/FORTRAN subroutines.
- By default, `ls()` returns the names of the objects in the current (under R) and global (under S) environment, respectively. For example, given

```
x <- 1; fun <- function() {y <- 1; ls()}
```

then `fun()` returns `"y"` in R and `"x"` (together with the rest of the global environment) in S.

- R allows for zero-extent matrices (and arrays, i.e., some elements of the `dim` attribute vector can be 0). This has been determined a useful feature as it helps reducing the need for special-case tests for empty subsets. For example, if `x` is a matrix, `x[, FALSE]` is not `NULL` but a “matrix” with 0 columns. Hence, such objects need to be tested for by checking whether their `length()` is zero (which works in both R and S), and not using `is.null()`.
- Named vectors are considered vectors in R but not in S (e.g., `is.vector(c(a = 1:3))` returns `FALSE` in S and `TRUE` in R).
- Data frames are not considered as matrices in R (i.e., if `DF` is a data frame, then `is.matrix(DF)` returns `FALSE` in R and `TRUE` in S).
- R by default uses treatment contrasts in the unordered case, whereas S uses the Helmert ones. This is a deliberate difference reflecting the opinion that treatment contrasts are more natural.

- In R, the argument of a replacement function which corresponds to the right hand side must be named ‘value’. E.g., `f(a) <- b` is evaluated as `a <- "f<-"(a, value = b)`. S always takes the last argument, irrespective of its name.
- In S, `substitute()` searches for names for substitution in the given expression in three places: the actual and the default arguments of the matching call, and the local frame (in that order). R looks in the local frame only, with the special rule to use a “promise” if a variable is not evaluated. Since the local frame is initialized with the actual arguments or the default expressions, this is usually equivalent to S, until assignment takes place.
- In S, the index variable in a `for()` loop is local to the inside of the loop. In R it is local to the environment where the `for()` statement is executed.
- In S, `tapply(simplify=TRUE)` returns a vector where R returns a one-dimensional array (which can have named dimnames).
- In S(-PLUS) the C locale is used, whereas in R the current operating system locale is used for determining which characters are alphanumeric and how they are sorted. This affects the set of valid names for R objects (for example accented chars may be allowed in R) and ordering in sorts and comparisons (such as whether `"aA" < "Bb"` is true or false). From version 1.2.0 the locale can be (re-)set in R by the `Sys.setlocale()` function.
- In S, `missing(arg)` remains TRUE if `arg` is subsequently modified; in R it doesn’t.
- From R version 1.3.0, `data.frame` strips `I()` when creating (column) names.
- In R, the string "NA" is not treated as a missing value in a character variable. Use `as.character(NA)` to create a missing character value.
- R disallows repeated formal arguments in function calls.
- In S, `dump()`, `dput()` and `deparse()` are essentially different interfaces to the same code. In R from version 2.0.0, this is only true if the same `control` argument is used, but by default it is not. By default `dump()` tries to write code that will evaluate to reproduce the object, whereas `dput()` and `deparse()` default to options for producing deparsed code that is readable.
- In R, indexing a vector, matrix, array or data frame with `[` using a character vector index looks only for exact matches (whereas `[[` and `$` allow partial matches). In S, `[` allows partial matches.
- S has a two-argument version of `atan` and no `atan2`. A call in S such as `atan(x1, x2)` is equivalent to R’s `atan2(x1, x2)`. However, beware of named arguments since S’s `atan(x = a, y = b)` is equivalent to R’s `atan2(y = a, x = b)` with the meanings of `x` and `y` interchanged. (R used to have undocumented support for a two-argument `atan` with positional arguments, but this has been withdrawn to avoid further confusion.)
- Numeric constants with no fractional and exponent (i.e., only integer) part are taken as integer in S-PLUS 6.x or later, but as double in R.

There are also differences which are not intentional, and result from missing or incorrect code in R. The developers would appreciate hearing about any deficiencies you may find (in a written report fully documenting the difference as you see it). Of course, it would be useful if you were to implement the change yourself and make sure it works.

3.4 Is there anything R can do that S-PLUS cannot?

Since almost anything you can do in R has source code that you could port to S-PLUS with little effort there will never be much you can do in R that you couldn't do in S-PLUS if you wanted to. (Note that using lexical scoping may simplify matters considerably, though.)

R offers several graphics features that S-PLUS does not, such as finer handling of line types, more convenient color handling (via palettes), gamma correction for color, and, most importantly, mathematical annotation in plot texts, via input expressions reminiscent of \TeX constructs. See the help page for `plotmath`, which features an impressive on-line example. More details can be found in Paul Murrell and Ross Ihaka (2000), “An Approach to Providing Mathematical Annotation in Plots”, *Journal of Computational and Graphical Statistics*, **9**, 582–599.

3.5 What is R-plus?

For a very long time, there was no such thing.

XLSolutions Corporation is currently beta testing a commercially supported version of R named R+ (read R plus).

In addition, **REvolution Computing** has released **RPro**, an enterprise-class statistical analysis system based on R, suitable for deployment in professional, commercial and regulated environments.

Random Technologies offers **RStat**, an enterprise-strength statistical computing environment which combines R with enterprise-level validation, documentation, software support, and consulting services, as well as related R-based products.

4 R Web Interfaces

Rweb is developed and maintained by [Jeff Banfield](#). The [Rweb Home Page](#) provides access to all three versions of Rweb—a simple text entry form that returns output and graphs, a more sophisticated Javascript version that provides a multiple window environment, and a set of point and click modules that are useful for introductory statistics courses and require no knowledge of the R language. All of the Rweb versions can analyze Web accessible datasets if a URL is provided.

The paper “Rweb: Web-based Statistical Analysis”, providing a detailed explanation of the different versions of Rweb and an overview of how Rweb works, was published in the Journal of Statistical Software (<http://www.jstatsoft.org/v04/i01/>).

[Ulf Bartel](#) has developed **R-Online**, a simple on-line programming environment for R which intends to make the first steps in statistical programming with R (especially with time series) as easy as possible. There is no need for a local installation since the only requirement for the user is a JavaScript capable browser. See <http://osvisions.com/r-online/> for more information.

Rcgi is a CGI WWW interface to R by [MJ Ray](#). It had the ability to use “embedded code”: you could mix user input and code, allowing the HTML author to do anything from load in data sets to enter most of the commands for users without writing CGI scripts. Graphical output was possible in PostScript or GIF formats and the executed code was presented to the user for revision. However, it is not clear if the project is still active. Currently, a modified version of **Rcgi** by [Mai Zhou](#) (actually, two versions: one with (bitmap) graphics and one without) as well as the original code are available from <http://www.ms.uky.edu/~statweb/>.

CGI-based web access to R is also provided at <http://hermes.sdu.dk/cgi-bin/go/>. There are many additional examples of web interfaces to R which basically allow to submit R code to a remote server, see for example the collection of links available from <http://biostat.mc.vanderbilt.edu/twiki/bin/view/Main/StatCompCourse>.

[David Firth](#) has written **CGIwithR**, an R add-on package available from CRAN. It provides some simple extensions to R to facilitate running R scripts through the CGI interface to a web server, and allows submission of data using both GET and POST methods. It is easily installed using Apache under Linux and in principle should run on any platform that supports R and a web server provided that the installer has the necessary security permissions. David’s paper “CGIwithR: Facilities for Processing Web Forms Using R” was published in the Journal of Statistical Software (<http://www.jstatsoft.org/v08/i10/>). The package is now maintained by [Duncan Temple Lang](#) and has a web page at <http://www.omegahat.org/CGIwithR/>.

Rpad, developed and actively maintained by Tom Short, provides a sophisticated environment which combines some of the features of the previous approaches with quite a bit of Javascript, allowing for a GUI-like behavior (with sortable tables, clickable graphics, editable output), etc.

Jeff Horner is working on the R/Apache Integration Project which embeds the R interpreter inside Apache 2 (and beyond). A tutorial and presentation are available from the project web page at <http://biostat.mc.vanderbilt.edu/twiki/bin/view/Main/RApacheProject>.

Rserve is a project actively developed by Simon Urbanek. It implements a TCP/IP server which allows other programs to use facilities of R. Clients are available from the web site for Java and C++ (and could be written for other languages that support TCP/IP sockets).

OpenStatServer is being developed by a team lead by Greg Warnes; it aims “to provide clean access to computational modules defined in a variety of computational environments (R, SAS, Matlab, etc) via a single well-defined client interface” and to turn computational services into web services.

Two projects use PHP to provide a web interface to R. **R_PHP_Online** by Steve Chen (though it is unclear if this project is still active) is somewhat similar to the above Rcgi and Rweb. **R-php** is actively developed by Alfredo Pontillo and Angelo Mineo and provides both a web interface to R and a set of pre-specified analyses that need no R code input.

webbioc is “an integrated web interface for doing microarray analysis using several of the Bioconductor packages” and is designed to be installed at local sites as a shared computing resource.

Finally, **Rwui** is a web application to create user-friendly web interfaces for R scripts. All code for the web interface is created automatically. There is no need for the user to do any extra scripting or learn any new scripting techniques.

5 R Add-On Packages

5.1 Which add-on packages exist for R?

5.1.1 Add-on packages in R

The R distribution comes with the following packages:

base	Base R functions (and datasets before R 2.0.0).
datasets	Base R datasets (added in R 2.0.0).
grDevices	Graphics devices for base and grid graphics (added in R 2.0.0).
graphics	R functions for base graphics.
grid	A rewrite of the graphics layout capabilities, plus some support for interaction.
methods	Formally defined methods and classes for R objects, plus other programming tools, as described in the Green Book.
splines	Regression spline functions and classes.
stats	R statistical functions.
stats4	Statistical functions using S4 classes.
tcltk	Interface and language bindings to Tcl/Tk GUI elements.
tools	Tools for package development and administration.
utils	R utility functions.

These “base packages” were substantially reorganized in R 1.9.0. The former **base** was split into the four packages **base**, **graphics**, **stats**, and **utils**. Packages **ctest**, **eda**, **modreg**, **mva**, **nls**, **stepfun** and **ts** were merged into **stats**, package **lqs** returned to the recommended package **MASS**, and package **mle** moved to **stats4**.

5.1.2 Add-on packages from CRAN

The following packages are available from the CRAN ‘**src/contrib**’ area. (Packages denoted as *Recommended* are to be included in all binary distributions of R.)

ADaCGH	Analysis of data from aCGH experiments.
AIS	Tools to look at the data (“Ad Inidicia Spectata”).
AMORE	A MORE flexible neural network package, providing the TAO robust neural network algorithm.
ARES	Allelic richness estimation, with extrapolation beyond the sample size.
AcceptanceSampling	Creation and evaluation of acceptance sampling plans,
AdaptFit	Adaptive semiparametric regression.
AlgDesign	Algorithmic experimental designs. Calculates exact and approximate theory experimental designs for D, A, and I criteria.

Amelia	Amelia II: a program for missing data.
AnalyzefMRI	Functions for I/O, visualisation and analysis of functional Magnetic Resonance Imaging (fMRI) datasets stored in the ANALYZE format.
ArDec	Time series autoregressive decomposition.
BACCO	Bayesian Analysis of Computer Code Output. Contains approximator , calibrator , and emulator , for Bayesian prediction of complex computer codes, calibration of computer models, and emulation of computer programs, respectively.
BARD	Better Automated ReDistricting.
BHH2	Functions and data sets reproducing some examples in “Statistics for Experimenters II” by G. E. P. Box, J. S. Hunter, and W. C. Hunter, 2005, John Wiley and Sons.
BMA	Bayesian Model Averaging for linear models, generalizable linear models and survival models (Cox regression).
BRugs	OpenBUGS and its R interface BRugs.
BayHaz	Functions for Bayesian Hazard rate estimation.
BayesTree	Bayesian methods for tree based models.
BayesValidate	Bayesian software validation using posterior quantiles.
Bhat	Functions for general likelihood exploration (MLE, MCMC, CIs).
BiasedUrn	Biased urn model distributions.
BioIDMapper	Mapping between BioIDs.
Biodem	A number of functions for biodemographycal analysis.
BiodiversityR	GUI for biodiversity and community ecology analysis.
Bolstad	Functions and data sets for the book “Introduction to Bayesian Statistics” by W. M. Bolstad, 2004, John Wiley and Sons.
BootCL	Bootstrapping test for chromosomal localization.
BradleyTerry	Specify and fit the Bradley-Terry model and structured versions.
Brobdignag	Very large numbers in R.
BSDA	Data sets for the book “Basic Statistics and Data Analysis” by L. J. Kitchens, 2003, Duxbury.
BsMD	Bayes screening and model discrimination follow-up designs.

CCA	Canonical correlation analysis.
CDNmoney	Components of Canadian monetary aggregates.
CGIwithR	Facilities for the use of R to write CGI scripts.
CORREP	Multivariate correlation estimation.
CPGchron	Create radiocarbon-dated depth chronologies.
CTFS	The CTFS large plot forest dynamics analyses.
CVThresh	Level-dependent Cross-Validation Thresholding.
Cairo	Graphics device using cairographics library for creating high-quality PNG, PDF, SVG, PostScript output and interactive display devices such as X11.
CarbonEL	Carbon Event Loop.
CircStats	Circular Statistics, from “Topics in Circular Statistics” by S. Rao Jammalamadaka and A. SenGupta, 2001, World Scientific.
CoCo	Graphical modeling for contingency tables using CoCo.
ComPairWise	Compare phylogenetic or population genetic data alignments.
CompetingRiskFrailty	Competing risk model with frailties for right censored survival data.
CreditMetrics	Functions for calculating the CreditMetrics risk model.
DAAG	Various data sets used in examples and exercises in “Data Analysis and Graphics Using R” by John H. Maindonald and W. John Brown, 2003.
DAAGbio	Data sets and functions, for demonstrations with expression arrays.
DAAGxtras	Data sets and functions additional to DAAG .
DBI	A common database interface (DBI) class and method definitions. All classes in this package are virtual and need to be extended by the various DBMS implementations.
DCluster	A set of functions for the detection of spatial clusters of diseases using count data.
DDHFm	Variance stabilization by Data-Driven Haar-Fisz (for microarrays).
DEoptim	Differential Evolution Optimization.
DICOM	Import and manipulate medical imaging data using the Digital Imaging and Communications in Medicine (DICOM) Standard.
DPpackage	Semiparametric Bayesian analysis using Dirichlet process priors.

Davies	Functions for the Davies quantile function and the Generalized Lambda distribution.
Defaults	Create global function defaults.
DescribeDisplay	R interface to the DescribeDisplay GGobi plugin.
Design	Regression modeling, testing, estimation, validation, graphics, prediction, and typesetting by storing enhanced model design attributes in the fit. Design is a collection of about 180 functions that assist and streamline modeling, especially for biostatistical and epidemiologic applications. It also contains new functions for binary and ordinal logistic regression models and the Buckley-James multiple regression model for right-censored responses, and implements penalized maximum likelihood estimation for logistic and ordinary linear models. Design works with almost any regression model, but it was especially written to work with logistic regression, Cox regression, accelerated failure time models, ordinary linear models, and the Buckley-James model.
Devore5	Data sets and sample analyses from “Probability and Statistics for Engineering and the Sciences (5th ed)” by Jay L. Devore, 2000, Duxbury.
Devore6	Data sets and sample analyses from “Probability and Statistics for Engineering and the Sciences (6th ed)” by Jay L. Devore, 2003, Duxbury.
Devore7	Data sets and sample analyses from “Probability and Statistics for Engineering and the Sciences (7th ed)” by Jay L. Devore, 2008, Thomson.
EDR	Estimation of the effective dimension reduction (EDR) space.
EMV	Estimation of missing values in a matrix by a k -th nearest neighbors algorithm.
EbayesThresh	Empirical Bayes thresholding and related methods.
Ecdat	Data sets from econometrics textbooks.
ElemStatLearn	Data sets, functions and examples from the book “The Elements of Statistical Learning: Data Mining, Inference, and Prediction” by Trevor Hastie, Robert Tibshirani and Jerome Friedman (2001), Springer.
Epi	Statistical analysis in epidemiology, with functions for demographic and epidemiological analysis in the Lexis diagram.
FGN	Fractional Gaussian Noise model fitting.
FKBL	Fuzzy Knowledge Base Learning.
FactoMineR	Factor analysis and data mining with R.
Fahrmeir	Data from the book “Multivariate Statistical Modelling Based on Generalized Linear Models” by Ludwig Fahrmeir and Gerhard Tutz (1994), Springer.
FieldSim	Random fields simulations.

Flury	Data sets from from “A First Course in Multivariate Statistics” by Bernard Flury (1997), Springer.
FracSim	Simulation of one- and two-dimensional fractional and multifractional Levy motions.
FunCluster	Functional profiling of cDNA microarray expression data.
G1DBN	Dynamic Bayesian Network inference using 1st order conditional dependencies.
GAMBoost	Generalized additive models by likelihood based boosting.
GDD	Platform and X11 independent device for creating bitmaps (png, gif and jpeg) using the GD graphics library.
GLDEX	Fit RS and FMKL generalised lambda distributions using discretized and maximum likelihood methods.
GOSim	Computation of functional similarities between GO terms and gene products.
GPArotation	Gradient Projection Algorithm rotation for factor analysis.
GRASS	An interface between the GRASS geographical information system and R, based on starting R from within the GRASS environment and chosen LOCATION_NAME and MAPSET. Wrapper and helper functions are provided for a range of R functions to match the interface metadata structures.
GSA	Gene set analysis.
GSM	Gamma Shape Mixture.
GenABEL	Genome-wide SNP association analysis.
GenKern	Functions for generating and manipulating generalised binned kernel density estimates.
GeneCycle	Identification of periodically expressed genes.
GeneF	Generalized F -statistics.
GeneNT	Relevance or Dependency network and signaling pathway discovery.
GeneNet	Modeling and inferring gene networks.
GeneTS	A package for analysing multiple gene expression time series data. Currently, implements methods for cell cycle analysis and for inferring large sparse graphical Gaussian models.
Geneland	MCMC inference from individual genetic data based on a spatial statistical model.
GeoXp	Interactive exploratory spatial data analysis.
GillespieSSA	Gillespie’s Stochastic Simulation Algorithm (SSA).

GroupSeq	Computations related to group-sequential boundaries.
HH	Support software for “Statistical Analysis and Data Display” by Richard M. Heiberger and Burt Holland, Springer, 2005.
HI	Simulation from distributions supported by nested hyperplanes.
HSAUR	Functions, data sets, analyses and examples from the book “A Handbook of Statistical Analyses Using R” by Brian S. Everitt and Torsten Hothorn (2006), Chapman & Hall/CRC.
HTMLapplets	Functions inserting dynamic scatterplots and grids in documents generated by R2HTML .
HFWutils	Utilities by H. Felix Wittmann: Excel connections, string matching, and passing by reference.
HardyWeinberg	Graphical tests for Hardy-Weinberg equilibrium.
HiddenMarkov	Hidden Markov Models.
HighProbability	Estimation of the alternative hypotheses having frequentist or Bayesian probabilities at least as great as a specified threshold, given a list of p -values.
Hmisc	Functions useful for data analysis, high-level graphics, utility operations, functions for computing sample size and power, importing datasets, imputing missing values, advanced table making, variable clustering, character string manipulation, conversion of S objects to \LaTeX code, recoding variables, and bootstrap repeated measures analysis.
HydroMe	Estimation of soil hydraulic parameters from experimental data.
HyperbolicDist	Basic functions for the hyperbolic distribution: probability density function, distribution function, quantile function, a routine for generating observations from the hyperbolic, and a function for fitting the hyperbolic distribution to data.
ICE	Iterated Conditional Expectation: kernel estimators for interval-censored data.
ICEinfer	Incremental Cost-Effectiveness (ICE) statistical inference (from two unbiased samples).
ICS	ICS/ICA computation based on two scatter matrices.
ICSNP	Tools for multivariate nonparametrics.
IDPmisc	Utilities from the Institute of Data Analyses and Process Design, IDP/ZHW.
IPSUR	Accompanies “Introduction to Probability and Statistics Using R” by G. Andy Chang and G. Jay Kerns(in progress).
ISwR	Data sets for “Introductory Statistics with R” by Peter Dalgaard, 2002, Springer.

Icens	Functions for computing the NPMLE for censored and truncated data.
JADE	JADE and ICA performance criteria.
JLLprod	Nonparametric estimation of homothetic and generalized homothetic production functions.
JGR	Java Gui for R.
JavaGD	Java Graphics Device.
JointGLM	Joint modeling of mean and dispersion through two interlinked GLM's. <i>Defunct</i> in favor of JointModeling .
JointModeling	Joint modeling of mean and dispersion.
JudgeIt	Calculates bias, responsiveness, and other characteristics of two-party electoral systems, with district-level electoral and other data.
KMsurv	Data sets and functions for “Survival Analysis, Techniques for Censored and Truncated Data” by Klein and Moeschberger, 1997, Springer.
Kendall	Kendall rank correlation and Mann-Kendall trend test.
KernSmooth	Functions for kernel smoothing (and density estimation) corresponding to the book “Kernel Smoothing” by M. P. Wand and M. C. Jones, 1995. <i>Recommended</i> .
LDheatmap	Heat maps of linkage disequilibrium measures.
LLAhclust	Hierarchical clustering of variables or objects based on the likelihood linkage analysis method.
LLN	Learning with latent networks.
LMGene	Date transformation and identification of differentially expressed genes in gene expression arrays.
LearnBayes	Functions for Learning Bayesian Inference.
Lmoments	Estimation of L-moments and the parameters of normal and Cauchy polynomial quantile mixtures.
LogConcDEAD	Maximum likelihood estimation of a log-concave density.
LogicReg	Routines for Logic Regression.
LoopAnalyst	A collection of tools to conduct Levins' Loop Analysis.
LowRankQP	Low Rank Quadratic Programming: QP problems where the hessian is represented as the product of two matrices.

MASS	Functions and datasets from the main package of Venables and Ripley, “Modern Applied Statistics with S”. Contained in the ‘VR’ bundle. <i>Recommended</i> .
MBA	Multilevel B -spline Approximation.
MBESS	Methods for the Behavioral, Educational, and Social Sciences.
MCMCpack	Markov chain Monte Carlo (MCMC) package: functions for posterior simulation for a number of statistical models.
MChtest	Monte Carlo hypothesis tests.
MEMSS	Data sets and sample analyses from “Mixed-effects Models in S and S-PLUS” by J. Pinheiro and D. Bates, 2000, Springer.
MFDA	Model Based Functional Data Analysis.
MKLE	Maximum kernel likelihood estimation.
MLDS	Maximum Likelihood Difference Scaling.
MLEcens	Computation of the MLE for bivariate (interval) censored data.
MNP	Fitting Bayesian Multinomial Probit models via Markov chain Monte Carlo. Along with the standard Multinomial Probit model, it can also fit models with different choice sets for each observation and complete or partial ordering of all the available alternatives.
MPV	Data sets from the book “Introduction to Linear Regression Analysis” by D. C. Montgomery, E. A. Peck, and C. G. Vining, 2001, John Wiley and Sons.
MSBVAR	Bayesian vector autoregression models, impulse responses and forecasting.
MarkedPointProcess	Non-parametric analysis of the marks of marked point processes.
MasterBayes	Maximum likelihood and Markov chain Monte Carlo methods for pedigree reconstruction, analysis and simulation.
MatchIt	Select matched samples of the original treated and control groups with similar covariate distributions.
Matching	Multivariate and propensity score matching with formal tests of balance.
Matrix	A Matrix package.
MiscPsycho	Miscellaneous Psychometrics.
NADA	Methods described in “Nondetects And Data Analysis: Statistics for Censored Environmental Data” by Dennis R. Helsel, 2004, John Wiley and Sons.
NISTnls	A set of test nonlinear least squares examples from NIST, the U.S. National Institute for Standards and Technology.
NMMAPSlite	U.S. National Morbidity, Mortality, and Air Pollution Study data lite.

- NORMT3** Evaluates complex erf, erfc and density of sum of Gaussian and Student's t .
- NRAIA** Data sets with sample code from "Nonlinear Regression Analysis and Its Applications" by Doug Bates and Donald Watts, 1988, Wiley.
- NestedCohort**
Survival analysis for cohorts with missing covariate information.
- ORMDR** Odds ratio based multivector-dimensionality reduction method for detecting gene-gene interactions.
- Oarray** Arrays with arbitrary offsets.
- PBSmapping**
Software evolved from fisheries research conducted at the Pacific Biological Station (PBS) in Nanaimo, British Columbia, Canada. Draws maps and implements other GIS procedures.
- PBSmodelling**
Software to facilitate the design, testing, and operation of computer models.
- PET** Simulation and reconstruction of PET images.
- PHYLOGR**
Manipulation and analysis of phylogenetically simulated data sets (as obtained from PDSIMUL in package PDAP) and phylogenetically-based analyses using GLS.
- PK** Estimation of pharmacokinetic parameters.
- PKfit** A nonlinear regression (including a genetic algorithm) program designed to deal with curve fitting for pharmacokinetics.
Unified computational interfaces for pop PK.
- POT** Generalized Pareto distribution and Peaks Over Threshold.
- PSAgraphics**
Propensity Score Analysis Graphics.
- PTAk** A multiway method to decompose a tensor (array) of any order, as a generalisation of SVD also supporting non-identity metrics and penalisations. Also includes some other multiway methods.
- PearsonICA**
Independent component analysis using score functions from the Pearson system.
- PerformanceAnalytics**
Econometric tools for performance and risk analysis.
- PhySim** Phylogenetic tree simulation.
- PresenceAbsence**
Presence-absence model evaluation.
- ProbForecastGOP**
Probabilistic weather field forecasts using the Geostatistical Output Perturbation method introduced by Gel, Raftery and Gneiting (2004).

ProbeR	Reliability for gene expression from Affymetrix chip.
ProfessR	Programs to determine student grades and create examinations from question banks.
QCA	Qualitative Comparative Analysis for crisp sets.
QCAGUI	QCA Graphical User Interface.
QRMlib	Code to examine Quantitative Risk Management concepts.
R.cache	Fast and light-weight caching of objects.
R.huge	Methods for accessing huge amounts of data.
R.matlab	Read and write of MAT files together with R-to-Matlab connectivity.
R.oo	R object-oriented programming with or without references.
R.rsp	R server pages.
R.utils	Utility classes and methods useful when programming in R and developing R packages.
R2HTML	Functions for exporting R objects & graphics in an HTML document.
R2WinBUGS	Running WinBUGS from R: call a BUGS model, summarize inferences and convergence in a table and graph, and save the simulations in arrays for easy access in R.
RArcInfo	Functions to import Arc/Info V7.x coverages and data.
RBGL	Interface to the boost C++ graph library.
RBloomberg	Fetch data from a Bloomberg API using COM.
RColorBrewer	ColorBrewer palettes for drawing nice maps shaded according to a variable.
RDieHarder	R interface to the dieharder random number generator test suite.
RFA	Regional Frequency Analysis.
RFOC	Graphics for spherical distributions and earthquake focal mechanisms.
RGtk2	Facilities for programming graphical interfaces using Gtk (the Gimp Tool Kit) version 2.
RGrace	Mouse/menu driven interactive plotting application.
RGraphics	Data and functions from the book “R Graphics” by Paul Murrell, 2005, Chapman & Hall/CRC.
RHmm	Hidden Markov Model simulations and estimations.
RII	Estimation of the relative index of inequality for interval-censored data using natural cubic splines.

RJDBC	Access to databases through the JDBC interface.
RJaCGH	Reversible Jump MCMC for the analysis of CGH arrays.
RLMM	A genotype calling algorithm for Affymetrix SNP arrays.
RLRsim	Exact (Restricted) Likelihood Ratio tests for mixed and additive models.
RLadyBug	Analysis of infectious diseases using stochastic epidemic models.
RMySQL	An interface between R and the MySQL database system.
RNetCDF	An interface to Unidata's NetCDF library functions (version 3) and furthermore access to Unidata's udunits calendar conversions.
ROCR	Visualizing the performance of scoring classifiers.
RODBC	An ODBC database interface.
ROptEst	Optimally robust estimation.
ROptEstTS	Optimally robust estimation for regression-type models.
ROracle	Oracle Database Interface driver for R. Uses the ProC/C++ embedded SQL.
RPMG	Poor Man's Gui: create interactive R analysis sessions.
RPyGeo	ArcGIS Geoprocessing in R via Python.
RQuantLib	Provides access to (some) of the QuantLib functions from within R; currently limited to some Option pricing and analysis functions. The QuantLib project aims to provide a comprehensive software framework for quantitative finance.
RSAGA	SAGA geoprocessing and terrain analysis in R.
SQLite	Database Interface R driver for SQLite. Embeds the SQLite database engine in R.
RScalLAPACK	An interface to ScaLAPACK functions from R.
RSVGtipsDevice	An R SVG graphics device with dynamic tips and hyperlinks.
RSvgDevice	A graphics device for R that uses the new w3.org XML standard for Scalable Vector Graphics.
RTisean	R interface to Tisean algorithms.
RUnit	Functions implementing a standard Unit Testing framework, with additional code inspection and report generation tools.
RWeka	An R interface to Weka, a rich collection of machine learning algorithms for data mining tasks.
RWinEdt	A plug in for using WinEdt as an editor for R.

- RXshrink** Maximum Likelihood Shrinkage via Ridge or Least Angle Regression.
- RadioSonde**
A collection of programs for reading and plotting SKEW-T,log p diagrams and wind profiles for data collected by radiosondes (the typical weather balloon-borne instrument).
- RandVar** Implementation of random variables by means of S4 classes and methods.
- RandomFields**
Creating random fields using various methods.
- RaschSampler**
Sampling binary matrices with fixed margins.
- Rcapture** Loglinear models in capture-recapture experiments.
- Rcmdr** A platform-independent basic-statistics GUI (graphical user interface) for R, based on the **tcltk** package.
- RcmdrPlugin.HH**
Rcmdr support for the introductory course at Temple University.
- RcmdrPlugin.TeachingDemos**
Rcmdr Teaching Demos plug-in.
- Reliability** Functions for estimating parameters in software reliability models.
- ResistorArray**
Electrical properties of resistor networks.
- Rfwdmv** Forward Search for Multivariate Data.
- RiboSort** Classification and analysis of microbial community profiles.
- Rigroup** Provides small integer group functions.
- Rlab** Functions and data sets for the NCSU ST370 class.
- Rlsf** Interface to the LSF queuing system.
- Rmdr** R-Multifactor Dimensionality Reduction.
- Rmetrics** Financial engineering and computational finance.
- Rmpi** An interface (wrapper) to MPI (Message-Passing Interface) APIs. It also provides an interactive R slave environment in which distributed statistical computing can be carried out.
- RobLox** Optimally robust influence curves for location and scale.
- RobRex** Optimally robust influence curves for regression and scale.
- Rpad** Utility functions for the Rpad workbook-style interface.
- Rsac** Seismic tools for R.
- Rserve** A socket server (TCP/IP or local sockets) which allows binary requests to be sent to R.

Runuran	Interface to the UNU.RAN library for Universal Non-Uniform RANdom variate generators.
Rvelslant	Downhole seismic analysis.
Rwave	An environment for the time-frequency analysis of 1-D signals (and especially for the wavelet and Gabor transforms of noisy signals), based on the book “Practical Time-Frequency Analysis: Gabor and Wavelet Transforms with an Implementation in S” by Rene Carmona, Wen L. Hwang and Bruno Torresani, 1998, Academic Press.
Ryacac	An R interfaces to the yacas computer algebra system.
SASmixed	Data sets and sample linear mixed effects analyses corresponding to the examples in “SAS System for Mixed Models” by R. C. Littell, G. A. Milliken, W. W. Stroup and R. D. Wolfinger, 1996, SAS Institute.
SASxport	Read and write SAS XPORT files.
SIN	A SINful approach to selection of Gaussian Graphical Markov Models.
SLmisc	Miscellaneous Functions for analysis of gene expression data at SIRS-Lab GmbH.
SMPracticals	Data sets and a few functions for use with the practicals outlined in Appendix A of the book “Statistical Models” by Anthony Davison, 2003, Cambridge University Press.
SNPassoc	SNP-based whole genome association studies.
SNPmaxsel	Maximally selected statistics for SNP data.
SRPM	Shared Reproducibility Package Management.
SQLiteDF	Stores data frames and matrices in SQLite tables.
SciViews	A bundle of packages to implement a full reusable GUI API for R. Contains svGUI with the main GUI features, svDialogs for the dialog boxes, svIO for data import/export, svMisc with miscellaneous supporting functions, and svViews providing views and report features (views are HTML presentations of the content of R objects, combining text, tables and graphs in the same document).
SemiPar	Functions for semiparametric regression analysis, to complement the book “Semiparametric Regression” by R. Ruppert, M. P. Wand, and R. J. Carroll, 2003, Cambridge University Press.
SenSrivastava	Collection of datasets from “Regression Analysis, Theory, Methods and Applications” by A. Sen and M. Srivastava, 1990, Springer.
SensoMineR	Sensory data analysis.
SeqKnn	Sequential KNN imputation.

SharedHT2

Shared Hotelling T^2 test for small sample microarray experiments.

SimHap

A comprehensive modeling framework for epidemiological outcomes and a multiple-imputation approach to haplotypic analysis of population-based data.

Snowball

Snowball stemmers.

SoDA

Utilities and examples from the book “Software for Data Analysis: Programming with R” by John Chambers, Springer, 2008.

SoPhy

Soil Physics Tools: simulation of water flux and solute transport in soil.

SparseLogReg

Sparse logistic regression.

SparseM

Basic linear algebra for sparse matrices.

SpatialNP

Multivariate nonparametric methods based on spatial signs and ranks.

SpherWave

Spherical Wavelets and SW-based spatially adaptive methods.

StatDA

Statistical analysis for environmental data, a companion to the book “Statistical Data Analysis Explained: Applied Environmental Statistics with R” by C. Reimann, P. Filzmoser, R. G. Garrett, and R. Dutter, 2008, John Wiley and Sons.

StatDataML

Read and write StatDataML.

SuppDists

Ten distributions supplementing those built into R (Inverse Gauss, Kruskal-Wallis, Kendall’s Tau, Friedman’s chi squared, Spearman’s rho, maximum F ratio, the Pearson product moment correlation coefficient, Johnson distributions, normal scores and generalized hypergeometric distributions).

SwissAir

Air quality data of Switzerland for one year in 30 min resolution.

Synth

Causal inference using the synthetic control group method.

TIMP

A problem solving environment for fitting superposition models.

TRAMPR

Terminal Restriction Fragment Length Polymorphism (TRFLP) Analysis and Matching Package for R.

TSMysql

Time Series Database Interface extensions for MySQL.

TSP

Traveling Salesperson Problem (TSP).

TSSQLite

Time Series Database Interface extensions for SQLite.

TSdbi

Time Series Database Interface.

TSpadi

Connect to a time series database (e.g., Fame) via PADI (Protocol for Application Database Interface), using the **TSdbi** infrastructure.

TTR

Technical Trading Rules.

TWIX Trees With eXtra splits.

TeachingDemos

A set of demonstration functions that can be used in a classroom to demonstrate statistical concepts, or on your own to better understand the concepts or the programming.

TwslmSpikeWeight

Normalization of cDNA microarray data with the two-way semilinear model (TW-SLM).

TwoWaySurvival

Additive two-way hazards modeling of right censored survival data.

UNF Tools for creating universal numeric fingerprints for data.

USPS Unsupervised and Supervised methods of Propensity Score adjustment for bias.

Umacs Universal MARKov Chain Sampler.

UsingR Data sets to accompany the textbook “Using R for Introductory Statistics” by J. Verzani, 2005, Chapman & Hall/CRC.

VDCutil Utilities supporting VDC, an open source digital library system for quantitative data.

VGAM Vector Generalized Linear and Additive Models.

VLMC Functions, classes & methods for estimation, prediction, and simulation (bootstrap) of VLMC (Variable Length Markov Chain) models.

VaR Methods for calculation of Value at Risk (VaR).

WWGbook

Functions and datasets for the book “Linear Mixed Models: A Practical Guide Using Statistical Software” by B. West, K. Welch, and A. Galecki, 2006, Chapman & Hall/CRC.

WeedMap Map of weed intensity.

WhatIf Software for evaluating counterfactuals.

XML Tools for reading XML documents and DTDs.

YaleToolkit

Data exploration tools from Yale University.

ZIGP Zero Inflated Generalized Poisson (ZIGP) regression models.

Zelig Everyone’s statistical software: an easy-to-use program that can estimate, and help interpret the results of, an enormous range of statistical models.

aaMI Mutual information for protein sequence alignments.

abind Combine multi-dimensional arrays.

accuracy A suite of tools designed to test and improve the accuracy of statistical computation.

acepack	ACE (Alternating Conditional Expectations) and AVAS (Additivity and Variance Stabilization for regression) methods for selecting regression transformations.
actuar	Functions related to actuarial science applications.
ada	Performs boosting algorithms for a binary response.
adabag	Adaboost.M1 and Bagging.
adapt	Adaptive quadrature in up to 20 dimensions.
ade4	Multivariate data analysis and graphical display.
ade4TkGUI	Tcl/Tk Graphical User Interface for ade4 .
adegenet	Genetic data handling for multivariate analysis using ade4 .
adehabitat	A collection of tools for the analysis of habitat selection by animals.
adimpro	Adaptive smoothing of digital images.
adlift	Adaptive Wavelet transforms for signal denoising.
ads	Spatial point patterns analysis.
agce	Analysis of growth curve experiments.
agricolae	Statistical procedures for agricultural research.
agsemisc	Miscellaneous plotting and utility functions.
akima	Linear or cubic spline interpolation for irregularly gridded data.
allelic	A fast, unbiased and exact allelic exact test.
alr3	Methods and data to accompany the textbook “Applied Linear Regression” by S. Weisberg, 2005, Wiley.
amap	Another Multidimensional Analysis Package.
analogue	Analogue methods for palaeoecology.
animation	Demonstrate animations in statistics.
anm	Analog model for statistical/empirical downscaling.
aod	Analysis of Overdispersed Data.
apTreeshape	Analyses of phylogenetic treeshape.
ape	Analyses of Phylogenetics and Evolution, providing functions for reading and plotting phylogenetic trees in parenthetic format (standard Newick format), analyses of comparative data in a phylogenetic framework, analyses of diversification and macroevolution, computing distances from allelic and nucleotide data, reading nucleotide sequences from GenBank via internet, and several tools such as Mantel’s test, computation of minimum spanning tree, or the population parameter theta based on various approaches.

aplpack	Another PLOt PACKage: stem.leaf, bagplot, faces, spin3R, . . .
argosfilter	Argos locations filter.
arm	Data Analysis using Regression and Multilevel/hierarchical models.
arrayImpute	Missing imputation for microarray data.
arrayMissPattern	Exploratory analysis of missing patterns for microarray data.
ars	Adaptive Rejection Sampling.
arules	Mining association rules and frequent itemsets with R.
arulesSequences	Mining frequent sequences.
ash	David Scott's ASH routines for 1D and 2D density estimation.
aspace	Estimating centrographic statistics and computational geometries from spatial point patterns.
assist	A suite of functions implementing smoothing splines.
aster	Functions and datasets for Aster modeling (forest graph exponential family conditional or unconditional canonical statistic models for life history trait modeling).
asypow	A set of routines that calculate power and related quantities utilizing asymptotic likelihood ratio methods.
asuR	Functions and data sets for a lecture in "Advanced Statistics using R".
aws	Functions to perform adaptive weights smoothing.
backtest	Exploring portfolio-based hypotheses about financial instruments.
bayesSurv	Bayesian survival regression with flexible error and (later on also random effects) distributions.
bayescount	Bayesian analysis of count distributions with JAGS.
bayesm	Bayes Inference for Marketing/Micro-econometrics.
bayesmix	Bayesian mixture models of univariate Gaussian distributions using JAGS.
bbmle	Modifications and extensions of stats4 MLE code.
bcp	Bayesian Change Point based on the Barry and Hartigan product partition model.
benchden	28 benchmark densities from Berlinet/Devroye (1994).
betareg	Beta regression for modeling rates and proportions.
bs	Utilities for the Birnbaum-Saunders distribution.
biOps	Basic image operations and image processing.

bicreduc	Reduction algorithm for the NPMLE for the distribution function of bivariate interval-censored data.
biglm	Linear regression for data too large to fit in memory.
bim	Bayesian interval mapping diagnostics: functions to interpret QTLCart and Bmapqtl samples.
binGroup	Evaluation and experimental design for binomial group testing.
binMto	Asymptotic simultaneous confidence intervals for many-to-one comparisons of proportions.
bindata	Generation of correlated artificial binary data.
binom	Binomial confidence intervals for several parameterizations.
bio.infer	Compute biological inferences.
biopara	Self-contained parallel system for R.
bitops	Functions for Bitwise operations on integer vectors.
bivpois	Bivariate Poisson models using the EM algorithm.
blighty	Function for drawing the coastline of the United Kingdom.
blockTools	Block, randomly assign, and diagnose potential problems between units in randomized experiments.
blockrand	Randomization for block random clinical trials.
bnlearn	Bayesian network structure learning.
boa	Bayesian Output Analysis Program for MCMC.
boolean	Boolean logit and probit: a procedure for testing Boolean hypotheses.
boost	Boosting methods for real and simulated data, featuring ‘BagBoost’, ‘Logit-Boost’, ‘AdaBoost’, and ‘L2Boost’.
boot	Functions and datasets for bootstrapping from the book “Bootstrap Methods and Their Applications” by A. C. Davison and D. V. Hinkley, 1997, Cambridge University Press. <i>Recommended.</i>
bootStepAIC	Model selection by bootstrapping the stepAIC() procedure.
bootstrap	Software (bootstrap, cross-validation, jackknife), data and errata for the book “An Introduction to the Bootstrap” by B. Efron and R. Tibshirani, 1993, Chapman and Hall.
bqtl	QTL mapping toolkit for inbred crosses and recombinant inbred lines. Includes maximum likelihood and Bayesian tools.
brainwaver	Basic wavelet analysis of multivariate time series with a vizualisation and parametrization using graph theory.
brew	Templating framework for report generation.

brlr	Bias-reduced logistic regression: fits logistic regression models by maximum penalized likelihood.
butler	Unit testing, profiling and benchmarking for R.
ca	Simple, multiple and joint Correspondence Analysis.
caMassClass	Processing and Classification of protein mass spectra (SELDI) data.
caTools	Miscellaneous utility functions, including reading/writing ENVI binary files, a LogitBoost classifier, and a base64 encoder/decoder.
cacheSweave	Tools for caching Sweave computations.
cacher	Tools for caching and distributing statistical analyses.
cairoDevice	Loadable CAIRO/GTK device driver.
calib	Statistical tool for calibration of plate based bioassays.
calibrate	Calibration of biplot axes.
car	Companion to Applied Regression, containing functions for applied regression, linear models, and generalized linear models, with an emphasis on regression diagnostics, particularly graphical diagnostic methods.
caret	Classification and REgression Training.
caretLSF	Classification and REgression Training, LSF style.
caretNWS	Classification and REgression Training in parallel using NetworkSpaces.
cat	Analysis of categorical-variable datasets with missing values.
catmap	Case-control and TDT meta-analysis package.
catspec	Special models for categorical variables.
cba	Clustering for Business Analytics, including implementations of Proximus and Rock.
cclust	Convex clustering methods, including k -means algorithm, on-line update algorithm (Hard Competitive Learning) and Neural Gas algorithm (Soft Competitive Learning) and calculation of several indexes for finding the number of clusters in a data set.
celsius	Retrieve Affymetrix microarray measurements and metadata from Celsius.
cfa	Analysis of configuration frequencies.
cggd	Continuous Generalized Gradient Descent.
cgh	Analysis of microarray comparative genome hybridisation data using the Smith-Waterman algorithm.
cghFLasso	Hot spot detecting for CGH array data with fused lasso regression.

chplot	Augmented convex hull plots: informative and nice plots for grouped bivariate data.
changeLOS	Change in length of hospital stay (LOS).
chemCal	Calibration functions for analytical chemistry.
choplump	Choplump tests (permutation tests for comparing two groups with some positive but many zero responses).
chron	A package for working with chronological objects (times and dates).
circular	Circular statistics, from “Topics in Circular Statistics” by Rao Jammalamadaka and A. SenGupta, 2001, World Scientific.
clValid	Statistical and biological validation of clustering results.
clac	Clust Along Chromosomes, a method to call gains/losses in CGH array data.
class	Functions for classification (k -nearest neighbor and LVQ). Contained in the ‘VR’ bundle. <i>Recommended</i> .
classGraph	Construct graph of S4 class hierarchies.
classInt	Choose univariate class intervals for mapping or other graphics purposes.
classPP	Projection Pursuit for supervised classification.
classify	Explore classification models in high dimensions.
clim.pact	Climate analysis and downscaling for monthly and daily data.
climatol	Functions to fill missing data in climatological (monthly) series and to test their homogeneity, plus functions to draw wind-rose and Walter&Lieth diagrams.
clines	Calculates Contour Lines.
clinfun	Utilities for clinical study design and data analyses.
clue	CLUster Ensembles.
clustTool	GUI for clustering data with spatial information.
cluster	Functions for cluster analysis. <i>Recommended</i> .
clusterGeneration	Random cluster generation (with specified degree of separation).
clusterRepro	Reproducibility of gene expression clusters.
clusterSim	Searching for optimal clustering procedure for a data set.
clusterfly	Explore clustering interactively using R and GGobi.
clustvarsel	Variable selection for model-based clustering.
clv	Cluster validation techniques.

cmprsk	Estimation, testing and regression modeling of subdistribution functions in competing risks.
cobs99	Constrained B-splines: outdated 1999 version.
cobs	Constrained B-splines: qualitatively constrained (regression) smoothing via linear programming and sparse matrices.
cocorresp	Co-correspondence analysis ordination methods for community ecology.
coda	Output analysis and diagnostics for Markov Chain Monte Carlo (MCMC) simulations.
codetools	Code analysis tools. <i>Recommended</i> for R 2.5.0 or later.
coin	COnditional INference procedures for the general independence problem including two-sample, K -sample, correlation, censored, ordered and multivariate problems.
colorRamp	Builds single and double gradient color maps.
colorspace	Mapping between assorted color spaces.
combinat	Combinatorics utilities.
compOverlapCorr	Comparing overlapping correlation coefficients.
compositions	Functions for the consistent analysis of compositional data (e.g., portions of substances) and positive numbers (e.g., concentrations).
concor	Concordance, providing “SVD by blocks”.
concord	Measures of concordance and reliability.
conf.design	A series of simple tools for constructing and manipulating confounded and fractional factorial designs.
connectedness	Find disconnected sets for two-way classification.
contrast	A collection of contrast methods.
copula	Classes of commonly used copulas (including elliptical and Archimedean), and methods for density, distribution, random number generators, and plotting.
corpora	Utility functions for the statistical analysis of corpus frequency data.
corpcor	Efficient estimation of covariance and (partial) correlation.
corrgram	Plot a correlogram.
covRobust	Robust covariance estimation via nearest neighbor cleaning.
coxphf	Cox regression with Firth’s penalized likelihood.
coxrobust	Robust Estimation in the Cox proportional hazards regression model.

cramer	Routine for the multivariate nonparametric Cramer test.
crossdes	Functions for the construction and randomization of balanced carryover balanced designs, to check given designs for balance, and for simulation studies on the validity of two randomization procedures.
crosshybDetector	Detection of cross-hybridization events in microarray experiments.
crq	Quantile regression for randomly censored data.
cslogistic	Likelihood and posterior analysis of conditionally specified logistic regression models.
cts	Continuous time autoregressive models and the Kalman filter.
ctv	Server-side and client-side tools for CRAN task views.
cwhmisc	Miscellaneous functions by Christian W. Hoffmann.
cyclones	Cyclone identification.
date	Functions for dealing with dates. The most useful of them accepts a vector of input dates in any of the forms ‘8/30/53’, ‘30Aug53’, ‘30 August 1953’, . . . , ‘August 30 53’, or any mixture of these.
dblcens	Calculates the NPMLE of the survival distribution for doubly censored data.
ddesolve	Solver for Delay Differential Equations.
deal	Bayesian networks with continuous and/or discrete variables can be learned and compared from data.
debug	Debugger for R functions, with code display, graceful error recovery, line-numbered conditional breakpoints, access to exit code, flow control, and full keyboard input.
deldir	Calculates the Delaunay triangulation and the Dirichlet or Voronoi tessellation (with respect to the entire plane) of a planar point set.
delt	Estimation of multivariate densities with adaptive histograms.
demogR	Analysis of age-structured demographic models.
denpro	Visualization of multivariate density functions and estimates with level set trees and shape trees, and visualization of multivariate data with tail trees.
depmix	Dependent Mixture Models: fit (multi-group) mixtures of latent Markov models on mixed categorical and continuous (time series) data.
desirability	Desirability function optimization and ranking.
dglm	Double generalized linear models.
diamonds	Functions for illustrating aperture-4 diamond partitions in the plane, or on the surface of an octahedron or icosahedron, for use as analysis or sampling grids.
dice	Calculate probabilities of various dice-rolling events.

dichromat	Color schemes for dichromats: collapse red-green distinctions to simulate the effects of colour-blindness.
digest	Two functions for the creation of “hash” digests of arbitrary R objects using the md5 and sha-1 algorithms permitting easy comparison of R language objects.
diptest	Compute Hartigan’s dip test statistic for unimodality.
dispmod	Functions for modelling dispersion in GLMs.
distr	An object orientated implementation of distributions and some additional functionality.
distrDoc	Documentation for packages distr , distrEx , distrSim , and distrTEst .
distrEx	Extensions of package distr .
distrSim	Simulation classes based on package distr .
distrTEst	Estimation and Testing classes based on package distr .
distributions	Probability distributions based on TI-83 Plus.
diveMove	Dive analysis and calibration.
dlm	Maximum likelihood and Bayesian analysis of Dynamic Linear Models.
doBy	Facilities for groupwise computations.
dplR	Dendrochronology Program Library in R.
dprep	Data preprocessing and visualization functions for classification.
dr	Functions, methods, and datasets for fitting dimension reduction regression, including pHd and inverse regression methods SIR and SAVE.
drc	Non-linear regression analysis for multiple curves with focus on concentration-response, dose-response and time-response curves.
drm	Regression and association models for clustered categorical responses.
drfit	Dose-response data evaluation.
dse	Dynamic System Estimation, a multivariate time series package bundle. Contains dse1 (the base system, including multivariate ARMA and state space models) and dse2 (extensions for evaluating estimation techniques, forecasting, and for evaluating forecasting model).
dt	Discrete Trigonometric Transforms.
dyn	Time series regression.
dynamicGraph	Interactive graphical tool for manipulating graphs.
dynlm	Dynamic linear models and time series regression.
e1071	Miscellaneous functions used at the Department of Statistics at TU Wien (E1071), including moments, short-time Fourier transforms, Independent Component Analysis, Latent Class Analysis, support vector machines, and fuzzy clustering, shortest path computation, bagged clustering, and some more.

eRm	Estimating extended Rasch models.
earth	Earth: multivariate adaptive regression spline models.
eba	Fitting and testing probabilistic choice models, especially the BTL, elimination-by-aspects (EBA), and preference tree (Pretree) models.
ecespa	Functions and data for spatial point pattern analysis.
eco	Fitting Bayesian models of ecological inference in 2 by 2 tables.
ecodist	Dissimilarity-based functions for ecological analysis.
edci	Edge Detection and Clustering in Images.
effects	Graphical and tabular effect displays, e.g., of interactions, for linear and generalised linear models.
eha	A package for survival and event history analysis.
eiPack	Ecological inference and higher-dimension data management.
eigenmodel	Semiparametric factor and regression models for symmetric relational data.
elasticnet	Elastic net regularization and variable selection.
ellipse	Package for drawing ellipses and ellipse-like confidence regions.
elliptic	A suite of elliptic and related functions including Weierstrass and Jacobi forms.
elrm	Exact Logistic Regression via MCMC.
emdbook	Data sets and auxiliary functions for “Ecological Models and Data” by Ben Bolker (work in progress).
emme2	Functions to read from and write to an EMME/2 databank.
emplik	Empirical likelihood ratio for means/quantiles/hazards from possibly right censored data.
energy	E-statistics (energy) tests for comparing distributions: multivariate normality, Poisson test, multivariate k -sample test for equal distributions, hierarchical clustering by e-distances.
ensembleBMA	Probabilistic forecasting using Bayesian Model Averaging of ensembles using a mixture of normal distributions.
epibasix	Elementary functions for epidemiological analysis.
epicalc	Epidemiological calculator.
epitools	Basic tools for applied epidemiology.
epsi	Edge Preserving Smoothing for Images.
equivalence	Tests and graphics for assessing tests of equivalence.

evd	Functions for extreme value distributions. Extends simulation, distribution, quantile and density functions to univariate, bivariate and (for simulation) multivariate parametric extreme value distributions, and provides fitting functions which calculate maximum likelihood estimates for univariate and bivariate models.
evdbayes	Functions for the bayesian analysis of extreme value models, using MCMC methods.
evir	Extreme Values in R: Functions for extreme value theory, which may be divided into the following groups; exploratory data analysis, block maxima, peaks over thresholds (univariate and bivariate), point processes, gev/gpd distributions.
exactLoglinTest	Monte Carlo exact tests for log-linear models.
exactRankTests	Computes exact p -values and quantiles using an implementation of the Streitberg/Roehmel shift algorithm.
exactmaxsel	Exact methods for maximally selected statistics for binary response variables.
experiment	Designing and analyzing randomized experiments.
extRemes	Extreme value toolkit.
fArma	The Rmetrics module for “ARMA Time Series Modelling”.
fAsianOptions	The Rmetrics module for “Option Valuation”.
fAssets	The Rmetrics module for “Assets Selection and Modelling”.
fBasics	The Rmetrics module for “Markets and Basic Statistics”.
fBonds	The Rmetrics module for “Bonds and Interest Rate Models”.
fCalendar	The Rmetrics module for “Chronological and Calendarical Objects”.
fCopulae	The Rmetrics module for “Dependence Structures with Copulas”.
fEcofin	The Rmetrics module for “Economic and Financial Data Sets”.
fExoticOptions	The Rmetrics module for “Option Valuation”.
fExtremes	The Rmetrics module for “Extreme Financial Market Data”.
fGarch	The Rmetrics module for “Autoregressive Conditional Heteroskedastic Modelling”.
fImport	The Rmetrics module for “Chronological and Calendarical Objects”.
fMultivar	The Rmetrics module for “Multivariate Market Analysis”.
fNonlinear	The Rmetrics module for “Nonlinear and Chaotic Time Series Modelling”.

fOptions	The Rmetrics module for “Basics of Option Valuation”.
fPortfolio	The Rmetrics module for “Portfolio Selection and Optimization”.
fRegression	The Rmetrics module for “Regression Based Decision and Prediction”.
fSeries	The Rmetrics module for “Financial Time Series Objects”.
fTrading	The Rmetrics module for “Technical Trading Analysis”.
fUnitRoots	The Rmetrics module for “The Dynamical Process Behind Markets”.
fUtilities	The Rmetrics module for “Rmetrics Function Utilities”.
fame	Interface for FAME time series database.
far	Modelization for Functional AutoRegressive processes.
faraway	Functions and datasets for books by Julian Faraway.
fastICA	Implementation of FastICA algorithm to perform Independent Component Analysis (ICA) and Projection Pursuit.
fda	Functional Data Analysis: analysis of data where the basic observation is a function of some sort.
fdim	Functions for calculating fractal dimension.
fdrtool	Estimation and control of (local) False Discovery Rates.
feature	Feature significance for multivariate kernel density estimation.
femmeR	Output analysis of FEMME model results.
ff	Flat file database designed for large vectors and multi-dimensional arrays.
ffmanova	Fifty-fifty MANOVA.
fgac	Families of Generalized Archimedean Copulas.
fields	A collection of programs for curve and function fitting with an emphasis on spatial data. The major methods implemented include cubic and thin plate splines, universal Kriging and Kriging for large data sets. The main feature is that any covariance function implemented in R can be used for spatial prediction.
filehash	Simple file-based hash table.
filehashSQLite	Simple key-value database using SQLite as the backend.
financial	Solving financial problems in R.
fingerprint	Functions to operate on binary fingerprint data.
flexclust	Flexible cluster algorithms.
flexmix	Flexible Mixture Modeling: a general framework for finite mixtures of regression models using the EM algorithm.

fmri	Functions for the analysis of fMRI experiments.
forecasting	A bundle with functions and datasets for forecasting. Contains forecast (time series forecasting), fma (data sets from the book “Forecasting: Methods and Applications” by Makridakis, Wheelwright & Hyndman, 1998), and Mcomp (data from the M-competitions).
foreign	Functions for reading and writing data stored by statistical software like Minitab, S, SAS, SPSS, Stata, Systat, etc. <i>Recommended</i> .
forensic	Statistical methods in forensic genetics.
fork	Functions for handling multiple processes: simple wrappers around the Unix process management API calls.
fortunes	R fortunes.
forward	Forward search approach to robust analysis in linear and generalized linear regression models.
fpc	Fixed point clusters, clusterwise regression and discriminant plots.
fracdiff	Maximum likelihood estimation of the parameters of a fractionally differenced ARIMA(p, d, q) model (Haslett and Raftery, Applied Statistics, 1989).
fractal	Insightful fractal time series modeling and analysis.
frailtypack	Fit a shared gamma frailty model and Cox proportional hazards model using a Penalized Likelihood on the hazard function.
fso	Fuzzy set ordination.
ftnonpar	Features and strings for nonparametric regression.
fuzzyFDR	Exact calculation of fuzzy decision rules for multiple testing.
fuzzyRankTests	Fuzzy rank tests and confidence intervals.
g.data	Create and maintain delayed-data packages (DDP's).
gRbase	A package for graphical modelling in R. Defines S4 classes for graphical meta data and graphical models, and illustrates how hierarchical log-linear models may be implemented and combined with dynamicGraph .
gRcox	Inference in graphical gaussian models with edge and vertex symmetries.
gWidgets	gWidgets API for building toolkit-independent, interactive GUIs.
gWidgetsRGtk2	Toolkit implementation of gWidgets for RGtk2 .
gWidgetsRJava	Toolkit implementation of gWidgets for rJava .
gWidgetstcltk	Toolkit implementation of gWidgets for tcltk .

gafit	Genetic algorithm for curve fitting.
gam	Functions for fitting and working with Generalized Additive Models, as described in chapter 7 of the White Book, and in “Generalized Additive Models” by T. Hastie and R. Tibshirani (1990).
gamair	Data sets used in the book “Generalized Additive Models: An Introduction with R” by S. Wood (2006).
gamlss	Functions to fit Generalized Additive Models for Location Scale and Shape.
gamlss.cens	A GAMLSS add on package for censored data.
gamlss.dist	Extra distributions for GAMLSS modeling.
gamlss.mx	A GAMLSS add on package for fitting mixture distributions.
gamlss.nl	A GAMLSS add on package for fitting non linear parametric models.
gamlss.tr	A GAMLSS add on for generating and fitting truncated (gamlss.family) distributions.
gap	Genetic analysis package for both population and family data.
gbev	Gradient Boosted regression trees with Errors-in-Variables.
gbm	Generalized Boosted Regression Models: implements extensions to Freund and Schapire’s AdaBoost algorithm and J. Friedman’s gradient boosting machine. Includes regression methods for least squares, absolute loss, logistic, Poisson, Cox proportional hazards partial likelihood, and AdaBoost exponential loss.
gcl	Compute a fuzzy rules or tree classifier from data.
gclus	Clustering Graphics. Orders panels in scatterplot matrices and parallel coordinate displays by some merit index.
gcmrec	Parameters estimation of the general semiparametric model for recurrent event data proposed by Peña and Hollander.
gdata	Various functions to manipulate data.
gee	An implementation of the Liang/Zeger generalized estimating equation approach to GLMs for dependent data.
geepack	Generalized estimating equations solver for parameters in mean, scale, and correlation structures, through mean link, scale link, and correlation link. Can also handle clustered categorical responses.
geiger	Analysis of evolutionary diversification.
genalg	R based genetic algorithm for binary and floating point chromosomes.
genetics	Classes and methods for handling genetic data. Includes classes to represent genotypes and haplotypes at single markers up to multiple markers on multiple chromosomes, and functions for allele frequencies, flagging homo/heterozygotes, flagging carriers of certain alleles, computing disequilibrium, testing Hardy-Weinberg equilibrium, . . .

geoR	Functions to perform geostatistical data analysis including model-based methods.
geoRglm	Functions for inference in generalised linear spatial models.
geometry	Mesh generation and surface tessellation, based on the Qhull library.
ggm	Functions for defining directed acyclic graphs and undirected graphs, finding induced graphs and fitting Gaussian Markov models.
ggplot	Grammar of graphics based plots for R.
ggplot2	An implementation of the Grammar of Graphics in R.
ghyp	Univariate and multivariate generalized hyperbolic distributions.
giRaph	Data structures and algorithms for computations on graphs.
gld	Basic functions for the generalised (Tukey) lambda distribution.
gllm	Routines for log-linear models of incomplete contingency tables, including some latent class models via EM and Fisher scoring approaches.
glmcc	Fitting Generalized Linear Models subject to Constraints.
glmmAK	Generalized Linear Mixed Models.
glmmML	A Maximum Likelihood approach to generalized linear models with random intercept.
glmPath	L1 regularization path for Generalized Linear Models.
glpk	Interface to the GNU Linear Programming Kit (GLPK).
gmodels	Various functions to manipulate models.
gmp	Arithmetic “without limitations” using the GNU Multiple Precision library.
gmt	Interface between the GMT 4.0 map-making software and R.
gnm	Functions to specify and fit generalized nonlinear models, including models with multiplicative interaction terms such as the UNIDIFF model from sociology and the AMMI model from crop science.
gpclib	General polygon clipping routines for R based on Alan Murta’s C library.
gpls	Classification using generalized partial least squares for two-group and multi-group (more than 2 group) classification.
gplots	Various functions to draw plots.
grImport	Importing vector graphics.
granova	Graphical Analysis of Variance.
graph	Handling of graph data structures.
grasp	Generalized Regression Analysis and Spatial Predictions for R.
gregmisc	Miscellaneous functions written/maintained by Gregory R. Warnes.
gridBase	Integration of base and grid graphics.

grnnR	A Generalized Regression Neural Network.
grouped	Regression models for grouped and coarse data, under the Coarsened At Random assumption.
grplasso	Fit user specified models with group lasso penalty.
gsl	Wrapper for special functions of the Gnu Scientific Library (GSL).
gss	A comprehensive package for structural multivariate function estimation using smoothing splines.
gstat	multivariable geostatistical modelling, prediction and simulation. Includes code for variogram modelling; simple, ordinary and universal point or block (co)kriging, sequential Gaussian or indicator (co)simulation, and map plotting functions.
gsubfn	Miscellaneous string utilities.
gtkDevice	GTK graphics device driver that may be used independently of the R-GNOME interface and can be used to create R devices as embedded components in a GUI using a Gtk drawing area widget, e.g., using RGtk.
gtools	Various functions to help manipulate data.
gvlna	Global Validation of Linear Models Assumptions.
hapassoc	Likelihood inference of trait associations with SNP haplotypes and other attributes using the EM Algorithm.
haplo.ccs	Estimate haplotype relative risks in case-control data.
haplo.stats	Statistical analysis of haplotypes with traits and covariates when linkage phase is ambiguous.
hapsim	Haplotype data simulation.
hbim	Hill/Bliss Independence Model for combination vaccines.
hddplot	Use known groups in high-dimensional data to derive scores for plots.
hdeco	Hierarchical DECOMposition of entropy for categorical map comparisons.
hdf5	Interface to the NCSA HDF5 library.
hdrode	Highest Density Regions and Conditional Density Estimation.
heatmap.plus	Heatmap with sensible behavior.
heplots	Visualizing tests in multivariate linear models.
hett	Functions for the fitting and summarizing of heteroscedastic t-regression.
hexView	Viewing binary files.
hier.part	Hierarchical Partitioning: variance partition of a multivariate data set.

hierfstat	Estimation of hierarchical F-statistics from haploid or diploid genetic data with any numbers of levels in the hierarchy, and tests for the significance of each F and variance components.
hints	Provide hints on what to do next.
hmm.discnp	Hidden Markov models with discrete non-parametric observation distributions.
hoa	A bundle of packages for higher order likelihood-based inference. Contains cond for approximate conditional inference for logistic and loglinear models, csampling for conditional simulation in regression-scale models, marg for approximate marginal inference for regression-scale models, and nlreg for higher order inference for nonlinear heteroscedastic models.
homals	Homogeneity Analysis (HOMALS) package with optional Tcl/Tk interface.
homtest	Homogeneity tests for regional frequency analysis.
hopach	Hierarchical Ordered Partitioning and Collapsing Hybrid (HOPACH).
hot	Computation on micro-arrays.
howmany	A lower bound for the number of correct rejections.
httpRequest	Implements HTTP Request protocols (GET, POST, and multipart POST requests).
hwde	Models and tests for departure from Hardy-Weinberg equilibrium and independence between loci.
hybridHclust	Hybrid hierarchical clustering via mutual clusters.
hydrosanity	Graphical user interface for exploring hydrological time series.
ibdreg	Regression methods for IBD linkage with covariates.
identity	Jacquard condensed coefficients of identity.
ifa	Independent Factor Analysis.
ifs	Iterated Function Systems distribution function estimator.
ifultools	Insightful research tools.
ig	Robust and classical versions of the inverse Gaussian distribution.
igraph	Routines for simple graphs.
iid.test	Testing whether data is independent and identically distributed.
impute	Imputation for microarray data (currently KNN only).
ineq	Inequality, concentration and poverty measures, and Lorenz curves (empirical and theoretic).
inetwork	Network analysis and plotting.

inline	Inline C/C++ function calls from R.
intcox	Implementation of the Iterated Convex Minorant Algorithm for the Cox proportional hazard model for interval censored event data.
iplots	Interactive graphics for R.
ipred	Improved predictive models by direct and indirect bootstrap aggregation in classification and regression as well as resampling based estimators of prediction error.
irr	Coefficients of Interrater Reliability and Agreement for quantitative, ordinal and nominal data.
irtoys	Simple interface to the estimation and plotting of IRT models.
ismev	Functions to support the computations carried out in “An Introduction to Statistical Modeling of Extreme Values;” by S. Coles, 2001, Springer. The functions may be divided into the following groups; maxima/minima, order statistics, peaks over thresholds and point processes.
its	An S4 class for handling irregular time series.
kappalab	The “laboratory for capacities”, an S4 tool box for capacity (or non-additive measure, fuzzy measure) and integral manipulation on a finite setting.
kernelPop	Spatially explicit population genetic simulations.
kernlab	Kernel-based machine learning methods including support vector machines.
kin.cohort	Analysis of kin-cohort studies.
kinship	Mixed-effects Cox models, sparse matrices, and modeling data from large pedigrees.
kknn	Weighted k -nearest neighbors classification and regression.
klaR	Miscellaneous functions for classification and visualization developed at the Department of Statistics, University of Dortmund.
klin	Linear equations with Kronecker structure.
km.ci	Confidence intervals for the Kaplan-Meier estimator.
knnFinder	Fast nearest neighbor search.
knnTree	Construct or predict with k -nearest-neighbor classifiers, using cross-validation to select k , choose variables (by forward or backwards selection), and choose scaling (from among no scaling, scaling each column by its SD, or scaling each column by its MAD). The finished classifier will consist of a classification tree with one such k -nn classifier in each leaf.
knncat	Nearest-neighbor classification with categorical variables.
knnflex	A more flexible k -NN.
kohonen	Supervised and unsupervised self-organising maps.
ks	Kernel smoothing: bandwidth matrices for kernel density estimators and kernel discriminant analysis for bivariate data.

kza	Kolmogorov-Zurbenko Adaptive filter for locating change points in a time series.
kzft	Kolmogorov-Zurbenko Fourier Transform and application.
kzs	Kolmogorov-Zurbenko Spline.
labdsv	Laboratory for Dynamic Synthetic Vegetation Phenomenology.
labstatR	Functions for the book “Laboratorio di statistica con R” by S. M. Iacus and G. Masarotto, 2002, McGraw-Hill. Function names and documentation in Italian.
lancet.iraqmortality	Surveys of Iraq mortality published in The Lancet.
languageR	Data sets and functions for the book “Analyzing Linguistic Data: A practical introduction to statistics” by R. H. Baayen, 2007, Cambridge: Cambridge University Press.
lars	Least Angle Regression, Lasso and Forward Stagewise: efficient procedures for fitting an entire lasso sequence with the cost of a single least squares fit.
laser	Likelihood Analysis of Speciation/Extinction Rates from phylogenies.
lasso2	Routines and documentation for solving regression problems while imposing an L1 constraint on the estimates, based on the algorithm of Osborne et al. (1998).
latentnet	Latent position and cluster models for statistical networks.
lattice	Lattice graphics, an implementation of Trellis Graphics functions. <i>Recommended.</i>
latticeExtra	Generic functions and standard methods for Trellis-based displays.
lawstat	Statistical tests widely utilized in biostatistics, public policy and law.
lazy	Lazy learning for local regression.
ldDesign	Design of experiments for detection of linkage disequilibrium,
ldbounds	Lan-DeMets method for group sequential boundaries.
leaps	A package which performs an exhaustive search for the best subsets of a given set of potential regressors, using a branch-and-bound algorithm, and also performs searches using a number of less time-consuming techniques.
lga	Tools for Linear Grouping Analysis (LGA).
lgtdl	A set of methods for longitudinal data objects.
lhs	Latin Hypercube Samples.
linprog	Solve linear programming/linear optimization problems by using the simplex algorithm.
ljr	Logistic Joinpoint Regression.
lme4	Fit linear and generalized linear mixed-effects models.

lmeSplines	Fit smoothing spline terms in Gaussian linear and nonlinear mixed-effects models.
lmm	Linear mixed models.
lmomco	<i>L</i> -moments and <i>L</i> -comoments.
lmtest	A collection of tests on the assumptions of linear regression models from the book “The linear regression model under test” by W. Kraemer and H. Sonnberger, 1986, Physica.
locfdr	Computation of local false discovery rates.
locfit	Local Regression, likelihood and density estimation.
lodplot	Assorted plots of location score versus genetic map position.
logcondens	Estimate a log-concave probability density from i.i.d. observations.
logilasso	Analysis of sparse contingency tables with penalization approaches.
logistf	Firth’s bias reduced logistic regression approach with penalized profile likelihood based confidence intervals for parameter estimates.
logspline	Logspline density estimation.
lokern	Kernel regression smoothing with adaptive local or global plug-in bandwidth selection.
longmemo	Datasets and Functionality from the textbook “Statistics for Long-Memory Processes” by J. Beran, 1994, Chapman & Hall.
lpSolve	Functions that solve general linear/integer problems, assignment problems, and transportation problems via interfacing Lp_solve.
lpbridge	Local polynomial (ridge) regression.
lsa	Latent Semantic Analysis.
lspls	LS-PLS (least squares — partial least squares) models.
lss	Accelerated failure time model to right censored data based on least-squares principle.
ltm	Analysis of multivariate Bernoulli data using latent trait models (including the Rasch model) under the Item Response Theory approach.
ltsa	Linear Time Series Analysis.
luca	Likelihood Under Covariate Assumptions (LUCA).
lvplot	Letter-value box plots.
mAr	Estimation of multivariate AR models through a computationally efficient step-wise least-squares algorithm.
mFilter	Miscellaneous time series filters.

maanova	Analysis of N -dye Micro Array experiments using mixed model effect. Contains analysis of variance, permutation and bootstrap, cluster and consensus tree.
magic	A variety of methods for creating magic squares of any order greater than 2, and various magic hypercubes.
mapLD	Linkage Disequilibrium mapping.
mapdata	Supplement to package maps , providing the larger and/or higher-resolution databases.
mapproj	Map Projections: converts latitude/longitude into projected coordinates.
maps	Draw geographical maps. Projection code and larger maps are in separate packages.
maptools	Set of tools for manipulating and reading geographic data, in particular ESRI shapefiles.
maptree	Functions with example data for graphing and mapping models from hierarchical clustering and classification and regression trees.
mathgraph	Tools for constructing and manipulating objects from a class of directed and undirected graphs.
matlab	Emulate MATLAB code using R.
matrixcalc	Collection of functions for matrix differential calculus.
maxstat	Maximally selected rank and Gauss statistics with several p-value approximations.
mblm	Median-based Linear models, using Theil-Sen single or Siegel repeated medians.
mboost	Gradient boosting for fitting generalized linear, additive and interaction models.
mcgibbsit	Warnes and Raftery's MCGibbsit MCMC diagnostic.
mclust	Model-based clustering and normal mixture modeling including Bayesian regularization.
mclust02	Model-based cluster analysis: the 2002 version of MCLUST.
mcmc	Functions for Markov Chain Monte Carlo (MCMC).
mda	Code for mixture discriminant analysis (MDA), flexible discriminant analysis (FDA), penalized discriminant analysis (PDA), multivariate additive regression splines (MARS), adaptive back-fitting splines (BRUTO), and penalized regression.
meboot	Maximum entropy bootstrap for time series.
mefa	Faunistic count data handling and reporting.
meifly	Interactive model exploration using GGobi.
memisc	Miscellaneous Tools for data management, simulation, and presentation of estimates.

merror	Accuracy and precision of measurements.
meta	Fixed and random effects meta-analysis, with functions for tests of bias, forest and funnel plot.
mfp	Multiple Fractional Polynomials.
mgcv	Routines for GAMs and other generalized ridge regression problems with multiple smoothing parameter selection by GCV or UBRE. <i>Recommended.</i>
micEcon	Tools for microeconomic analysis and microeconomic modelling.
mice	Multivariate Imputation by Chained Equations.
mimR	An R interface to MIM for graphical modeling in R.
minpack.lm	R interface for two functions from the MINPACK least squares optimization library, solving the nonlinear least squares problem by a modification of the Levenberg-Marquardt algorithm.
misc3d	A collection of miscellaneous 3d plots, including rgl-based isosurfaces.
mitools	Tools to perform analyses and combine results from multiple-imputation datasets.
mix	Estimation/multiple imputation programs for mixed categorical and continuous data.
mixPHM	Mixtures of proportional hazard models.
mixreg	Functions to fit mixtures of regressions.
mixstock	Mixed stock analysis functions.
mixtools	Tools for mixture models.
mlCopulaSelection	Copula selection and fitting using maximum likelihood.
mlbench	A collection of artificial and real-world machine learning benchmark problems, including the Boston housing data.
mlegp	Maximum Likelihood Estimates of Gaussian Processes.
mlca	Independent Component Analysis using Maximum Likelihood.
mlmRev	Examples from Multilevel Modelling Software Review.
mlmmm	Maximum likelihood estimation under multivariate linear mixed models with missing values.
mmclr	Mixed-mode latent class regression (also known as mixed-mode mixture model regression or mixed-mode mixture regression models) which can handle both longitudinal and one-time responses.
mnormt	The multivariate normal and t distributions.
moc	Fits a variety of mixtures models for multivariate observations with user-defined distributions and curves.

modeest	Mode estimation and Chernoff distribution.
modehunt	Multiscale analysis for density functions.
modeltools	A collection of tools to deal with statistical models.
mokken	Mokken Scale Analysis for test and questionnaire data.
moments	Moments, skewness, kurtosis and related tests.
monomvn	Estimation for multivariate normal data with monotone missingness.
monreg	Estimation of monotone regression and variance functions in nonparametric models.
monoProc	Strictly monotone smoothing procedure.
mota	Mean Optimal Transformation Approach.
mprobit	Multivariate probit model for binary/ordinal response.
mra	Analysis of capture-recapture data.
mratios	Inferences for ratios of coefficients in the general linear model.
msm	Functions for fitting continuous-time Markov multi-state models to categorical processes observed at arbitrary times, optionally with misclassified responses, and covariates on transition or misclassification rates.
muS2RC	S-plus to R Compatibility for package muStat .
muhaz	Hazard function estimation in survival analysis.
multcomp	Multiple comparison procedures for the one-way layout.
multcompView	Visualizations of paired comparisons.
multic	Quantitative linkage analysis tools using the variance components approach.
multilevel	Analysis of multilevel data by organizational and social psychologists.
multinomRob	Overdispersed multinomial regression using robust (LQD and tanh) estimation.
multtest	Resampling-based multiple hypothesis testing.
mvbutils	Utilities by Mark V. Bravington for project organization, editing and backup, sourcing, documentation (formal and informal), package preparation, macro functions, and more.
mvnmle	ML estimation for multivariate normal data with missing values.
mvnormtest	Generalization of the Shapiro-Wilk test for multivariate variables.
mvtnormpcs	Multivariate Normal and T Distribution functions of Dunnett (1989).

mvoutlier	Multivariate outlier detection based on robust estimates of location and covariance structure.
mvpart	Multivariate partitioning.
mvtnorm	Multivariate normal and t distributions.
nFDR	Nonparametric Estimate of FDR Based on Bernstein polynomials.
nFactors	Non-graphical solution to the Cattell Scree Test.
ncdf	Interface to Unidata netCDF data files.
ncomplete	Functions to perform the regression depth method (RDM) to binary regression to approximate the minimum number of observations that can be removed such that the reduced data set has complete separation.
ncvar	High-level R interface to netCDF datasets.
negenes	Estimating the number of essential genes in a genome on the basis of data from a random transposon mutagenesis experiment, through the use of a Gibbs sampler.
network	Tools to create and modify network objects, which can represent a range of relational data types.
neural	RBF and MLP neural networks with graphical user interface.
nice	Get or set UNIX priority (niceness) of running R process.
nlme	Fit and compare Gaussian linear and nonlinear mixed-effects models. <i>Recommended.</i>
nlmeODE	Combine the nlme and odesolve packages for mixed-effects modelling using differential equations.
nlstools	Tools for nonlinear regression diagnostics.
nltn	NonLinear Transformation Models for survival analysis.
nnet	Software for single hidden layer perceptrons (“feed-forward neural networks”), and for multinomial log-linear models. Contained in the ‘VR’ bundle. <i>Recommended.</i>
nnls	The Lawson-Hanson NNLS algorithm for non-negative least squares.
nonbinROC	ROC-type analysis for non-binary gold standards.
nor1mix	One-dimensional normal mixture models classes, for, e.g., density estimation or clustering algorithms research and teaching; providing the widely used Marron-Wand densities.
norm	Analysis of multivariate normal datasets with missing values.
normalp	A collection of utilities for normal of order p distributions (General Error Distributions).
nortest	Five omnibus tests for the composite hypothesis of normality.

noverlap	Functions to perform the regression depth method (RDM) to binary regression to approximate the amount of overlap, i.e., the minimal number of observations that need to be removed such that the reduced data set has no longer overlap.
np	Nonparametric kernel smoothing methods for mixed datatypes.
npmc	Nonparametric Multiple Comparisons: provides simultaneous rank test procedures for the one-way layout without presuming a certain distribution.
nsRFA	Non-supervised Regional Frequency Analysis.
numDeriv	Accurate numerical derivatives.
nws	Functions for NetWorkSpaces and Sleigh.
oc	Optimal Classification roll call analysis.
oce	Analysis of oceanographic data.
odesolve	An interface for the Ordinary Differential Equation (ODE) solver lsoda. ODEs are expressed as R functions.
odfWeave	Sweave processing of Open Document Format (ODF) files.
onion	A collection of routines to manipulate and visualize quaternions and octonions.
optmatch	Functions to perform optimal matching, particularly full matching.
orientlib	Representations, conversions and display of orientation SO(3) data.
ouch	Ornstein-Uhlenbeck models for phylogenetic comparative hypotheses.
outliers	A collection of some tests commonly used for identifying outliers.
oz	Functions for plotting Australia's coastline and state boundaries.
pARtial	(Partial) attributable risk estimates, corresponding variance estimates and confidence intervals.
pairwiseCI	Calculate and plot unadjusted confidence intervals for two sample comparisons.
paleoTS	Modeling evolution in paleontological time-series.
paleoTSalt	Modeling evolution in paleontological time-series (alternate parameterization).
pamr	Pam: Prediction Analysis for Microarrays.
pan	Multiple imputation for multivariate panel or clustered data.
panel	Functions and datasets for fitting models to Panel data.
papply	Parallel apply function using MPI.
paran	Horn's test of principal components/factors.
partitions	Additive partitions of integers.
partsm	Periodic AutoRegressive Time Series Models.
party	Unbiased recursive partitioning in a conditional inference framework.

pastecs	Package for Analysis of Space-Time Ecological Series.
pbatR	Frontend to PBAT to run within R.
pcaPP	Robust PCA by Projection Pursuit.
pcalg	Standard and robust estimation of the skeleton (ugraph) of a Directed Acyclic Graph (DAG) via the PC algorithm.
pcse	Panel-Corrected Standard Error estimation.
pcurve	Fits a principal curve to a numeric multivariate dataset in arbitrary dimensions. Produces diagnostic plots. Also calculates Bray-Curtis and other distance matrices and performs multi-dimensional scaling and principal component analyses.
pear	Periodic Autoregression Analysis.
penalized	Penalized estimation in generalized linear models.
permax	Functions intended to facilitate certain basic analyses of DNA array data, especially with regard to comparing expression levels between two types of tissue.
permtest	Permutation test to compare variability within and distance between two groups.
perturb	Perturbation analysis for evaluating collinearity.
pgam	Poisson-Gamma Additive Models.
pgirmess	Functions for analysis and display of ecological and spatial data.
pheno	Some easy-to-use functions for time series analyses of (plant-) phenological data sets.
phpSerialize	Serialize R to PHP associative array.
pinktoe	Converts S trees to HTML/Perl files for interactive tree traversal.
pixmap	Functions for import, export, plotting and other manipulations of bitmapped images.
plRasch	Log linear by linear association models.
playwith	A GUI for interactive plots using GTK+.
plink	Separate calibration linking methods.
plm	Linear models for panel data.
plotAndPlayGTK	A GUI for interactive plots using GTK.
plotrix	Various useful functions for enhancing plots.
plugdensity	Kernel density estimation with global bandwidth selection via “plug-in”.
pls	Partial Least Squares Regression (PLSR) and Principal Component Regression (PCR).

plsgenomics	PLS analyses for genomics.
pmg	Poor Man's GUI.
pmml	Generate Predictive Modelling Markup Language (PMML) for various models.
poLCA	POLytomous variable Latent Class Analysis.
polspline	Routines for the polynomial spline fitting routines hazard regression, hazard estimation with flexible tails, logspline, lspec, polyclass, and polymars, by C. Kooperberg and co-authors.
polyapost	Simulating from the Polya posterior.
polycor	Polychoric and polyserial correlations.
polynom	A collection of functions to implement a class for univariate polynomial manipulations.
pomp	Partially-observed Markov processes.
popbio	Construction and analysis of matrix population models.
popgen	Statistical and POPulation GENetics.
poplab	Population Lab, a tool for constructing a virtual electronic population evolving over time.
portfolio	Classes for analyzing and implementing portfolios.
portfolioSim	Framework for simulating equity portfolio strategies.
powell	Optimizes a function using Powell's UObyQA algorithm.
powerpkg	Power analyses for the affected sib pair and the TDT design.
ppc	Sample classification of protein mass spectra by peak probability contrasts.
ppls	Penalized Partial Least Squares.
pps	Functions to select samples using PPS (probability proportional to size) sampling, for stratified simple random sampling, and to compute joint inclusion probabilities for Sampford's method of PPS sampling.
prabclus	Distance based parametric bootstrap tests for clustering, mainly thought for presence-absence data (clustering of species distribution maps). Jaccard and Kulczynski distance measures, clustering of MDS scores, and nearest neighbor based noise detection.
predbayescor	Classification rule based on Bayesian naive Bayes models with feature selection bias corrected.
predmixcor	Classification rule based on Bayesian mixture models with feature selection bias corrected.

prettyR	Pretty descriptive stats.
prim	Patient Rule Induction Method (PRIM).
princurve	Fits a principal curve to a matrix of points in arbitrary dimension.
proftools	Profile output processing tools for R.
proj4	A simple interface to the PROJ.4 cartographic projections library.
proptest	Tests of the proportional hazards assumption in the Cox model.
proto	An object oriented system using prototype or object-based (rather than class-based) object oriented ideas.
proxy	Distance and similarity measures.
pscl	R in the Political Science Computational Laboratory, Stanford University.
pseudo	Pseudo-observations.
pspline	Smoothing splines with penalties on order m derivatives.
psy	Various procedures used in psychometry: Kappa, ICC, Cronbach alpha, screeplot, PCA and related methods.
psych	Procedures for personality and psychological research.
psychometric	Applied psychometric theory: functions useful for correlation theory, meta-analysis (validity-generalization), reliability, item analysis, inter-rater reliability, and classical utility.
psyphy	Functions for analyzing psychophysical data in R.
pwr	Basic functions for power analysis.
pvclust	Hierarchical clustering with p -value.
qcc	Quality Control Charts. Shewhart quality control charts for continuous, attribute and count data. Cusum and EWMA charts. Operating characteristic curves. Process capability analysis. Pareto chart and cause-and-effect chart.
qgen	Quantitative Genetics using R.
qp	q -order partial correlation graph search algorithm.
qtl	Analysis of experimental crosses to identify QTLs.
qtlDesign	Tools for the design of QTL experiments.
qtlbim	QTL Bayesian Interval Mapping.
quadprog	For solving quadratic programming problems.
qualV	Qualitative methods for the validation of models.
quantchem	Quantitative chemical analysis: calibration and evaluation of results.
quantmod	Quantitative financial modelling framework.

quantreg	Quantile regression and related methods.
quantregForest	Quantile Regression Forests, a tree-based ensemble method for estimation of conditional quantiles.
qvalue	Q-value estimation for false discovery rate control.
qvcalc	Functions to compute quasi-variances and associated measures of approximation error.
rJava	Low-level R to Java interface. Allows creation of objects, calling methods and accessing fields.
race	Implementation of some racing methods for the empirical selection of the best.
rake	Raking survey datasets by re-weighting.
ramps	Bayesian geostatistical modeling of Gaussian processes using a reparameterized and marginalized posterior sampling (RAMPS) algorithm.
randaes	Random number generator based on AES cipher.
random	True random numbers using random.org.
randomSurvivalForest	Ishwaran and Kogalur's random survival forest.
randomForest	Breiman's random forest classifier.
rankreg	Rank regression estimator for the AFT model with right censored data.
rateratio.test	Exact rate ratio test.
rattle	A graphical user interface for data mining in R using GTK.
rbugs	Functions to prepare files needed for running BUGS in batch mode, and running BUGS from R. Support for Linux systems with Wine is emphasized.
rcdd	C Double Description for R, an interface to the CDD computational geometry library.
rcdk	Interface to the CDK libraries, a Java framework for cheminformatics.
rcom	R COM Client Interface and internal COM Server.
rcompgen	Completion generator for R. <i>Recommended</i> for R 2.5.0 or 2.6.0.
rda	Shrunken Centroids Regularized Discriminant Analysis.
realized	Realized variance toolkit.
ref	Functions for creating references, reading from and writing ro references and a memory efficient refdata type that transparently encapsulates matrices and data frames.
regress	Fitting Gaussian linear models where the covariance structure is a linear combination of known matrices by maximising the residual log likelihood. Can be used for multivariate models and random effects models.

regsubseq	Detect and test regular sequences and subsequences.
regtest	Regression testing.
relaimpo	RELAtive IMPOrtance of regressors in linear models.
relations	Data structures for k -ary relations with arbitrary domains, predicate functions, and fitters for consensus relations.
relax	Functions for report writing, presentation, and programming.
relaxo	Relaxed Lasso.
reldist	Functions for the comparison of distributions, including nonparametric estimation of the relative distribution PDF and CDF and numerical summaries as described in “Relative Distribution Methods in the Social Sciences” by Mark S. Handcock and Martina Morris, 1999, Springer.
relimp	Functions to facilitate inference on the relative importance of predictors in a linear or generalized linear model.
relsurv	Various functions for regression in relative survival.
reshape	Flexibly reshape data.
resper	Sampling from restricted permutations.
reweight	Adjustment of survey respondent weights.
rgcvtack	R interface for GCVPACK Fortran package.
rgdal	Provides bindings to Frank Warmerdam’s Geospatial Data Abstraction Library (GDAL).
rgenoud	R version of GENetic Optimization Using Derivatives.
rggm	Robustified methods for Gaussian Graphical Models.
rggobi	Interface between R and GGobi.
rgl	3D visualization device system (OpenGL).
rgr	The GSC (Geological Survey of Canada) applied geochemistry EDA package.
rhosp	Side effect risks in hospital: simulation and estimation.
rimage	Functions for image processing, including Sobel filter, rank filters, fft, histogram equalization, and reading JPEG files.
rindex	Indexing for R.
riv	Robust Instrumental Variables estimators based on high breakpoint point S-estimators of multivariate location and scatter matrices.
rjacobi	Jacobi polynomials and Gauss-Jacobi quadrature related operations.
rjson	JSON (JavaScript Object Notation) for R.
rlecuyer	R interface to RNG with multiple streams.
rmeta	Functions for simple fixed and random effects meta-analysis for two-sample comparison of binary outcomes.

rmetasim	An interface between R and the metasim simulation engine. Facilitates the use of the metasim engine to build and run individual based population genetics simulations.
robust	Insightful robust package.
robustbase	Basic Robust Statistics.
rpanel	Simple interactive controls for R using the tcltk package.
rpart	Recursive PARTitioning and regression trees. <i>Recommended.</i>
rpart.permutation	Permutation tests of rpart models.
rpubchem	R interface to the PubChem collection.
rpvm	R interface to PVM (Parallel Virtual Machine). Provides interface to PVM APIs, and examples and documentation for its use.
rqmcmb2	Markov chain marginal bootstrap for quantile regression.
rrcov	Functions for robust location and scatter estimation and robust regression with high breakdown point.
rrp	Random Recursive Partitioning.
rsbml	R support for SBML (Systems Biology Markup Language), using libsbml.
rsprng	Provides interface to SPRNG (Scalable Parallel Random Number Generators) APIs, and examples and documentation for its use.
rstream	Unified object oriented interface for multiple independent streams of random numbers from different sources.
rtiff	Read TIFF format images and return them as pixmap objects.
rv	Simulation-based random variable object class.
rwt	Rice Wavelet Toolbox wrapper, providing a set of functions for performing digital signal processing.
sac	Semiparametric empirical likelihood ratio based test of changepoint with one-change or epidemic alternatives with data-based model diagnostic.
sampling	A set of tools to select and to calibrate samples.
sampfling	Implements a modified version of the Sampford sampling algorithm. Given a quantity assigned to each unit in the population, samples are drawn with probability proportional to the product of the quantities of the units included in the sample.
samr	Significance Analysis of Microarrays.
sandwich	Model-robust standard error estimators for time series and longitudinal data.
sapa	Insightful Spectral Analysis for Physical Applications.
sbgcop	Semiparametric Bayesian Gaussian copula estimation.

sca	Simple Component Analysis.
scagnostics	Compute scagnostics.
scaleboot	Approximately unbiased p -values via multiscale bootstrap.
scape	functions to import and plot results from statistical catch-at-age models, used in fisheries stock assessments.
scapeMCMC	Markov-chain Monte Carlo diagnostic plots, accompanying the scape package.
scatterplot3d	Plots a three dimensional (3D) point cloud perspective.
schoolmath	Functions and datasets for math used in school.
sciplot	Scientific graphing functions for factorial designs.
scope	Data manipulation using arbitrary row and column criteria.
scuba	Scuba diving calculations and decompression models.
sdcMicro	Statistical Disclosure Control methods for the generation of public and scientific use files.
sde	Simulation and inference for Stochastic Differential Equations.
seacarb	Calculates parameters of the seawater carbonate system.
seas	Detailed seasonal plots of temperature and precipitation data.
seewave	Time wave analysis and graphical representation.
segmented	Functions to estimate break-points of segmented relationships in regression models (GLMs).
sem	Functions for fitting general linear Structural Equation Models (with observed and unobserved variables) by the method of maximum likelihood using the RAM approach.
sendplot	Tool for sending interactive plots.
sensitivity	Sensitivity analysis.
seqinr	Exploratory data analysis and data visualization for biological sequence (DNA and protein) data.
seqmon	Sequential monitoring of clinical trials.
seriation	Infrastructure for seriation.
session	Functions for interacting with, saving and restoring R sessions.
setRNG	Set (normal) random number generator and seed.
sets	Data structures and basic operations for ordinary sets, and generalizations such as fuzzy sets, multisets, and fuzzy multisets.

sfsmisc	Utilities from Seminar fuer Statistik ETH Zurich.
sgeostat	An object-oriented framework for geostatistical modeling.
shapefiles	Functions to read and write ESRI shapefiles.
shapes	Routines for the statistical analysis of shapes, including procrustes analysis, displaying shapes and principal components, testing for mean shape difference, thin-plate spline transformation grids and edge superimposition methods.
sigma2tools	Test of hypothesis about sigma2.
signal	A set of generally Matlab/Octave-compatible signal processing functions.
signalextraction	Real-time signal extraction (Direct Filter Approach).
simba	Functions for similarity calculation of binary data.
simco	Import Structure files and deduce similarity coefficients from them.
simecol	SIMulation of ECOLogical (and other) dynamic systems.
simex	SIMEX and MCSIMEX algorithms for measurement error models.
simpleboot	Simple bootstrap routines.
skewt	Density, distribution function, quantile function and random generation for the skewed t distribution of Fernandez and Steel.
sm	Software linked to the book “Applied Smoothing Techniques for Data Analysis: The Kernel Approach with S-PLUS Illustrations” by A. W. Bowman and A. Azzalini, 1997, Oxford University Press.
sma	Functions for exploratory (statistical) microarray analysis.
smatr	(Standardized) Major Axis estimation and Testing Routines.
smoothSurv	Survival regression with smoothed error distribution.
smoothtail	Smooth estimation of generalized Pareto distribution shape parameter.
sn	Functions for manipulating skew-normal probability distributions and for fitting them to data, in the scalar and the multivariate case.
sna	A range of tools for social network analysis, including node and graph-level indices, structural distance and covariance methods, structural equivalence detection, p^* modeling, and network visualization.
snow	Simple Network of Workstations: support for simple parallel computing in R.
snowFT	Fault Tolerant Simple Network of Workstations.
snp.plotter	Plots of p -values using single SNP and/or haplotype data.
snpXpert	Tools to analyze SNP data.

som	Self-Organizing Maps (with application in gene clustering).
sound	A sound interface for R: Basic functions for dealing with ‘.wav’ files and sound samples.
sp	A package that provides classes and methods for spatial data, including utility functions for plotting data as maps, spatial selection, and much more.
spBayes	Fit Gaussian models with potentially complex hierarchical error structures by Markov chain Monte Carlo (MCMC).
spam	SPArse Matrix algebra.
spatclus	Arbitrarily shaped multiple spatial cluster detection for case event data.
spatgraphs	Graphs for 2-d point patterns.
spatial	Functions for kriging and point pattern analysis from “Modern Applied Statistics with S” by W. Venables and B. Ripley. Contained in the ‘VR’ bundle. <i>Recommended.</i>
spatialCovariance	Computation of spatial covariance matrices for data on rectangles using one dimensional numerical integration and analytic results.
spatialkernel	Nonparameteric estimation of spatial segregation in a multivariate point process.
spatstat	Data analysis and modelling of two-dimensional point patterns, including multitype points and spatial covariates.
spc	Statistical Process Control: evaluation of control charts by means of the zero-state, steady-state ARL (Average Run Length), setting up control charts for given in-control ARL, and plotting of the related figures.
spdep	A collection of functions to create spatial weights matrix objects from polygon contiguities, from point patterns by distance and tessellations, for summarising these objects, and for permitting their use in spatial data analysis; a collection of tests for spatial autocorrelation, including global Moran’s I and Geary’s C, local Moran’s I, saddlepoint approximations for global and local Moran’s I; and functions for estimating spatial simultaneous autoregressive (SAR) models. (Was formerly the three packages: spweights , sptests , and spsarlm .)
spe	Stochastic Proximity Embedding.
spectralGP	Approximate Gaussian processes using the Fourier basis.
spectrino	Spectra organizer, visualization and data extraction from within R.
spgrass6	Interface between the GRASS 6.0 geographical information system and R.
spgwr	Geographically weighted regression.
splanCS	Spatial and space-time point pattern analysis functions.

splus2R	Insightful package providing missing S-PLUS functionality in R.
spsurvey	Spatial survey design and analysis.
sqldf	Perform SQL selects on R data frames.
ssanv	Sample Size Adjusted for Nonadherence or Variability of input parameters.
sspir	State SPace models In R.
sspline	Smoothing splines on the sphere.
st	Shrinkage t statistic.
staRt	Inferenza classica con TI-83 Plus.
startupmsg	Utilities for start-up messages.
stashR	A Set of Tools for Administering SHared Repositories.
statmod	Miscellaneous biostatistical modelling functions.
stepPlr	L2 penalized logistic regression with a stepwise variable selection.
stepwise	A stepwise approach to identifying recombination breakpoints in a sequence alignment.
stinepack	Stineman interpolation package.
stochasticGEM	Fitting Stochastic General Epidemic Models.
stochmod	Learning and inference algorithms for a variety of probabilistic models.
stream.net	Building and analyzing binary stream networks.
strucchange	Various tests on structural change in linear regression models.
subselect	A collection of functions which assess the quality of variable subsets as surrogates for a full data set, and search for subsets which are optimal under various criteria.
sudoku	Sudoku puzzle solver.
supclust	Methodology for supervised grouping of predictor variables.
superpc	Supervised principal components.
surv2sample	Two-sample tests for survival analysis.
survBayes	Fits a proportional hazards model to time to event data by a Bayesian approach.
surveillance	Outbreak detection algorithms for surveillance data.
survey	Summary statistics, generalized linear models, and general maximum likelihood estimation for stratified, cluster-sampled, unequally weighted survey samples.

surveyNG	Complex survey samples: database interface, sparse matrices.
survival	Functions for survival analysis, including penalised likelihood. <i>Recommended.</i>
survrec	Survival analysis for recurrent event data.
svcR	A support vector machine technique for clustering.
svcm	2d and 3d Space-Varying Coefficient Models.
svmpath	Computes the entire regularization path for the two-class svm classifier with essentially the same cost as a single SVM fit.
systemfit	Contains functions for fitting simultaneous systems of equations using Ordinary Least Squares (OLS), Two-Stage Least Squares (2SLS), and Three-Stage Least Squares (3SLS).
taskPR	Task-Parallel R package.
tcltk2	A series of widgets and functions to supplement tcltk .
tdist	Computes the distribution of a linear combination of independent Student's t variables.
tdm	A tool for Therapeutic Drug Monitoring.
tdthap	Transmission/disequilibrium tests for extended marker haplotypes.
tensor	Tensor product of arrays.
tensorA	Advanced tensors arithmetic with named indices.
termstrc	Term structure and credit spread estimation.
tframe	Time Frame coding kernel: functions for writing code that is independent of the way time is represented.
tgp	Bayesian regression and adaptive sampling with Treed Gaussian Process models.
time	Time tracking for developers.
timsac	TIME Series Analysis and Control package.
titan	Titration analysis for mass spectrometry data.
titecrm	TIme-To-Event Continual Reassessment Method and calibration tools.
tkrgl	TK widget tools for rgl package.
tkrplot	Simple mechanism for placing R graphics in a Tk widget.
tlmise	Two-level normal independent sampling estimation.
tm	A framework for text mining applications within R.
trackObjs	Track objects.
tradeCosts	Post-trade analysis of transaction costs.
tree	Classification and regression trees.

treegia	Stem analysis functions for volume increment and carbon uptake assessment from tree-rings.
triangle	Standard distribution functions for the triangle distribution.
trimcluster	Cluster analysis with trimming.
trip	Spatial analysis of animal track data.
tripEstimation	Metropolis sampler and supporting functions for estimating animal movement from archival tags and satellite fixes.
tripack	A constrained two-dimensional Delaunay triangulation package.
truncgof	Goodness-of-fit tests allowing for left truncated data.
trust	Local optimization using two derivatives and trust regions.
tsDyn	Time series analysis based on dynamical systems theory.
tseries	Package for time series analysis with emphasis on non-linear modelling.
tseriesChaos	Routines for the analysis of non-linear time series.
tsfa	Time Series Factor Analysis.
tuneR	Collection of tools to analyze music, handle wave files, transcription, etc.
tutoR	Student-friendly package to mask common functions.
twang	Toolkit for Weighting and Analysis of Nonequivalent Groups.
tweedie	Maximum likelihood computations for Tweedie exponential family models.
twslm	A two-way semilinear model for normalization and analysis of cDNA microarray data.
udunits	Interface to Unidata's routines to convert units.
ump	Uniformly Most Powerful tests.
unbalhaar	Function estimation via Unbalanced Haar wavelets.
untb	Ecological drift under the UNTB (Unified Neutral Theory of Biodiversity).
urca	Unit root and cointegration tests for time series data.
urn	Functions for sampling without replacement (simulated urns).
uroot	Unit root tests and graphics for seasonal time series.
vabayelMix	Variational Bayesian mixture model.
varSelRF	Variable selection using random forests.
vardiag	Interactive variogram diagnostics.
varmixt	Mixture model on the variance for the analysis of gene expression data.

vars	VAR modeling.
vbmp	Variational Bayesian Multinomial Probit Regression.
vcd	Functions and data sets based on the book “Visualizing Categorical Data” by Michael Friendly.
vegan	Various help functions for vegetation scientists and community ecologists.
verification	Utilities for verification of discrete and probabilistic forecasts.
verify	Construction of test suites using verify objects.
vioplot	Violin plots, which are a combination of a box plot and a kernel density plot.
vrtest	Variance ratio tests for weak-form market efficiency.
waved	WaveD transform in R.
wavelets	Functions for computing wavelet filters, wavelet transforms and multiresolution analyses.
waveslim	Basic wavelet routines for time series analysis.
wavethresh	Software to perform 1-d and 2-d wavelet statistics and transforms.
wccsom	SOM networks for comparing patterns with peak shifts.
wikibooks	Functions and datasets for the German WikiBook “GNU R”.
wle	Robust statistical inference via a weighted likelihood approach.
wmtsa	Insightful Wavelet Methods for Time Series Analysis.
wnominate	WNOMINATE roll call analysis software.
wombsoft	Wombling computation.
wordnet	WordNet interface.
write.snns	Function for exporting data to SNNS (Stuttgart Neural Network Simulator) pattern files.
xgobi	Interface to the XGobi and XGvis programs for graphical data analysis.
xlsReadWrite	Natively read and write Excel files.
xtable	Export data to L ^A T _E X and HTML tables.
yaImpute	Performs popular nearest neighbor routines.
yest	Gaussian independence models.
zicounts	Fit classical, zero-inflated and interval censored count data regression models.
zipfR	Statistical models for word frequency distributions.
zoeppritz	Zoeppritz equations: calculate and plot scattering coefficients of seismic waves when they interact at an interface between two layers.

zoo A class with methods for totally ordered indexed observations such as irregular time series.

See CRAN ‘`src/contrib/PACKAGES`’ for more information.

There used to be a CRAN ‘`src/contrib/Devel`’ directory with packages still “under development” or depending on features only present in the current development versions of R. This area is no longer provided, with packages formerly in this area either in the regular package area or the archive ‘`src/contrib/Archive`’.

5.1.3 Add-on packages from Omegahat

The **Omegahat Project for Statistical Computing** provides a variety of open-source software for statistical applications, with special emphasis on web-based software, Java, the Java virtual machine, and distributed computing. A CRAN style R package repository is available via <http://www.omegahat.org/R/>.

Currently, there are the following packages.

Aspell An interface to facilities in the aspell library.

CGIwithR Facilities for the use of R to write CGI scripts.

CORBA Dynamic CORBA client/server facilities for R. Connects to other CORBA-aware applications developed in arbitrary languages, on different machines and allows R functionality to be exported in the same way to other applications.

Combinations

Compute the combinations of choosing r items from n elements.

IDocs Infrastructure for interactive documents.

OOP OOP style classes and methods for R and S-PLUS. Object references and class-based method definition are supported in the style of languages such as Java and C++.

RCurl Allows one to compose HTTP requests to fetch URIs, post forms, etc., and process the results returned by the Web server.

RDCOMClient

Provides dynamic client-side access to (D)COM applications from within R.

RDCOMEvents

Provides facilities to use R functions and objects as handlers for DCOM events.

RDCOMServer

Facilities for exporting S objects and functions as COM objects.

REmbeddedPostgres

Allows R functions and objects to be used to implement SQL functions — per-record, aggregate and trigger functions.

REventLoop

An abstract event loop mechanism that is toolkit independent and can be used to to replace the R event loop.

Rexif Extract meta-information from JPEG files.

RGdkPixbuf

S language functions to access the facilities in the GdkPixbuf library for manipulating images.

RGnumeric

A plugin for the Gnumeric spreadsheet that allows R functions to be called from cells within the sheet, automatic recalculation, etc.

RGtk

Facilities in the S language for programming graphical interfaces using Gtk, the Gnome GUI toolkit.

RGtkBindingGenerator

A meta-package which generates C and R code to provide bindings to a Gtk-based library.

RGtkExtra

A collection of S functions that provide an interface to the widgets in the gtk+extra library such as the GtkSheet data-grid display, icon list, file list and directory tree.

RGtkGlade

S language bindings providing an interface to Glade, the interactive Gnome GUI creator.

RGtkHTML

A collection of S functions that provide an interface to creating and controlling an HTML widget which can be used to display HTML documents from files or content generated dynamically in S.

RGtkIPrimitives

A collection of low-level primitives for interactive use with R graphics and the gtkDevice using **RGtk**.

RGtkViewers

A collection of tools for viewing different S objects, databases, class and widget hierarchies, S source file contents, etc.

RJavaDevice

A graphics device for R that uses Java components and graphics. APIs.

RMatlab

A bi-directional interface between R and Matlab.

RObjectTables

The C and S code allows one to define R objects to be used as elements of the search path with their own semantics and facilities for reading and writing variables. The objects implement a simple interface via R functions (either methods or closures) and can access external data, e.g., in other applications, languages, formats, . . .

RSMETHODS

An implementation of S version 4 methods and classes for R, consistent with the basic material in “Programming with Data” by John M. Chambers, 1998, Springer NY.

RSPerl	An interface from R to an embedded, persistent Perl interpreter, allowing one to call arbitrary Perl subroutines, classes and methods.
RSPython	Allows Python programs to invoke S functions, methods, etc., and S code to call Python functionality.
RXLisp	An interface to call XLisp-Stat functions from within R.
Rcompression	In-memory decompression for GNU zip and bzip2 formats.
Rlibstree	Suffix Trees in R via the libstree C library.
Rstem	Interface to Snowball implementation of Porter's word stemming algorithm.
RwxWidgets	Facilities to program GUIs using wxWidgets in R.
Ryacac	R interface to yacas.
SASXML	Example for reading XML files in SAS 8.2 manner.
SJava	An interface from R to Java to create and call Java objects and methods.
SLanguage	Functions and C support utilities to support S language programming that can work in both R and S-PLUS.
SNetscape	Plugin for Netscape and JavaScript.
SSOAP	A client interface to SOAP (Simple Object Access Protocol) servers from within S.
SWinRegistry	Provides access from within R to read and write the Windows registry.
SWinTypeLibs	Provides ways to extract type information from type libraries and/or DCOM objects that describes the methods, properties, etc., of an interface.
SXalan	Process XML documents using XSL functions implemented in R and dynamically substituting output from R.
Slcc	Parses C source code, allowing one to analyze and automatically generate interfaces from S to that code, including the table of S-accessible native symbols, parameter count and type information, S constructors from C objects, call graphs, etc.
Sxslt	An extension module for libxslt, the XML-XSL document translator, that allows XSL functions to be implemented via R functions.
XML	Tools for reading XML documents and DTDs.

5.1.4 Add-on packages from Bioconductor

The **Bioconductor Project** produces an open source software framework that will assist biologists and statisticians working in bioinformatics, with primary emphasis on inference using DNA microarrays. A CRAN style R package repository is available via <http://www.bioconductor.org/>.

The following R packages are contained in the current release of Bioconductor, with more packages under development.

ABarray Microarray QA and statistical data analysis for Applied Biosystems Genome Survey Micorarray (AB1700) gene expression data.

ACME Algorithms for Calculating Microarray Enrichment (ACME).

AffyExpress
Affymetrix quality assessment and analysis tool.

AnnBuilder
Processing annotation data from public data repositories and building annoat-ion data packages or XML data documents using the source data.

AnnotationDbi
Annotation DataBase Interface.

BSgenome Infrastructure for Biostrings-based genome data packages.

BeadExplorer
QC, normalization, annotation and exploration of Illumina BeadChip data.

BioMVCClass
Model-View-Controller (MVC) classes that use **Biobase**.

Biobase Object-oriented representation and manipulation of genomic data (S4 class structure).

Biostrings Class definitions and generics for biological sequences along with pattern match-ing algorithms.

BufferedMatrix
Microarray analysis methods that use BufferedMatrix objects.

BufferedMatrixMethods
A matrix data storage object held in temporary files.

CALIB Calibration model for estimating absolute expression levels from microarray data.

CGHcall Calling aberrations for array CGH tumor profiles.

CORREP Multivariate correlation estimation and statistical inference.

Category A collection of tools for performing category analysis.

ChromoViz
Draw gene expression profile onto chromosome using SVG.

CoCiteStat
A collection of software tools for dealing with co-citation data.

DEDS	Differential Expression via Distance Summary for microarray data.
DNAcopy	Segments DNA copy number data using circular binary segmentation to detect regions with abnormal copy number.
DynDoc	Functionality to create and interact with dynamic documents, vignettes, and other navigable documents.
EBImage	Image processing and image analysis toolkit.
EBarrays	Empirical Bayes tools for the analysis of replicated microarray data across multiple conditions.
GEOquery	Get data from NCBI Gene Expression Omnibus (GEO).
GGtools	Software and data for genetical genomics.
GLAD	Gain and Loss Analysis of DNA.
GOstats	Tools for manipulating GO and microarrays.
GSEABase	Gene set enrichment data structures and methods.
GeneMeta	A collection of meta-analysis tools for analyzing high throughput experimental data.
GeneR	Package manipulating nucleotidic sequences (Embl, Fasta, GenBank).
GeneSpring	Functions and class definitions to be able to read and write GeneSpring specific data objects and convert them to Bioconductor objects.
GeneTS	A package for analysing multiple gene expression time series data. Currently, implements methods for cell cycle analysis and for inferring large sparse graphical Gaussian models.
GeneTraffic	GeneTraffic R integration functions.
GeneticsBase	Classes and functions for handling genetic data.
GeneticsDesign	Functions for designing genetics studies.
GlobalAncova	Calculates a global test for differential gene expression between groups.
GraphAT	Graph theoretic Association Tests.
HEM	Heterogeneous Error Model for analysis of microarray data.
Harshlight	A “corrective make-up” program for microarray chips.
Heatplus	A heat map displaying covariates and coloring clusters.

Icens	Functions for computing the NPMLE for censored and truncated data.
KEGGSOAP	Client-side SOAP access KEGG.
LBE	Estimation of the false discovery rate.
LMGene	Analysis of microarray data using a linear model and glog data transformation.
LPE	Significance analysis of microarray data with small number of replicates using the Local Pooled Error (LPE) method.
MANOR	Micro-Array NORmalization.
MCReestimate	Misclassification error estimation with cross-validation.
MLInterfaces	Uniform interfaces to machine learning code for the <code>exprSet</code> class from Bioconductor.
MVCClass	Model-View-Controller (MVC) classes.
MantelCorr	Compute Mantel Cluster Correlations.
MassSpecWavelet	Mass spectrum processing by wavelet-based algorithms.
MeasurementError.cor	Two-stage measurement error model for correlation estimation with smaller bias than the usual sample correlation.
MergeMaid	Cross-study comparison of gene expression array data.
Mfuzz	Soft clustering of time series gene expression data.
MiPP	Misclassification Penalized Posterior Classification.
OCplus	Operating characteristics plus sample size and local fdr for microarray experiments.
OLIN	Optimized Local Intensity-dependent Normalisation of two-color microarrays.
OLINgui	Graphical user interface for OLIN .
OrderedList	Similarities of ordered gene lists.
OutlierD	Outlier detection using quantile regression on the M-A scatterplots of high-throughput data.
PGSEA	Parametric Gene Set Enrichment Analysis.
PROcess	Ciphergen SELDI-TOF processing.
RBGL	An interface between the graph package and the Boost graph libraries, allowing for fast manipulation of graph objects in R.

RLMM	A genotype calling algorithm for Affymetrix SNP arrays.
RMAGEML	Functionality to handle MAGEML documents.
RMAPPER	Interface to mapper.chip.org.
ROC	Receiver Operating Characteristic (ROC) approach for identifying genes that are differentially expressed in two types of samples.
RSNPper	Interface to chip.org::SNPper for SNP-related data.
RWebServices	Expose R functions as web services through Java/Axis/Apache.
RankProd	Rank Product method for identifying differentially expressed genes.
RbcBook1	Support for Springer monograph on Bioconductor.
Rdbi	Generic framework for database access in R.
RdbiPgSQL	Methods for accessing data stored in PostgreSQL tables.
RefPlus	Functions for pre-processing Affymetrix data using the RMA+ and the RMA++ methods.
Resourcerer	Read annotation data from TIGR Resourcerer or convert the annotation data into Bioconductor data package.
Rgraphviz	An interface with Graphviz for plotting graph objects in R.
Ringo	R Investigation of NimbleGen Oligoarrays..
Rintact	Interface to EBI Intact protein interaction data base.
Ruuid	Creates Universally Unique ID values (UUIDs) in R.
SAGElyzer	Locates genes based on SAGE tags.
SAGx	Statistical Analysis of the GeneChip.
SBMLR	Systems Biology Markup Language (SBML) interface and biochemical system analysis tools.
SLqPCR	Functions for analysis of real-time quantitative PCR data at SIRS-Lab GmbH.
SMAP	A Segmental Maximum A Posteriori approach to array-CGH copy number profiling.
SNPchip	Classes and methods for high throughput SNP chip data.
ScISI	In Silico Interactome.
SemSim	Gene ontology-based semantic similarity measures.
TypeInfo	Optional type specification prototype.

VanillaICE

Methods for fitting Hidden Markov Models to SNP chip data.

aCGH Classes and functions for Array Comparative Genomic Hybridization data.

adSplit Annotation-driven clustering.

affxparser Package for parsing Affymetrix files (CDF, CEL, CHP, BPMap, BAR).

affy Methods for Affymetrix Oligonucleotide Arrays.

affyPLM For fitting Probe Level Models.

affyQCReport

QC Report Generation for `affyBatch` objects.

affycomp Graphics toolbox for assessment of Affymetrix expression measures.

affycoretools

Functions useful for those doing repetitive analyses.

affyio Tools for parsing Affymetrix data files.

affymGUI

Graphical User Interface for `affy` analysis using package **limma**.

affypdnn Probe Dependent Nearest Neighbors (PDNN) for the **affy** package.

altcdfenvs Utilities to handle `cdfenvs`.

annaffy Functions for handling data from Bioconductor Affymetrix annotation data packages.

annotate Associate experimental data in real time to biological metadata from web databases such as GenBank, LocusLink and PubMed. Process and store query results. Generate HTML reports of analyses.

annotationTools

Annotate microarrays and perform cross-species gene expression analyses using flat file databases.

apComplex

Estimate protein complex membership using AP-MS protein data.

aroma.light

Light-weight methods for normalization and visualization of microarray data using only basic R data types.

arrayMagic

Utilities for quality control and processing for two-color cDNA microarray data.

arrayQuality

Performing print-run and array level quality assessment.

arrayQualityMetrics

Quality metrics on `ExpressionSets`.

beadarray Quality control and low-level analysis of `BeadArrays`.

beadarraySNP	Normalization and reporting of Illumina SNP bead arrays.
bgafun	A method to identify specificity determining residues in protein families.
bgx	Bayesian Gene eXpression.
bioDist	A collection of software tools for calculating distance measures.
biocGraph	Graph examples and use cases in Bioinformatics.
biocViews	Categorized views of R package repositories.
biomaRt	Interface to BioMart databases (e.g., Ensembl)
bridge	Bayesian Robust Inference for Differential Gene Expression.
cellHTS	Analysis of cell-based screens.
cellHTS2	Analysis of cell-based screens — revised version of cellHTS .
cghMCR	Find chromosome regions showing common gains/losses.
clusterStab	Compute cluster stability scores for microarray data.
codelink	Manipulation of Codelink Bioarrays data.
convert	Convert Microarray Data Objects.
copa	Functions to perform cancer outlier profile analysis.
cosmo	Supervised detection of conserved motifs in DNA sequences.
cosmoGUI	GUI for constructing constraint sets used by the cosmo package.
ctc	Tools to export and import Tree and Cluster to other programs.
daMA	Functions for the efficient design of factorial two-color microarray experiments and for the statistical analysis of factorial microarray data.
diffGeneAnalysis	Performs differential Gene expression Analysis.
ecolink	Metadata and tools to work with E. coli.
edd	Expression density diagnostics: graphical methods and pattern recognition algorithms for distribution shape classification.
exonmap	High level analysis of Affymetrix exon array data.
explorase	GUI for exploratory data analysis of systems biology data.
factDesign	A set of tools for analyzing data from factorial designed microarray experiments. The functions can be used to evaluate appropriate tests of contrast and perform single outlier detection.
fbat	Family Based Association Tests for genetic data.
fdrame	FDR Adjustments of Microarray Experiments (FDR-AME).

flowCore	Basic structures for flow cytometry data.
flowUtils	Database interface for flow cytometry.
flowViz	Visualization for flow cytometry.
gaggle	Broadcast data between R and Java bioinformatics programs.
gcrma	Background adjustment using sequence information.
genArise	A tool for dual color microarray data.
geneRecommender	A gene recommender algorithm to identify genes coexpressed with a query set of genes.
genefilter	Tools for sequentially filtering genes using a wide variety of filtering functions. Example of filters include: number of missing value, coefficient of variation of expression measures, ANOVA <i>p</i> -value, Cox model <i>p</i> -values. Sequential application of filtering functions to genes.
geneplotter	Graphical tools for genomic data, for example for plotting expression data along a chromosome or producing color images of expression data matrices.
globaltest	Testing globally whether a group of genes is significantly related to some clinical variable of interest.
goTools	Functions for description/comparison of oligo ID list using the Gene Ontology database.
gpls	Classification using generalized partial least squares for two-group and multi-group classification.
graph	Classes and tools for creating and manipulating graphs within R.
hexbin	Binning functions, in particular hexagonal bins for graphing.
hopach	Hierarchical Ordered Partitioning and Collapsing Hybrid (HOPACH).
hypergraph	Capabilities for representing and manipulating hypergraphs.
iSNetwork	Interactive network plots.
iSPlot	Link views that are based on the same data set.
idiogram	Plotting genomic data by chromosomal location.
impute	Imputation for microarray data (currently KNN only).
keggorth	Graph support for KO, KEGG Orthology.
lapmix	Laplace mixture model in microarray experiments.
limma	Linear models for microarray data.
limmaGUI	Graphical User Interface for package limma .

logicFS	Identification of SNP interactions.
lumi	BeadArray specific methods for Illumina microarrays.
maCorrPlot	Visualize artificial correlation in microarray data.
maDB	Microarray database and utility functions for microarray analysis.
maSigPro	Significant gene expression profile differences in time course microarray data.
maanova	Tools for analyzing micro array experiments.
macat	MicroArray Chromosome Analysis Tool.
made4	Multivariate analysis of microarray data using ADE4.
maigesPack	Functions to handle cDNA microarray data, including several methods of data analysis.
makePlatformDesign	Creates the Platform Design environments (PDenvs) required by oligo .
makecdfenv	Two functions. One reads a Affymetrix chip description file (CDF) and creates a hash table environment containing the location/probe set membership mapping. The other creates a package that automatically loads that environment.
marray	Exploratory analysis for two-color spotted microarray data.
matchprobes	Tools for sequence matching of probes on arrays.
metaArray	Integration of microarray data for meta-analysis.
multtest	Multiple testing procedures for controlling the family-wise error rate (FWER) and the false discovery rate (FDR). Tests can be based on t - or F -statistics for one- and two-factor designs, and permutation procedures are available to estimate adjusted p -values.
nem	Nested Effects Models to reconstruct phenotypic hierarchies.
nnNorm	Spatial and intensity based normalization of cDNA microarray data based on robust neural nets.
oligo	Oligonucleotide arrays.
oligoClasses	Classes for high-throughput SNP arrays.
oneChannelGUI	Extend the capabilities of affymGUI .
ontoTools	Graphs and sparse matrices for working with ontologies; formal objects for nomenclatures with provenance management.
pamr	Pam: Prediction Analysis for Microarrays.

panp	Presence-Absence calls from Negative strand matching Probesets.
pathRender	Render molecular pathways.
pcaMethods	A collection of PCA methods.
pcot2	Principal coordinates and Hotelling's T-square method.
pdInfoBuilder	Platform design information package builder.
pdmclass	CLASSification of microarray samples using Penalized Discriminant Methods.
pgUtils	Utility functions for PostgreSQL databases.
pickgene	Adaptive gene picking for microarray expression data analysis.
pkgDepTools	Package dependency tools.
plgem	Power Law Global Error Model.
plier	Implements the Affymetrix PLIER (Probe Logarithmic Error Intensity Estimate) algorithm.
ppiStats	Protein-Protein Interaction Statistical package.
prada	Tools for analyzing and navigating data from high-throughput phenotyping experiments based on cellular assays and fluorescent detection.
preprocessCore	A collection of pre-processing functions.
puma	Propagating Uncertainty in Microarray Analysis.
quantsmooth	Quantile smoothing and genomic visualization of array data.
qvalue	Q-value estimation for false discovery rate control.
rHVDM	Hidden Variable Dynamic Modeling.
rama	Robust Analysis of MicroArrays: robust estimation of cDNA microarray intensities with replicates using a Bayesian hierarchical model.
rbsurv	Robust likelihood-based survival modeling with microarray data.
reb	Regional Expression Biases.
rflowcyt	Statistical tools and data structures for analytic flow cytometry.
rsbml	R support for SBML, using libsbml.
safe	Significance Analysis of Function and Expression.
sagenhaft	Functions for reading and comparing SAGE (Serial Analysis of Gene Expression) libraries.
seqLogo	Sequence logos for DNA sequence alignments.

sigPathway	Pathway analysis.
siggenes	Identifying differentially expressed genes and estimating the False Discovery Rate (FDR) with both the Significance Analysis of Microarrays (SAM) and the Empirical Bayes Analyses of Microarrays (EBAM).
simpleaffy	Very simple high level analysis of Affymetrix data.
simulatorAPMS	Computationally simulates the AP-MS technology.
sizepower	Sample size and power calculation in microrarray studies.
snapCGH	Segmentation, normalization and processing of aCGH data.
spikeLI	Affymetrix Spike-in Langmuir Isotherm data analysis tool.
splicegear	A set of tools to work with alternative splicing.
splots	Visualization routines for high throughput screens.
spotSegmentation	Microarray spot segmentation and gridding for blocks of microarray spots.
sscore	S-score algorithm for Affymetrix oligonucleotide microarrays.
ssize	Estimate microarray sample size.
stam	STructured Analysis of Microarray data.
stepNorm	Stepwise normalization functions for cDNA microarrays.
tilingArray	Analysis of tiling arrays.
timecourse	Statistical analysis for developmental microarray time course data.
tkWidgets	Widgets in Tcl/Tk that provide functionality for Bioconductor packages.
topGO	Enrichment analysis for Gene Ontology.
twilight	Estimation of local false discovery rate.
vbmp	Variational Bayesian Multinomial Probit regression.
vsn	Calibration and variance stabilizing transformations for both Affymetrix and cDNA array data.
weaver	Tools and extensions for processing Sweave documents.
webbioc	Integrated web interface for doing microarray analysis using several of the Bioconductor packages.
widgetInvoke	Evaluation widgets for functions.
widgetTools	Tools for creating Tcl/Tk widgets, i.e., small-scale graphical user interfaces.
xcms	LC/MS and GC/MS data analysis: framework for processing and visualization of chromatographically separated mass spectral data.

5.1.5 Other add-on packages

Jim Lindsey has written a collection of R packages for nonlinear regression and repeated measurements, consisting of **event** (event history procedures and models), **gnlm** (generalized nonlinear regression models), **growth** (multivariate normal and elliptically-contoured repeated measurements models), **repeated** (non-normal repeated measurements models), **rmutil** (utilities for nonlinear regression and repeated measurements), and **stable** (probability functions and generalized regression models for stable distributions). All analyses in the new edition of his book “Models for Repeated Measurements” (1999, Oxford University Press) were carried out using these packages. Jim has also started **dna**, a package with procedures for the analysis of DNA sequences. Jim’s packages can be obtained from <http://popgen.unimaas.nl/~jlindsey/rcode.html>.

More code has been posted to the R-help mailing list, and can be obtained from the mailing list archive.

5.2 How can add-on packages be installed?

(Unix only.) The add-on packages on CRAN come as gzipped tar files named *pkg_version.tar.gz*, which may in fact be “bundles” containing more than one package. Provided that **tar** and **gzip** are available on your system, type

```
$ R CMD INSTALL /path/to/pkg_version.tar.gz
```

at the shell prompt to install to the library tree rooted at the first directory given in **R_LIBS** (see below) if this is set and non-null, and to the default library (the ‘**library**’ subdirectory of ‘**R_HOME**’) otherwise. (Versions of R prior to 1.3.0 installed to the default library by default.)

To install to another tree (e.g., your private one), use

```
$ R CMD INSTALL -l lib /path/to/pkg_version.tar.gz
```

where *lib* gives the path to the library tree to install to.

Even more conveniently, you can install and automatically update packages from within R if you have access to repositories such as CRAN. See the help page for **available.packages()** for more information.

You can use several library trees of add-on packages. The easiest way to tell R to use these is via the environment variable **R_LIBS** which should be a colon-separated list of directories at which R library trees are rooted. You do not have to specify the default tree in **R_LIBS**. E.g., to use a private tree in ‘**\$HOME/lib/R**’ and a public site-wide tree in ‘**/usr/local/lib/R-contrib**’, put

```
R_LIBS="$HOME/lib/R:/usr/local/lib/R-contrib"; export R_LIBS
```

into your (Bourne) shell profile or even preferably, add the line

```
R_LIBS=~ /lib/R:/usr/local/lib/R-contrib"
```

your ‘**~/.Renviron**’ file. (Note that no **export** statement is needed or allowed in this file; see the on-line help for **Startup** for more information.)

5.3 How can add-on packages be used?

To find out which additional packages are available on your system, type

`library()`
at the R prompt.

This produces something like

```
Packages in '/home/me/lib/R':

mystuff      My own R functions, nicely packaged but not documented

Packages in '/usr/local/lib/R/library':

KernSmooth   Functions for kernel smoothing for Wand & Jones (1995)
MASS          Main Package of Venables and Ripley's MASS
base         The R Base package
boot         Bootstrap R (S-Plus) Functions (Canty)
class        Functions for Classification
cluster      Functions for clustering (by Rousseeuw et al.)
datasets     The R datasets Package
foreign      Read data stored by Minitab, S, SAS, SPSS, Stata, ...
grDevices    The R Graphics Devices and Support for Colours and Fonts
graphics     The R Graphics Package
grid         The Grid Graphics Package
lattice      Lattice Graphics
methods      Formal Methods and Classes
mgcv         GAMs with GCV smoothness estimation and GAMMs by REML/PQ
nlme         Linear and nonlinear mixed effects models
nnet         Feed-forward Neural Networks and Multinomial Log-Linear
            Models
rpart        Recursive partitioning
spatial      Functions for Kriging and Point Pattern Analysis
splines      Regression Spline Functions and Classes
stats        The R Stats Package
stats4       Statistical functions using S4 classes
survival     Survival analysis, including penalised likelihood
tcltk        Tcl/Tk Interface
tools        Tools for Package Development
utils        The R Utils Package
```

You can “load” the installed package *pkg* by

```
library(pkg)
```

You can then find out which functions it provides by typing one of

```
library(help = pkg)
help(package = pkg)
```

You can unload the loaded package *pkg* by

```
detach("package:pkg")
```

5.4 How can add-on packages be removed?

Use

```
$ R CMD REMOVE pkg_1 ... pkg_n
```

to remove the packages *pkg_1*, ..., *pkg_n* from the library tree rooted at the first directory given in `R_LIBS` if this is set and non-null, and from the default library otherwise. (Versions of R prior to 1.3.0 removed from the default library by default.)

To remove from library *lib*, do

```
$ R CMD REMOVE -l lib pkg_1 ... pkg_n
```

5.5 How can I create an R package?

A package consists of a subdirectory containing the files ‘DESCRIPTION’ and ‘INDEX’, and the subdirectories ‘R’, ‘data’, ‘demo’, ‘exec’, ‘inst’, ‘man’, ‘src’, and ‘tests’ (some of which can be missing). Optionally the package can also contain script files ‘configure’ and ‘cleanup’ which are executed before and after installation.

See [section “Creating R packages” in *Writing R Extensions*](#), for details.

R version 1.3.0 has added the function `package.skeleton()` which will set up directories, save data and code, and create skeleton help files for a set of R functions and datasets.

See [Section 2.10 \[What is CRAN?\]](#), [page 10](#), for information on uploading a package to CRAN.

5.6 How can I contribute to R?

R is in active development and there is always a risk of bugs creeping in. Also, the developers do not have access to all possible machines capable of running R. So, simply using it and communicating problems is certainly of great value.

One place where functionality is still missing is the modeling software as described in “Statistical Models in S” (see [Section 3.1 \[What is S?\]](#), [page 12](#)); some of the nonlinear modeling code is not there yet.

The [R Developer Page](#) acts as an intermediate repository for more or less finalized ideas and plans for the R statistical system. It contains (pointers to) TODO lists, RFCs, various other writeups, ideas lists, and CVS miscellanea.

Many (more) of the packages available at the Statlib S Repository might be worth porting to R.

If you are interested in working on any of these projects, please notify [Kurt Hornik](#).

6 R and Emacs

6.1 Is there Emacs support for R?

There is an Emacs package called ESS (“Emacs Speaks Statistics”) which provides a standard interface between statistical programs and statistical processes. It is intended to provide assistance for interactive statistical programming and data analysis. Languages supported include: S dialects (R, S 3/4, and S-PLUS 3.x/4.x/5.x/6.x/7.x), LispStat dialects (XLispStat, ViSta), SAS, Stata, and BUGS.

ESS grew out of the need for bug fixes and extensions to S-mode 4.8 (which was a GNU Emacs interface to S/S-PLUS version 3 only). The current set of developers desired support for XEmacs, R, S4, and MS Windows. In addition, with new modes being developed for R, Stata, and SAS, it was felt that a unifying interface and framework for the user interface would benefit both the user and the developer, by helping both groups conform to standard Emacs usage. The end result is an increase in efficiency for statistical programming and data analysis, over the usual tools.

R support contains code for editing R source code (syntactic indentation and highlighting of source code, partial evaluations of code, loading and error-checking of code, and source code revision maintenance) and documentation (syntactic indentation and highlighting of source code, sending examples to running ESS process, and previewing), interacting with an inferior R process from within Emacs (command-line editing, searchable command history, command-line completion of R object and file names, quick access to object and search lists, transcript recording, and an interface to the help system), and transcript manipulation (recording and saving transcript files, manipulating and editing saved transcripts, and re-evaluating commands from transcript files).

The latest stable version of ESS are available via CRAN or the [ESS web page](http://stat.ethz.ch/ESS/). The HTML version of the documentation can be found at <http://stat.ethz.ch/ESS/>.

ESS comes with detailed installation instructions.

For help with ESS, send email to ESS-help@stat.math.ethz.ch.

Please send bug reports and suggestions on ESS to ESS-bugs@stat.math.ethz.ch. The easiest way to do this from is within Emacs by typing `M-x ess-submit-bug-report` or using the [ESS] or [iESS] pulldown menus.

6.2 Should I run R from within Emacs?

Yes, *definitely*. Inferior R mode provides a readline/history mechanism, object name completion, and syntax-based highlighting of the interaction buffer using Font Lock mode, as well as a very convenient interface to the R help system.

Of course, it also integrates nicely with the mechanisms for editing R source using Emacs. One can write code in one Emacs buffer and send whole or parts of it for execution to R; this is helpful for both data analysis and programming. One can also seamlessly integrate with a revision control system, in order to maintain a log of changes in your programs and data, as well as to allow for the retrieval of past versions of the code.

In addition, it allows you to keep a record of your session, which can also be used for error recovery through the use of the transcript mode.

To specify command line arguments for the inferior R process, use `C-u M-x R` for starting R.

6.3 Debugging R from within Emacs

To debug R “from within Emacs”, there are several possibilities. To use the Emacs GUD (Grand Unified Debugger) library with the recommended debugger GDB, type `M-x gdb` and give the path to the R *binary* as argument. At the `gdb` prompt, set `R_HOME` and other environment variables as needed (using e.g. `set env R_HOME /path/to/R/`, but see also below), and start the binary with the desired arguments (e.g., `run --quiet`).

If you have ESS, you can do `C-u M-x R` `(RET)` `- d` `(SPC)` `g d b` `(RET)` to start an inferior R process with arguments ‘`-d gdb`’.

A third option is to start an inferior R process via ESS (`M-x R`) and then start GUD (`M-x gdb`) giving the R binary (using its full path name) as the program to debug. Use the program `ps` to find the process number of the currently running R process then use the `attach` command in `gdb` to attach it to that process. One advantage of this method is that you have separate `*R*` and `*gud-gdb*` windows. Within the `*R*` window you have all the ESS facilities, such as object-name completion, that we know and love.

When using GUD mode for debugging from within Emacs, you may find it most convenient to use the directory with your code in it as the current working directory and then make a symbolic link from that directory to the R binary. That way ‘`.gdbinit`’ can stay in the directory with the code and be used to set up the environment and the search paths for the source, e.g. as follows:

```
set env R_HOME /opt/R
set env R_PAPERSIZE letter
set env R_PRINTCMD lpr
dir /opt/R/src/appl
dir /opt/R/src/main
dir /opt/R/src/nmath
dir /opt/R/src/unix
```

7 R Miscellanea

7.1 How can I set components of a list to NULL?

You can use

```
x[i] <- list(NULL)
```

to set component `i` of the list `x` to `NULL`, similarly for named components. Do not set `x[i]` or `x[[i]]` to `NULL`, because this will remove the corresponding component from the list.

For dropping the row names of a matrix `x`, it may be easier to use `rownames(x) <- NULL`, similarly for column names.

7.2 How can I save my workspace?

`save.image()` saves the objects in the user's `.GlobalEnv` to the file `‘.RData’` in the R startup directory. (This is also what happens after `q("yes")`.) Using `save.image(file)` one can save the image under a different name.

7.3 How can I clean up my workspace?

To remove all objects in the currently active environment (typically `.GlobalEnv`), you can do

```
rm(list = ls(all = TRUE))
```

(Without `‘all = TRUE’`, only the objects with names not starting with a `‘.’` are removed.)

7.4 How can I get `eval()` and `D()` to work?

Strange things will happen if you use `eval(print(x), envir = e)` or `D(x^2, "x")`. The first one will either tell you that `"x"` is not found, or print the value of the wrong `x`. The other one will likely return zero if `x` exists, and an error otherwise.

This is because in both cases, the first argument is evaluated in the calling environment first. The result (which should be an object of mode `"expression"` or `"call"`) is then evaluated or differentiated. What you (most likely) really want is obtained by “quoting” the first argument upon surrounding it with `expression()`. For example,

```
R> D(expression(x^2), "x")
2 * x
```

Although this behavior may initially seem to be rather strange, is perfectly logical. The “intuitive” behavior could easily be implemented, but problems would arise whenever the expression is contained in a variable, passed as a parameter, or is the result of a function call. Consider for instance the semantics in cases like

```
D2 <- function(e, n) D(D(e, n), n)
```

or

```
g <- function(y) eval(substitute(y), sys.frame(sys.parent(n = 2)))
g(a * b)
```

See the help page for `deriv()` for more examples.

7.5 Why do my matrices lose dimensions?

When a matrix with a single row or column is created by a subscripting operation, e.g., `row <- mat[2,]`, it is by default turned into a vector. In a similar way if an array with dimension, say, `2 x 3 x 1 x 4` is created by subscripting it will be coerced into a `2 x 3 x 4` array, losing the unnecessary dimension. After much discussion this has been determined to be a *feature*.

To prevent this happening, add the option `'drop = FALSE'` to the subscripting. For example,

```
rowmatrix <- mat[2, , drop = FALSE] # creates a row matrix
colmatrix <- mat[, 2, drop = FALSE] # creates a column matrix
a <- b[1, 1, 1, drop = FALSE]       # creates a 1 x 1 x 1 array
```

The `'drop = FALSE'` option should be used defensively when programming. For example, the statement

```
somerows <- mat[index, ]
```

will return a vector rather than a matrix if `index` happens to have length 1, causing errors later in the code. It should probably be rewritten as

```
somerows <- mat[index, , drop = FALSE]
```

7.6 How does autoloading work?

R has a special environment called `.AutoloadEnv`. Using `autoload(name, pkg)`, where `name` and `pkg` are strings giving the names of an object and the package containing it, stores some information in this environment. When R tries to evaluate `name`, it loads the corresponding package `pkg` and reevaluates `name` in the new package's environment.

Using this mechanism makes R behave as if the package was loaded, but does not occupy memory (yet).

See the help page for `autoload()` for a very nice example.

7.7 How should I set options?

The function `options()` allows setting and examining a variety of global “options” which affect the way in which R computes and displays its results. The variable `.Options` holds the current values of these options, but should never directly be assigned to unless you want to drive yourself crazy—simply pretend that it is a “read-only” variable.

For example, given

```
test1 <- function(x = pi, dig = 3) {
  oo <- options(digits = dig); on.exit(options(oo));
  cat(.Options$digits, x, "\n")
}
test2 <- function(x = pi, dig = 3) {
  .Options$digits <- dig
  cat(.Options$digits, x, "\n")
}
```

we obtain:

```
R> test1()
3 3.14
R> test2()
3 3.141593
```

What is really used is the *global* value of `.Options`, and using `options(OPT = VAL)` correctly updates it. Local copies of `.Options`, either in `.GlobalEnv` or in a function environment (frame), are just silently disregarded.

7.8 How do file names work in Windows?

As R uses C-style string handling, ‘\’ is treated as an escape character, so that for example one can enter a newline as ‘\n’. When you really need a ‘\’, you have to escape it with another ‘\’.

Thus, in filenames use something like "c:\\data\\money.dat". You can also replace ‘\’ by ‘/’ ("c:/data/money.dat").

7.9 Why does plotting give a color allocation error?

On an X11 device, plotting sometimes, e.g., when running `demo("image")`, results in “Error: color allocation error”. This is an X problem, and only indirectly related to R. It occurs when applications started prior to R have used all the available colors. (How many colors are available depends on the X configuration; sometimes only 256 colors can be used.)

One application which is notorious for “eating” colors is Netscape. If the problem occurs when Netscape is running, try (re)starting it with either the ‘`-no-install`’ (to use the default colormap) or the ‘`-install`’ (to install a private colormap) option.

You could also set the `colortype` of `X11()` to “`pseudo.cube`” rather than the default “`pseudo`”. See the help page for `X11()` for more information.

7.10 How do I convert factors to numeric?

It may happen that when reading numeric data into R (usually, when reading in a file), they come in as factors. If `f` is such a factor object, you can use

```
as.numeric(as.character(f))
```

to get the numbers back. More efficient, but harder to remember, is

```
as.numeric(levels(f))[as.integer(f)]
```

In any case, do not call `as.numeric()` or their likes directly for the task at hand (as `as.numeric()` or `unclass()` give the internal codes).

7.11 Are Trellis displays implemented in R?

The recommended package **lattice** (which is based on another recommended package, **grid**) provides graphical functionality that is compatible with most Trellis commands.

You could also look at `coplot()` and `dotchart()` which might do at least some of what you want. Note also that the R version of `pairs()` is fairly general and provides most of the functionality of `splom()`, and that R’s default plot method has an argument `asp` allowing to specify (and fix against device resizing) the aspect ratio of the plot.

(Because the word “Trellis” has been claimed as a trademark we do not use it in R. The name “lattice” has been chosen for the R equivalent.)

7.12 What are the enclosing and parent environments?

Inside a function you may want to access variables in two additional environments: the one that the function was defined in (“enclosing”), and the one it was invoked in (“parent”).

If you create a function at the command line or load it in a package its enclosing environment is the global workspace. If you define a function `f()` inside another function `g()` its enclosing environment is the environment inside `g()`. The enclosing environment for a function is fixed when the function is created. You can find out the enclosing environment for a function `f()` using `environment(f)`.

The “parent” environment, on the other hand, is defined when you invoke a function. If you invoke `lm()` at the command line its parent environment is the global workspace, if you invoke it inside a function `f()` then its parent environment is the environment inside `f()`. You can find out the parent environment for an invocation of a function by using `parent.frame()` or `sys.frame(sys.parent())`.

So for most user-visible functions the enclosing environment will be the global workspace, since that is where most functions are defined. The parent environment will be wherever the function happens to be called from. If a function `f()` is defined inside another function `g()` it will probably be used inside `g()` as well, so its parent environment and enclosing environment will probably be the same.

Parent environments are important because things like model formulas need to be evaluated in the environment the function was called from, since that’s where all the variables will be available. This relies on the parent environment being potentially different with each invocation.

Enclosing environments are important because a function can use variables in the enclosing environment to share information with other functions or with other invocations of itself (see the section on lexical scoping). This relies on the enclosing environment being the same each time the function is invoked. (In C this would be done with static variables.)

Scoping *is* hard. Looking at examples helps. It is particularly instructive to look at examples that work differently in R and S and try to see why they differ. One way to describe the scoping differences between R and S is to say that in S the enclosing environment is *always* the global workspace, but in R the enclosing environment is wherever the function was created.

7.13 How can I substitute into a plot label?

Often, it is desired to use the value of an R object in a plot label, e.g., a title. This is easily accomplished using `paste()` if the label is a simple character string, but not always obvious in case the label is an expression (for refined mathematical annotation). In such a case, either use `parse()` on your pasted character string or use `substitute()` on an expression. For example, if `ahat` is an estimator of your parameter a of interest, use

```
title(substitute(hat(a) == ahat, list(ahat = ahat)))
```

(note that it is ‘==’ and not ‘=’). Sometimes `bquote()` gives a more compact form, e.g.,

```
title(bquote(hat(a) = .(ahat)))
```

where subexpressions enclosed in ‘.(.)’ are replaced by their values.

There are more worked examples in the mailing list archives.

7.14 What are valid names?

When creating data frames using `data.frame()` or `read.table()`, R by default ensures that the variable names are syntactically valid. (The argument ‘`check.names`’ to these functions controls whether variable names are checked and adjusted by `make.names()` if needed.)

To understand what names are “valid”, one needs to take into account that the term “name” is used in several different (but related) ways in the language:

1. A *syntactic name* is a string the parser interprets as this type of expression. It consists of letters, numbers, and the dot and (for version of R at least 1.9.0) underscore characters, and starts with either a letter or a dot not followed by a number. Reserved words are not syntactic names.
2. An *object name* is a string associated with an object that is assigned in an expression either by having the object name on the left of an assignment operation or as an argument to the `assign()` function. It is usually a syntactic name as well, but can be any non-empty string if it is quoted (and it is always quoted in the call to `assign()`).
3. An *argument name* is what appears to the left of the equals sign when supplying an argument in a function call (for example, `f(trim=.5)`). Argument names are also usually syntactic names, but again can be anything if they are quoted.
4. An *element name* is a string that identifies a piece of an object (a component of a list, for example.) When it is used on the right of the ‘\$’ operator, it must be a syntactic name, or quoted. Otherwise, element names can be any strings. (When an object is used as a database, as in a call to `eval()` or `attach()`, the element names become object names.)
5. Finally, a *file name* is a string identifying a file in the operating system for reading, writing, etc. It really has nothing much to do with names in the language, but it is traditional to call these strings file “names”.

7.15 Are GAMs implemented in R?

Package **gam** from CRAN implements all the Generalized Additive Models (GAM) functionality as described in the GAM chapter of the White Book. In particular, it implements backfitting with both local regression and smoothing splines, and is extendable. There is a `gam()` function for GAMs in package **mgcv**, but it is not an exact clone of what is described in the White Book (no `lo()` for example). Package **gss** can fit spline-based GAMs too. And if you can accept regression splines you can use `glm()`. For gaussian GAMs you can use `bruto()` from package **mda**.

7.16 Why is the output not printed when I `source()` a file?

Most R commands do not generate any output. The command

```
1+1
```

computes the value 2 and returns it; the command

```
summary(glm(y~x+z, family=binomial))
```

fits a logistic regression model, computes some summary information and returns an object of class "summary.glm" (see [Section 8.1 \[How should I write summary methods?\]](#), page 104).

If you type '1+1' or 'summary(glm(y~x+z, family=binomial))' at the command line the returned value is automatically printed (unless it is `invisible()`), but in other circumstances, such as in a `source()`d file or inside a function it isn't printed unless you specifically print it.

To print the value use

```
print(1+1)
```

or

```
print(summary(glm(y~x+z, family=binomial)))
```

instead, or use `source(file, echo=TRUE)`.

7.17 Why does `outer()` behave strangely with my function?

As the help for `outer()` indicates, it does not work on arbitrary functions the way the `apply()` family does. It requires functions that are vectorized to work elementwise on arrays. As you can see by looking at the code, `outer(x, y, FUN)` creates two large vectors containing every possible combination of elements of `x` and `y` and then passes this to `FUN` all at once. Your function probably cannot handle two large vectors as parameters.

If you have a function that cannot handle two vectors but can handle two scalars, then you can still use `outer()` but you will need to wrap your function up first, to simulate vectorized behavior. Suppose your function is

```
foo <- function(x, y, happy) {
  stopifnot(length(x) == 1, length(y) == 1) # scalars only!
  (x + y) * happy
}
```

If you define the general function

```
wrapper <- function(x, y, my.fun, ...) {
  sapply(seq(along = x), FUN = function(i) my.fun(x[i], y[i], ...))
}
```

then you can use `outer()` by writing, e.g.,

```
outer(1:4, 1:2, FUN = wrapper, my.fun = foo, happy = 10)
```

7.18 Why does the output from `anova()` depend on the order of factors in the model?

In a model such as `~A+B+A:B`, R will report the difference in sums of squares between the models `~1`, `~A`, `~A+B` and `~A+B+A:B`. If the model were `~B+A+A:B`, R would report differences between `~1`, `~B`, `~A+B`, and `~A+B+A:B`. In the first case the sum of squares for `A` is comparing `~1` and `~A`, in the second case it is comparing `~B` and `~B+A`. In a non-orthogonal design (i.e., most unbalanced designs) these comparisons are (conceptually and numerically) different.

Some packages report instead the sums of squares based on comparing the full model to the models with each factor removed one at a time (the famous 'Type III sums of squares')

from SAS, for example). These do not depend on the order of factors in the model. The question of which set of sums of squares is the Right Thing provokes low-level holy wars on R-help from time to time.

There is no need to be agitated about the particular sums of squares that R reports. You can compute your favorite sums of squares quite easily. Any two models can be compared with `anova(model1, model2)`, and `drop1(model1)` will show the sums of squares resulting from dropping single terms.

7.19 How do I produce PNG graphics in batch mode?

Under Unix, the `png()` device uses the X11 driver, which is a problem in batch mode or for remote operation. If you have Ghostscript you can use `bitmap()`, which produces a PostScript file then converts it to any bitmap format supported by Ghostscript. On some installations this produces ugly output, on others it is perfectly satisfactory. In theory one could also use Xvfb from X.Org, which is an X11 server that does not require a screen; and the **GDD** package from CRAN, which produces PNG, JPEG and GIF bitmaps without X11.

7.20 How can I get command line editing to work?

The Unix command-line interface to R can only provide the inbuilt command line editor which allows recall, editing and re-submission of prior commands provided that the GNU readline library is available at the time R is configured for compilation. Note that the ‘development’ version of readline including the appropriate headers is needed: users of Linux binary distributions will need to install packages such as `libreadline-dev` (Debian) or `readline-devel` (Red Hat).

7.21 How can I turn a string into a variable?

If you have

```
varname <- c("a", "b", "d")
```

you can do

```
get(varname[1]) + 2
```

for

```
a + 2
```

or

```
assign(varname[1], 2 + 2)
```

for

```
a <- 2 + 2
```

or

```
eval(substitute(lm(y ~ x + variable),
                 list(variable = as.name(varname[1])))
```

for

```
lm(y ~ x + a)
```

At least in the first two cases it is often easier to just use a list, and then you can easily index it by name

```
vars <- list(a = 1:10, b = rnorm(100), d = LETTERS)
vars[["a"]]
```

without any of this messing about.

7.22 Why do lattice/trellis graphics not work?

The most likely reason is that you forgot to tell R to display the graph. Lattice functions such as `xyplot()` create a graph object, but do not display it (the same is true of Trellis graphics in S-PLUS). The `print()` method for the graph object produces the actual display. When you use these functions interactively at the command line, the result is automatically printed, but in `source()` or inside your own functions you will need an explicit `print()` statement.

7.23 How can I sort the rows of a data frame?

To sort the rows within a data frame, with respect to the values in one or more of the columns, simply use `order()` (e.g., `DF[order(DF$a, DF[["b"]]),]` to sort the data frame `DF` on columns named `a` and `b`).

7.24 Why does the `help.start()` search engine not work?

The browser-based search engine in `help.start()` utilizes a Java applet. In order for this to function properly, a compatible version of Java must be installed on your system and linked to your browser, and both Java *and* JavaScript need to be enabled in your browser.

There have been a number of compatibility issues with versions of Java and of browsers. See [section “Enabling search in HTML help” in *R Installation and Administration*](#), for further details.

7.25 Why did my `.Rprofile` stop working when I updated R?

Did you read the ‘NEWS’ file? For functions that are not in the `base` package you need to specify the correct package namespace, since the code will be run *before* the packages are loaded. E.g.,

```
ps.options(horizontal = FALSE)
help.start()
```

needs to be

```
grDevices::ps.options(horizontal = FALSE)
utils::help.start()
```

(`graphics::ps.options(horizontal = FALSE)` in R 1.9.x).

7.26 Where have all the methods gone?

Many functions, particularly S3 methods, are now hidden in namespaces. This has the advantage that they cannot be called inadvertently with arguments of the wrong class, but it makes them harder to view.

To see the code for an S3 method (e.g., `[.terms]`) use


```
getS3method("[", "terms")
```

To see the code for an unexported function `foo()` in the namespace of package `"bar"` use `bar:::foo`. Don't use these constructions to call unexported functions in your own code—they are probably unexported for a reason and may change without warning.

7.27 How can I create rotated axis labels?

To rotate axis labels (using base graphics), you need to use `text()`, rather than `mtext()`, as the latter does not support `par("srt")`.

```
## Increase bottom margin to make room for rotated labels
par(mar = c(7, 4, 4, 2) + 0.1)
## Create plot with no x axis and no x axis label
plot(1 : 8, xaxt = "n", xlab = "")
## Set up x axis with tick marks alone
axis(1, labels = FALSE)
## Create some text labels
labels <- paste("Label", 1:8, sep = " ")
## Plot x axis labels at default tick marks
text(1:8, par("usr")[3] - 0.25, srt = 45, adj = 1,
     labels = labels, xpd = TRUE)
## Plot x axis label at line 6 (of 7)
mtext(1, text = "X Axis Label", line = 6)
```

When plotting the x axis labels, we use `srt = 45` for text rotation angle, `adj = 1` to place the right end of text at the tick marks, and `xpd = TRUE` to allow for text outside the plot region. You can adjust the value of the 0.25 offset as required to move the axis labels up or down relative to the x axis. See `?par` for more information.

Also see Figure 1 and associated code in Paul Murrell (2003), “Integrating grid Graphics Output with Base Graphics Output”, *R News*, **3/2**, 7–12.

7.28 Why is `read.table()` so inefficient?

By default, `read.table()` needs to read in everything as character data, and then try to figure out which variables to convert to numerics or factors. For a large data set, this takes considerable amounts of time and memory. Performance can substantially be improved by using the `colClasses` argument to specify the classes to be assumed for the columns of the table.

7.29 What is the difference between package and library?

A *package* is a standardized collection of material extending R, e.g. providing code, data, or documentation. A *library* is a place (directory) where R knows to find packages it can use (i.e., which were *installed*). R is told to use a package (to “load” it and add it to the search path) via calls to the function `library`. I.e., `library()` is employed to load a package from libraries containing packages.

See [Chapter 5 \[R Add-On Packages\]](#), page 22, for more details. See also Uwe Ligges (2003), “R Help Desk: Package Management”, *R News*, **3/3**, 37–39.

7.30 I installed a package but the functions are not there

To actually *use* the package, it needs to be *loaded* using `library()`.

See Chapter 5 [R Add-On Packages], page 22 and Section 7.29 [What is the difference between package and library?], page 100 for more information.

7.31 Why doesn't R think these numbers are equal?

The only numbers that can be represented exactly in R's numeric type are integers and fractions whose denominator is a power of 2. Other numbers have to be rounded to (typically) 53 binary digits accuracy. As a result, two floating point numbers will not reliably be equal unless they have been computed by the same algorithm, and not always even then. For example

```
R> a <- sqrt(2)
R> a * a == 2
[1] FALSE
R> a * a - 2
[1] 4.440892e-16
```

The function `all.equal()` compares two objects using a numeric tolerance of `.Machine$double.eps ^ 0.5`. If you want much greater accuracy than this you will need to consider error propagation carefully.

For more information, see e.g. David Goldberg (1991), "What Every Computer Scientist Should Know About Floating-Point Arithmetic", *ACM Computing Surveys*, **23/1**, 5–48, also available via http://docs.sun.com/source/806-3568/ncg_goldberg.html.

7.32 How can I capture or ignore errors in a long simulation?

Use `try()`, which returns an object of class "try-error" instead of an error, or preferably `tryCatch()`, where the return value can be configured more flexibly. For example

```
beta[i,] <- tryCatch(coef(lm(formula, data)),
                    error = function(e) rep(NA, 4))
```

would return the coefficients if the `lm()` call succeeded and would return `c(NA, NA, NA, NA)` if it failed (presumably there are supposed to be 4 coefficients in this example).

7.33 Why are powers of negative numbers wrong?

You are probably seeing something like

```
R> -2^2
[1] -4
```

and misunderstanding the precedence rules for expressions in R. Write

```
R> (-2)^2
[1] 4
```

to get the square of -2 .

The precedence rules are documented in `?Syntax`, and to see how R interprets an expression you can look at the parse tree

```
R> as.list(quote(-2^2))
[[1]]
'-'

[[2]]
2^2
```

7.34 How can I save the result of each iteration in a loop into a separate file?

One way is to use `paste()` (or `sprintf()`) to concatenate a stem filename and the iteration number while `file.path()` constructs the path. For example, to save results into files ‘result1.rda’, ..., ‘result100.rda’ in the subdirectory ‘Results’ of the current working directory, one can use

```
for(i in 1:100) {
  ## Calculations constructing "some_object" ...
  fp <- file.path("Results", paste("result", i, ".rda", sep = ""))
  save(list = "some_object", file = fp)
}
```

7.35 Why are *p*-values not displayed when using `lmer()`?

Doug Bates has kindly provided an extensive response in a post to the r-help list, which can be reviewed at <https://stat.ethz.ch/pipermail/r-help/2006-May/094765.html>.

7.36 Why are there unwanted lines between polygons in PDF output viewed in Adobe Reader?

Output from `polygon()` (and other functions calling `polygon()`) with the argument `border=NA` or `border="transparent"` should suppress border lines between polygons for all graphics devices.

PDF output from R can be made in many ways, both directly, and through for example Postscript or Windows Metafiles converted to PDF in external software. In Adobe Reader, the default setting for line art, such as polygons, is to smooth, which produces the impression of thin borders. Adobe Reader does this both for PDF files written by R or through other software.

This is irritating, especially when using Adobe Reader for presentation. The unwanted effect can be removed by turning off smoothing for line art: use the ‘Edit | Preferences | Page Display | Smooth line art’ menu in Adobe Reader 7.0.

7.37 Why does backslash behave strangely inside strings?

This question most often comes up in relation to file names (see [Section 7.8 \[How do file names work in Windows?\]](#), page 94) but it also happens that people complain that they cannot seem to put a single ‘\’ character into a text string unless it happens to be followed by certain other characters.

To understand this, you have to distinguish between character strings and *representations* of character strings. Mostly, the representation in R is just the string with a single or double

quote at either end, but there are strings that cannot be represented that way, e.g., strings that themselves contains the quote character. So

```
> str <- "This \"text\" is quoted"
> str
[1] "This \"text\" is quoted"
> cat(str, "\n")
This "text" is quoted
```

The *escape sequences* ‘\’ and ‘\n’ represent a double quote and the newline character respectively. Printing text strings, using `print()` or by typing the name at the prompt will use the escape sequences too, but the `cat()` function will display the string as-is. Notice that ‘\n’ is a one-character string, not two; the backslash is not actually in the string, it is just generated in the printed representation.

```
> nchar("\n")
[1] 1
> substring("\n", 1, 1)
[1] "\n"
```

So how do you put a backslash in a string? For this, you have to escape the escape character. I.e., you have to double the backslash. as in

```
> cat("\\n", "\n")
\n
```

Some functions, particularly those involving regular expression matching, themselves use metacharacters, which may need to be escaped by the backslash mechanism. In those cases you may need a *quadruple* backslash to represent a single literal one.

In versions of R up to 2.4.1 an unknown escape sequence like ‘\p’ was quietly interpreted as just ‘p’. Current versions of R emit a warning.

8 R Programming

8.1 How should I write summary methods?

Suppose you want to provide a summary method for class "foo". Then `summary.foo()` should not print anything, but return an object of class "summary.foo", *and* you should write a method `print.summary.foo()` which nicely prints the summary information and invisibly returns its object. This approach is preferred over having `summary.foo()` print summary information and return something useful, as sometimes you need to grab something computed by `summary()` inside a function or similar. In such cases you don't want anything printed.

8.2 How can I debug dynamically loaded code?

Roughly speaking, you need to start R inside the debugger, load the code, send an interrupt, and then set the required breakpoints.

See [section "Finding entry points in dynamically loaded code" in *Writing R Extensions*](#).

8.3 How can I inspect R objects when debugging?

The most convenient way is to call `R_PV` from the symbolic debugger.

See [section "Inspecting R objects when debugging" in *Writing R Extensions*](#).

8.4 How can I change compilation flags?

Suppose you have C code file for dynloading into R, but you want to use `R CMD SHLIB` with compilation flags other than the default ones (which were determined when R was built).

Starting with R 2.1.0, users can provide personal Makevars configuration files in `‘$HOME/.R’` to override the default flags. See [section "Add-on packages" in *R Installation and Administration*](#).

For earlier versions of R, you could change the file `‘$R_HOME/etc/Makeconf’` to reflect your preferences, or (at least for systems using GNU Make) override them by the environment variable `MAKEFLAGS`. See [section "Creating shared objects" in *Writing R Extensions*](#).

8.5 How can I debug S4 methods?

Use the `trace()` function with argument `signature=` to add calls to the browser or any other code to the method that will be dispatched for the corresponding signature. See `?trace` for details.

9 R Bugs

9.1 What is a bug?

If R executes an illegal instruction, or dies with an operating system error message that indicates a problem in the program (as opposed to something like “disk full”), then it is certainly a bug. If you call `.C()`, `.Fortran()`, `.External()` or `.Call()` (or `.Internal()`) yourself (or in a function you wrote), you can always crash R by using wrong argument types (modes). This is not a bug.

Taking forever to complete a command can be a bug, but you must make certain that it was really R’s fault. Some commands simply take a long time. If the input was such that you *know* it should have been processed quickly, report a bug. If you don’t know whether the command should take a long time, find out by looking in the manual or by asking for assistance.

If a command you are familiar with causes an R error message in a case where its usual definition ought to be reasonable, it is probably a bug. If a command does the wrong thing, that is a bug. But be sure you know for certain what it ought to have done. If you aren’t familiar with the command, or don’t know for certain how the command is supposed to work, then it might actually be working right. For example, people sometimes think there is a bug in R’s mathematics because they don’t understand how finite-precision arithmetic works. Rather than jumping to conclusions, show the problem to someone who knows for certain. Unexpected results of comparison of decimal numbers, for example $0.28 * 100 \neq 28$ or $0.1 + 0.2 \neq 0.3$, are not a bug. See [Section 7.31 \[Why doesn’t R think these numbers are equal?\]](#), page 101, for more details.

Finally, a command’s intended definition may not be best for statistical analysis. This is a very important sort of problem, but it is also a matter of judgment. Also, it is easy to come to such a conclusion out of ignorance of some of the existing features. It is probably best not to complain about such a problem until you have checked the documentation in the usual ways, feel confident that you understand it, and know for certain that what you want is not available. If you are not sure what the command is supposed to do after a careful reading of the manual this indicates a bug in the manual. The manual’s job is to make everything clear. It is just as important to report documentation bugs as program bugs. However, we know that the introductory documentation is seriously inadequate, so you don’t need to report this.

If the online argument list of a function disagrees with the manual, one of them must be wrong, so report the bug.

9.2 How to report a bug

When you decide that there is a bug, it is important to report it and to report it in a way which is useful. What is most useful is an exact description of what commands you type, starting with the shell command to run R, until the problem happens. Always include the version of R, machine, and operating system that you are using; type `version` in R to print this.

The most important principle in reporting a bug is to report *facts*, not hypotheses or categorizations. It is always easier to report the facts, but people seem to prefer to strain

to posit explanations and report them instead. If the explanations are based on guesses about how R is implemented, they will be useless; others will have to try to figure out what the facts must have been to lead to such speculations. Sometimes this is impossible. But in any case, it is unnecessary work for the ones trying to fix the problem.

For example, suppose that on a data set which you know to be quite large the command

```
R> data.frame(x, y, z, monday, tuesday)
```

never returns. Do not report that `data.frame()` fails for large data sets. Perhaps it fails when a variable name is a day of the week. If this is so then when others got your report they would try out the `data.frame()` command on a large data set, probably with no day of the week variable name, and not see any problem. There is no way in the world that others could guess that they should try a day of the week variable name.

Or perhaps the command fails because the last command you used was a method for `"["()` that had a bug causing R's internal data structures to be corrupted and making the `data.frame()` command fail from then on. This is why others need to know what other commands you have typed (or read from your startup file).

It is very useful to try and find simple examples that produce apparently the same bug, and somewhat useful to find simple examples that might be expected to produce the bug but actually do not. If you want to debug the problem and find exactly what caused it, that is wonderful. You should still report the facts as well as any explanations or solutions. Please include an example that reproduces the problem, preferably the simplest one you have found.

Invoking R with the `'--vanilla'` option may help in isolating a bug. This ensures that the site profile and saved data files are not read.

Before you actually submit a bug report, you should check whether the bug has already been reported and/or fixed. First, try the "Search Existing Reports" facility in the Bug Tracking page at <http://bugs.R-project.org/>. Second, consult <https://svn.R-project.org/R/trunk/NEWS>, which records changes that will appear in the *next* release of R, including some bug fixes that do not appear in Bug Tracking. (Windows users should additionally consult <https://svn.R-project.org/R/trunk/src/gnuwin32/CHANGES>.) Third, if possible try the current r-patched or r-devel version of R. If a bug has already been reported or fixed, please do not submit further bug reports on it. Finally, check carefully whether the bug is with R, or a contributed package. Bug reports on contributed packages should be sent first to the package maintainer, and only submitted to the R-bugs repository by package maintainers, mentioning the package in the subject line.

On Unix systems a bug report can be generated using the function `bug.report()`. This automatically includes the version information and sends the bug to the correct address. Alternatively the bug report can be emailed to R-bugs@R-project.org or submitted to the Web page at <http://bugs.R-project.org/>. Please try including results of `sessionInfo()` in your bug report.

There is a section of the bug repository for suggestions for enhancements for R labelled `'wishlist'`. Suggestions can be submitted in the same ways as bugs, but please ensure that the subject line makes clear that this is for the wishlist and not a bug report, for example by starting with `'Wishlist:'`.

Comments on and suggestions for the Windows port of R should be sent to R-windows@R-project.org.

Corrections to and comments on message translation should be sent to the last translator (listed at the top of the appropriate ‘.po’ file) or to the translation team as listed at <http://developer.R-project.org/TranslationTeams.html>.

10 Acknowledgments

Of course, many many thanks to Robert and Ross for the R system, and to the package writers and porters for adding to it.

Special thanks go to Doug Bates, Peter Dalgaard, Paul Gilbert, Stefano Iacus, Fritz Leisch, Jim Lindsey, Thomas Lumley, Martin Maechler, Brian D. Ripley, Anthony Rossini, and Andreas Weingessel for their comments which helped me improve this FAQ.

More to come soon . . .