



[Home](#) [About](#) [Search](#) [Changes](#) [Unused Pages](#) [Undefined Pages](#) [Index](#) [License](#)

[Edit this page](#)

JBossESBDeadLetterService

Your trail: [JBossESB](#) | [JBossESBQuickStart](#) | [JBossESBDeadLetterService](#) | [JBossESBQuickStart](#) | [JBossESBContentBasedRouting](#) | [JBossESBContentBasedRouting](#) | [JBossESBWireTap](#)

JBossESB - JBossESBEIP - Dead Letter Service

Pattern Description



The Dead Letter Service (DLS) has a category="JBossESB-Internal" and name="[DeadLetterService?](#)", and is a standard service to which message will be routed when delivery to the intended destination fails.

Implementation

By default the DLS is configured to store the message in the [Message Store](#), with category 'DLQ', status 'undelivered'.

Configuration

The Dead Letter Service is configured in the jbossesb.esb archive, which contains services used by the [JBossESB](#) itself. The [configuration](#) uses the [MessagePersister](#) to persist messages to the [Message Store](#). Note that the service can be configured to for instance deliver the message to a DLQ JMS Queue.

More information

- [eip.com](#)
- Quickstarts:
 - [deadletter](#)

Attachments:

[DeadLetterService.png](#)



821 bytes

[Go to top](#) [Edit this page](#) [More info...](#) [Attach file...](#)

This page last changed on 14-Jun-2007 19:07:36 EDT by kurt.stam@jboss.com.



© 2007 Red Hat Middleware, LLC. All rights reserved. [Privacy Policy](#)